

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。




Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/25/15	

APPROVED: _____ TITLE: _____
 DATE: _____

CUSTOM CABLE ASSEMBLIES ARE NON-CANCELLABLE/NON-RETURNABLE



PIN ASSIGNMENT
(TIA 568A)

P1	P2
1	1 White/Green
2	2 Green
3	3 White/Drange
6	6 Drange
4	4 Blue
5	5 White/Blue
7	7 White/Brown
8	8 Brown

NPC-5E-XXX-XX

LENGTH	CODE	COLOR	CODE
12.0" ±.39" [305±10]	001	BLUE	BU
36.0" ±1.2" [915±20]	003	ORANGE	OR
60.0" ±1.5" [1,525±40]	005	WHITE	WT
84.0" ±1.9" [2,135±50]	007	BLACK	BK
120.0" ±2.4" [3,050±50]	010	RED	RD
168.0" ±2.4" [4,270±60]	014	GREEN	GR
300.0" ±2.4" [7,625±60]	025	GRAY	GY
600.0" ±2.7" [15,250±70]	050	PURPLE	PU
1,200.0" ±2.7" [30,500±70]	100		

SPECIFICATIONS:

Plugs: RJ45, 8P8C, CAT 5e Plug, Long Body, Polycarbonate, Rated UL94V-0, Gold plated.
 Cable: Cat 5e, UTP 24 AWG X 4P, Stranded bare Copper, 350MHz O.D.: 5.4mm ±0.2mm, UL, cUL & ETL verified
 Jacket color (See Chart)
 Electrical: Hi-Pot: 300V DC / 10ms
 100% tested for Open, shorts and crossed wires
 Environmental:
 Lead free, RoHS compliant.

ADAM TECH
 909 Railway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

RJ45 NETWORK PATCH CABLE, CAT 5e,
 350MHz, UTP, STRANDED

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED	INCHES	HOLES
.X ±.10	ØXX ±.10	
.XX ±.020	ØXXX ±.015	
.XXX ±.015	ØXXXX ±.010	

APPROVALS	DATE
DRAWN SS	3/25/15
CHECKED	
APPROVED	

SIZE X	PART NO. NPC-5E-XXX-XX	REV. -
REF:	SCALE: NTS	SHEET 1 OF 1