

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

STANDARD PLUGGABLE PRINTED CIRCUIT US Pin Spacing^a Screw-Cage Clamp Plug

For standard industrial plug-in applications where multiple wire-to-board connections must be made quickly and simultaneously.

Reduce wiring mistakes, downtime and facilitate troubleshooting. Simply unplug defective board and plug in a new one.

Horizontal and Vertical, 45° and Double Level Headers are available. Headers are available in open and closed end designs. Refer to page 126 to 129.

- Multipole, Single Mold Construction
- Industry Standard Compatible
- Locking Tabs Prevent Unplugging
- Optional Keying Prevents Mislugging^b
- Housing Material: Polyamide 6.6
- Standard Color: Green

^aBlocks with metric pin spacing begin on page 132.



AKZ950

Wire Entry in Same Direction as Plug-In

Pole Spacing 5.08mm (.200)
Stripping Length 7mm (.276)
Screw Hole Diameter 3.5mm (.138)


Use with STLZ950, STLZ955, STLZ970,
STLZ975, STLZ11, STLZ990 Headers

Ratings IEC/VDE	Wire Range	Current	Voltage
UL (File No. E101811)	0.5-2.5mm ²	12A	250V
CSA (File No. LR68503)	22-12 AWG	15A	300V
	22-14 AWG	15A	300V

Ordering Information	No. of Poles	Type	Cat. No.	Length L mm (in.)	Std. Pk.
Plug, US (Inch) Pole Spacing	2	AKZ950/2	37.002	10.16 (.40)	100
	3	AKZ950/3	37.003	15.24 (.60)	100
	4	AKZ950/4	37.004	20.32 (.80)	50
	5	AKZ950/5	37.005	25.40 (1.00)	50
	6	AKZ950/6	37.006	30.48 (1.20)	50
	7	AKZ950/7	37.007	35.56 (1.40)	30

8	AKZ950/8	37.008	40.64 (1.60)	30
9	AKZ950/9	37.009	45.72 (1.80)	30
10	AKZ950/10	37.010	50.80 (2.00)	30
11	AKZ950/11	37.011	55.88 (2.20)	20
12	AKZ950/12	37.012	60.98 (2.40)	20
13	AKZ950/13	37.013	66.04 (2.60)	20
14	AKZ950/14	37.014	71.14 (2.80)	20
15	AKZ950/15	37.015	76.20 (3.00)	20
16	AKZ950/16	37.016	81.28 (3.20)	15
17	AKZ950/17	37.017	86.36 (3.40)	15
18	AKZ950/18	37.018	91.44 (3.60)	15
19	AKZ950/19	37.019	96.52 (3.80)	15
20	AKZ950/20	37.020	101.60 (4.00)	15
21	AKZ950/21	37.021	106.66 (4.20)	10
22	AKZ950/22	37.022	111.76 (4.40)	10
23	AKZ950/23	37.023	116.84 (4.60)	10
24	AKZ950/24	37.024	121.92 (4.80)	10

Dimensions				
mm	in.	mm	in.	
2.70	0.106	9.00	0.354	
3.10	0.039	15.00	0.600	
5.08	0.200	17.30	0.039	



*For Keying, refer to Accessories on Page146