

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Feed-Through

Altech "U" Series Universal Rail Mounting Standard Screw Clamp Feed through terminals are the most versatile terminals for wire-to-wire connection in control, automation, instrumentation and power distribution applications. A special design feature on the flexible foot enables easy mounting and dismantling from the DIN Rail with the help of a screwdriver.

The CTC4U Tab Connection terminals offer quick connection possibility. These terminal blocks are suited for standard 'Fast On' type lugs.

The connection is achieved by pushing the lug / ferrule onto the tab blade of the terminal block.

CTC4U is used primarily in railway systems.

A nice alternative to 'Fast On' style barrier strips.




CTS2.5U-N



CTS4U-N



CTC4U



Terminal Width	5 mm			6 mm			NEW	
Height x Length	45 x 43 mm			45 x 43 mm			49.5 x 47 mm	
Stripping Length	8 mm			8 mm			9 mm	
Insulation Material	Polyamide 6.6			Polyamide 6.6			Polyamide 6.6	
Type of Connection	2 screw clamps & 1 tapped hole for cross connect.			2 screw clamps & 1 tapped hole for cross connect.			5 tab connection points and 1 tapped hole for cross connection	
Approvals								
Wire Range	22-12 AWG	0.2-2.5 sq.mm	22-12 AWG	22-10 AWG	0.2-4 sq.mm	22-10 AWG		
Rated Cross Section	1 conductor per clamp 2 same size conductors						0.25-4.0 sq.mm 24-12 AWG 0.25-2.5 sq.mm 24-12 AWG	
Voltage Rating	600 V	1000 V	600 V	600 V	1000 V	600 V	300 V	
Current Rating	25 A	24 A	25 A	35/40 A*	32 A	35/40A*	32 A	
Torque	7 lb-in	0.4 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in		
Tab Blade Size							6.3 x 0.8	

Other Approvals						AEx eII Ex eII U						AEx eII Ex eII U	
-----------------	--	--	--	--	--	---------------------	--	--	--	--	--	---------------------	--

Terminal Block	CTS2.5U-N	100	CTS4U-N	100	CTS4U	100
----------------	------------------	-----	----------------	-----	--------------	-----

End Plate		EP2.5/4UN	50	EP2.5/4UN	50	EPCTC4U	50
Isolation Partition		PP2.5/4UN	50	PP2.5/4UN	50		
Separator Plate		SP2.5/4UN	100	SP2.5/4UN	100		

DIN Rail for ordering information refer to pages 90-91						
--	--	--	--	--	--	--

End Stop for ordering info. refer to page 92		CA702	50	CA702	50	CA702	50
		CA802	50	CA802	50	CA802	50

Internal Jumper		2 pole	CA721/2	100	CA722/2	100	CA727/2	100
		3 pole	CA721/3	50	CA722/3	50	CA727/3	50
		4 pole	CA721/4	50	CA722/4	50	CA727/4	50
		10 pole	CA721/10	10	CA722/10	10	CA727/10	10
		100 pole	CA721/100	10	CA722/100	10		

Insulated Internal Jumper		2 pole	CA741/2	100	CA742/2	100	CA747/2	100
		3 pole	CA741/3	50	CA742/3	50	CA747/3	50
		4 pole	CA741/4	50	CA742/4	50	CA747/4	50
		10 pole	CA741/10	10	CA742/10	10	CA747/10	10
		100 pole	CA741/100	10	CA742/100	10		

Current Bars		2 pole	CA703/01	100	CA703/01	100	CA703/1	100
		3 pole	CA704/01	100	CA704/01	100	CA704/1	100
		4 pole	CA705/01	100	CA705/01	100	CA705/1	100
		10 pole	CA731/10	100	CA732/10	100	CA732/10	100
		10 pole (breakable)	—		CA732/10-A	100	CA732/10-A	100
		100 pole	CA731/100	10	CA732/100	10	CA732/100	10

Shorting Sleeve & Screw		CA 707/S/Q/01	100	CA 707/S/Q/01	100	CA807/S/Q/01	100
-------------------------	--	---------------	-----	---------------	-----	--------------	-----

External Jumper		2 pole	CA717/2	100	CA714/2	100	CA707/TS/01	100
		3 pole	CA717/3	100	CA714/3	100		
		4 pole	CA717/4	100	CA714/4	100		
		10 pole	CA717/10	25	CA714/10	25		

Test Socket						CA707/TS/01	100
-------------	--	--	--	--	--	-------------	-----

Marking Tags		MT5	100	MT6	100	MT6	100
--------------	--	-----	-----	-----	-----	-----	-----

Mounting Handle

See page 91.



COLOR BLOCKS
(other than standard grey)

When ordering please add color suffix to Cat. No.

Example for color Red: **Cat.No./R**

Color	Ordering Suffix
Red	R
Yellow	Y
Blue	BU
Green	G

Consult Altech for availability:

Orange	O
Beige	BG
Dark Brown	DB
Black	BL
White	W

* 35A with one No. 10 AWG and 40A with two No. 12 AWG wires.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Altech:](#)

[CTS4U-N](#) [CTS2.5U-N](#)