


阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Standard Thick Film Chip Resistors



FEATURES

- Stability $\Delta R/R = 1\%$ for 1000 h at 70 °C
- 2 mm pitch packaging option for 0603 size
- Pure tin solder contacts on Ni barrier layer provides compatibility with lead (Pb)-free and lead containing soldering processes
- Metal glaze on high quality ceramic
- AEC-Q200 qualified
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE

STANDARD ELECTRICAL SPECIFICATIONS

| MODEL | SIZE | | RATED DISSIPATION $P_{70^\circ\text{C}}$ W | LIMITING ELEMENT VOLTAGE $U_{\text{max. AC/DC}}$ | TEMPERATURE COEFFICIENT ppm/K | TOLERANCE % | RESISTANCE RANGE Ω | SERIES |
|--------------|------|----------|--|---|----------------------------------|--------------------|------------------------------|-----------------|
| | INCH | METRIC | | | | | | |
| D10/CRCW0402 | 0402 | RR 1005M | 0.063 | 50 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 10M | E24; E96 E24 |
| | | | | | | | | |
| D11/CRCW0603 | 0603 | RR 1608M | 0.10 | 75 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 10M | E24; E96 E24 |
| | | | | | | | | |
| D12/CRCW0805 | 0805 | RR 2012M | 0.125 | 150 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 10M | E24; E96 E24 |
| | | | | | | | | |
| D25/CRCW1206 | 1206 | RR 3216M | 0.25 | 200 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 10M | E24; E96 E24 |
| | | | | | | | | |
| CRCW1210 | 1210 | RR 3225M | 0.5 | 200 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 10M | E24; E96 E24 |
| | | | | | | | | |
| CRCW1218 | 1218 | RR 3246M | 1.0 | 200 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 2M2 | E24; E96 E24 |
| | | | | | | | | |
| CRCW2010 | 2010 | RR 5025M | 0.75 | 400 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 10M | E24; E96 E24 |
| | | | | | | | | |
| CRCW2512 | 2512 | RR 6332M | 1.0 | 500 | ± 100 ± 200 | ± 1 ± 5 | 1R0 to 10M | E24; E96 E24 |
| | | | | | | | | |

Notes

- These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.
- Marking: See data sheet "Surface Mount Resistor Marking" (document number 20020).
- Power rating depends on the max. temperature at the solder point, the component placement density and the substrate material.





| TECHNICAL SPECIFICATIONS | | | | | | | | | |
|---|--------------------|------------------------|------------------|------------------|------------------|----------|----------|----------|----------|
| PARAMETER | UNIT | D10/ CRCW0402 | D11/ CRCW0603 | D12/ CRCW0805 | D25/ CRCW1206 | CRCW1210 | CRCW1218 | CRCW2010 | CRCW2512 |
| Rated dissipation $P_{70}^{(1)}$ | W | 0.063 | 0.1 | 0.125 | 0.25 | 0.5 | 1.0 | 0.75 | 1.0 |
| Limiting element voltage $U_{max. AC/DC}$ | V | 50 | 75 | 150 | 200 | 200 | 200 | 400 | 500 |
| Insulation voltage U_{ins} (1 min) | V | > 75 | > 100 | > 200 | > 300 | > 300 | > 300 | > 300 | > 300 |
| Insulation resistance | Ω | > 10^9 | | | | | | | |
| Category temperature range | $^{\circ}\text{C}$ | - 55 to + 155 | | | | | | | |
| Failure rate | h^{-1} | < 0.1×10^{-9} | | | | | | | |
| Weight | mg | 0.65 | 2 | 5.5 | 10 | 16 | 29.5 | 25.5 | 40.5 |

Note

⁽¹⁾ The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature of 155 °C is not exceeded.

| PART NUMBER AND PRODUCT DESCRIPTION | | | | | | | | | | | | | | | | | |
|--|---|---|---|---|---|--|---|---|---|-------------------------------------|---|---|---|---|---|--|--|
| Part Number: CRCW0603562RFKEC | | | | | | | | | | | | | | | | | |
| C | R | C | W | 0 | 6 | 0 | 3 | 5 | 6 | 2 | R | F | K | E | C | | |
| MODEL | | VALUE | | TOLERANCE | | TCR | | PACKAGING | | SPECIAL | | | | | | | |
| CRCW0402 CRCW0603 CRCW0805 CRCW1206 CRCW1210 CRCW1218 CRCW2010 CRCW2512 | | R = Decimal K = Thousand M = Million 0000 = Jumper | | F = $\pm 1.0\%$ J = $\pm 5.0\%$ Z = Jumper | | K = ± 100 ppm/K N = ± 200 ppm/K 0 = Jumper | | EA, EB, EC, ED, EE, EF, EG, EH, EI, EL, EK | | Up to 2 digits | | | | | | | |
| Product Description: D11/CRCW0603 100 562R 1 % ET6 e3 | | | | | | | | | | | | | | | | | |
| D11/CRCW0603 | | 100 | | 562R | | 1 % | | ET6 | | e3 | | | | | | | |
| MODEL | | TCR | | RESISTANCE VALUE | | TOLERANCE | | PACKAGING | | LEAD (Pb)-FREE | | | | | | | |
| D10/CRCW0402 D11/CRCW0603 D12/CRCW0805 D25/CRCW1206 CRCW1210 CRCW1218 CRCW2010 CRCW2512 | | ± 200 ppm/K ± 100 ppm/K | | 10R = 10 Ω 562R = 562 Ω 10K = 10 k Ω 1M0 = 1 M Ω 0R0 = Jumper | | $\pm 5\%$ $\pm 1\%$ | | ET1, ET2, ET3, ET4, ET5, ET6, ET7, ET8, ET9, ET4, E02, E67, E82 | | e3 = Pure tin termination finish | | | | | | | |

| PACKAGING | | | | | | | | |
|-----------|----------|----------|--|-------|-------|---------------|------|---------------|
| MODEL | CODE | QUANTITY | CARRIER TAPE | WIDTH | PITCH | REEL DIAMETER | | |
| CRCW0402 | ED = ET7 | 10 000 | Paper tape acc. to IEC 60068-3 Type I | 8 mm | 2 mm | 180 mm/7" | | |
| | EE = EF4 | 50 000 | | | | 330 mm/13" | | |
| CRCW0603 | EI = ET2 | 5000 | | 8 mm | 2 mm | 180 mm/7" | | |
| | ED = ET3 | 10 000 | | | | 180 mm/7" | | |
| | EL = ET4 | 20 000 | | | | 285 mm/11.25" | | |
| | EE = ET8 | 50 000 | | | | 330 mm/13" | | |
| | EA = ET1 | 5000 | | | | 8 mm | 4 mm | 180 mm/7" |
| | EB = ET5 | 10 000 | | | | | | 285 mm/11.25" |
| CRCW0805 | EC = ET6 | 20 000 | | 8 mm | 4 mm | 180 mm/7" | | |
| CRCW1206 | EA = ET1 | 5000 | | 8 mm | 4 mm | 285 mm/11.25" | | |
| | EB = ET5 | 10 000 | | | | 330 mm/13" | | |
| | EC = ET6 | 20 000 | | | | 180 mm/7" | | |
| CRCW1210 | EA = ET1 | 5000 | | 8 mm | 4 mm | 285 mm/11.25" | | |
| | EB = ET5 | 10 000 | 330 mm/13" | | | | | |
| | EC = ET6 | 20 000 | 180 mm/7" | | | | | |
| CRCW1218 | EK = ET9 | 4000 | Blister tape acc. to IEC 60068-3 Type II | 12 mm | 4 mm | 180 mm/7" | | |
| CRCW2010 | EF = E02 | 4000 | | 12 mm | 4 mm | 180 mm/7" | | |
| CRCW2512 | EG = E67 | 2000 | | 12 mm | 8 mm | 180 mm/7" | | |
| | EH = E82 | 4000 | 4 mm | | | 180 mm/7" | | |


DIMENSIONS


| SIZE | | DIMENSIONS in millimeters | | | | | SOLDER PAD DIMENSIONS in millimeters | | | | | |
|------|--------|--|-------------|-------------|---|-----------|--------------------------------------|-----|-----|----------------|-----|-----|
| | | | | | | | REFLOW SOLDERING | | | WAVE SOLDERING | | |
| INCH | METRIC | L | W | H | T1 | T2 | a | b | l | a | b | l |
| 0402 | 1005 | 1.0 ± 0.05 | 0.5 ± 0.05 | 0.35 ± 0.05 | 0.25 ± 0.05 | 0.2 ± 0.1 | 0.4 | 0.6 | 0.5 | | | |
| 0603 | 1608 | 1.55 ^{+0.10} / _{-0.05} | 0.85 ± 0.1 | 0.45 ± 0.05 | 0.3 ± 0.2 | 0.3 ± 0.2 | 0.5 | 0.9 | 1.0 | 0.9 | 0.9 | 1.0 |
| 0805 | 2012 | 2.0 ^{+0.20} / _{-0.10} | 1.25 ± 0.15 | 0.45 ± 0.05 | 0.3 ^{+0.20} / _{-0.10} | 0.3 ± 0.2 | 0.7 | 1.3 | 1.2 | 0.9 | 1.3 | 1.3 |
| 1206 | 3216 | 3.2 ^{+0.10} / _{-0.20} | 1.6 ± 0.15 | 0.55 ± 0.05 | 0.45 ± 0.2 | 0.4 ± 0.2 | 0.9 | 1.7 | 2.0 | 1.1 | 1.7 | 2.3 |
| 1210 | 3225 | 3.2 ± 0.2 | 2.5 ± 0.2 | 0.55 ± 0.05 | 0.45 ± 0.2 | 0.4 ± 0.2 | 0.9 | 2.5 | 2.0 | 1.1 | 2.5 | 2.2 |
| 1218 | 3246 | 3.2 ^{+0.10} / _{-0.20} | 4.6 ± 0.15 | 0.55 ± 0.05 | 0.45 ± 0.2 | 0.4 ± 0.2 | 1.05 | 4.9 | 1.9 | 1.25 | 4.8 | 1.9 |
| 2010 | 5025 | 5.0 ± 0.15 | 2.5 ± 0.15 | 0.6 ± 0.1 | 0.6 ± 0.2 | 0.6 ± 0.2 | 1.0 | 2.5 | 3.9 | 1.2 | 2.5 | 3.9 |
| 2512 | 6332 | 6.3 ± 0.2 | 3.15 ± 0.15 | 0.6 ± 0.1 | 0.6 ± 0.2 | 0.6 ± 0.2 | 1.0 | 3.2 | 5.2 | 1.2 | 3.2 | 5.2 |




FUNCTIONAL PERFORMANCE

Single Pulse




Maximum pulse load, single pulse; applicable if $\bar{P} \rightarrow 0$ and $n < 1000$ and $\dot{U} \leq \dot{U}_{max}$; for permissible resistance change equivalent to 8000 h operation

Continuous Pulse






Maximum pulse load, continuous pulses; applicable if $\bar{P} \leq P(9_{amb})$ and $\dot{U} \leq \dot{U}_{max}$; for permissible resistance change equivalent to 8000 h operation



Maximum pulse voltage, single and continuous pulses; applicable if $\hat{P} \leq \hat{P}_{max}$; for permissible resistance change equivalent to 8000 h operation

Derating



| TEST PROCEDURES AND REQUIREMENTS | | | | | |
|----------------------------------|----------------------------------|---------------------------------|---|---|--|
| EN 60115-1 CLAUSE | IEC 60068-2 TEST METHOD | TEST | PROCEDURE | REQUIREMENTS PERMISSIBLE CHANGE (ΔR) | |
| | | | | SIZE 0402 to 2512 | |
| | | | | STABILITY CLASS 1 OR BETTER | STABILITY CLASS 2 OR BETTER |
| | | | Stability for product types: | | |
| | | | D/CRCW e3 | 1 Ω to 10 M Ω | |
| 4.5 | - | Resistance | - | $\pm 1\%$ | $\pm 5\%$ |
| 4.7 | - | Voltage proof | $U = 1.4 \times U_{ins}$; 60 s | No flashover or breakdown | |
| 4.13 | - | Short time overload | $U = 2.5 \times \sqrt{P_{70} \times R}$ $\leq 2 \times U_{max.}$; duration: Acc. to style | $\pm (0.25\% R + 0.05 \Omega)$ | $\pm (0.5\% R + 0.05 \Omega)$ |
| 4.17.2 | 58 (Td) | Solderability | Solder bath method; Sn60Pb40 non activated flux; (235 \pm 5) $^{\circ}$ C (2 \pm 0.2) s | Good tinning ($\geq 95\%$ covered) no visible damage | |
| | | | Solder bath method; Sn96.5Ag3Cu0.5 non-activated flux; (245 \pm 5) $^{\circ}$ C (3 \pm 0.3) s | Good tinning ($\geq 95\%$ covered) no visible damage | |
| 4.8.4.2 | - | Temperature coefficient | (20/- 55/20) $^{\circ}$ C and (20/125/20) $^{\circ}$ C | ± 100 ppm/K | ± 200 ppm/K |
| 4.32 | 21 (Uu ₃) | Shear (adhesion) | RR 1608 and smaller: 9 N RR 2012 and larger: 45 N | No visible damage | |
| 4.33 | 21 (Uu ₁) | Substrate bending | Depth 2 mm; 3 times | No visible damage, no open circuit in bent position $\pm (0.25\% R + 0.05 \Omega)$ | |
| 4.19 | 14 (Na) | Rapid change of temperature | 30 min. at - 55 $^{\circ}$ C; 30 min. at 125 $^{\circ}$ C 5 cycles 1000 cycles | $\pm (0.25\% R + 0.05 \Omega)$ $\pm (1\% R + 0.05 \Omega)$ | $\pm (0.5\% R + 0.05 \Omega)$ $\pm (1\% R + 0.05 \Omega)$ |
| 4.23 | - | Climatic sequence: | - | | |
| 4.23.2 | 2 (Ba) | Dry heat | 125 $^{\circ}$ C; 16 h | | |
| 4.23.3 | 30 (Db) | Damp heat, cyclic | 55 $^{\circ}$ C; $\geq 90\%$ RH; 24 h; 1 cycle | | |
| 4.23.4 | 1 (Aa) | Cold | - 55 $^{\circ}$ C; 2 h | $\pm (1\% R + 0.05 \Omega)$ | $\pm (2\% R + 0.1 \Omega)$ |
| 4.23.5 | 13 (M) | Low air pressure | 1 kPa; (25 \pm 10) $^{\circ}$ C; 1 h | | |
| 4.23.6 | 30 (Db) | Damp heat, cyclic | 55 $^{\circ}$ C; $\geq 90\%$ RH; 24 h; 5 cycles | | |
| 4.23.7 | - | DC load | $U = \sqrt{P_{70} \times R}$ | | |
| 4.25.1 | - | Endurance at 70 $^{\circ}$ C | $U = \sqrt{P_{70} \times R} \leq U_{max.}$; 1.5 h on; 0.5 h off; | | |
| | | | 70 $^{\circ}$ C; 1000 h | $\pm (1\% R + 0.05 \Omega)$ | $\pm (2\% R + 0.1 \Omega)$ |
| | | | 70 $^{\circ}$ C; 8000 h | $\pm (2\% R + 0.1 \Omega)$ | $\pm (4\% R + 0.1 \Omega)$ |



| TEST PROCEDURES AND REQUIREMENTS | | | | | |
|----------------------------------|----------------------------------|--|---|---|-----------------------------------|
| EN 60115-1 CLAUSE | IEC 60068-2 TEST METHOD | TEST | PROCEDURE | REQUIREMENTS PERMISSIBLE CHANGE (ΔR) | |
| | | | | SIZE 0402 to 2512 | |
| | | | | STABILITY CLASS 1 OR BETTER | STABILITY CLASS 2 OR BETTER |
| | | | Stability for product types: | | |
| | | | D/CRCW e3 | 1 Ω to 10 M Ω | |
| 4.18.2 | 58 (Td) | Resistance to soldering heat | Solder bath method (260 \pm 5) $^{\circ}$ C; (10 \pm 1) s | \pm (0.25 % R + 0.05 Ω) | \pm (0.5 % R + 0.05 Ω) |
| 4.35 | - | Flamability, needle flame test | IEC 60695-11-5; 10 s | No burning after 30 s | |
| 4.24 | 78 (Cab) | Damp heat, steady state | (40 \pm 2) $^{\circ}$ C; (93 \pm 3) % RH; 56 days | \pm (1 % R + 0.05 Ω) | |
| 4.25.3 | - | Endurance at upper category temperature | 155 $^{\circ}$ C, 1000 h | \pm (1 % R + 0.05 Ω) | \pm (2 % R + 0.1 Ω) |
| 4.40 | - | Electrostatic discharge (human body model) | IEC 61340-3-1; 3 pos. + 3 neg. discharges; ESD voltage acc. to size | \pm (1 % R + 0.05 Ω) | |
| 4.29 | 45 (XA) | Component solvent resistance | Isopropyl alcohol; 50 $^{\circ}$ C; method 2 | No visible damage | |
| 4.30 | 45 (XA) | Solvent resistance of marking | Isopropyl alcohol; 50 $^{\circ}$ C; method 1, toothbrush | Marking legible, no visible damage | |
| 4.22 | 6 (Fc) | Vibration, endurance by sweeping | f = 10 Hz to 2000 Hz; x, y, z \leq 1.5 mm; A \leq 200 m/s ² ; 10 sweeps per axis | \pm (0.25 % R + 0.05 Ω) | \pm (0.5 % R + 0.05 Ω) |
| 4.37 | - | Periodic electric overload | $U = \sqrt{15 \times P_{70} \times R}$ $\leq 2 \times U_{max.}$; 0.1 s on; 2.5 s off; 1000 cycles | \pm (1 % R + 0.05 Ω) | |
| 4.27 | - | Single pulse high voltage overload, 10 μ s/700 μ s | $\hat{U} = 10 \times \sqrt{P_{70} \times R}$ $\leq 2 \times U_{max.}$; 10 pulses | \pm (1 % R + 0.05 Ω) | |

All tests are carried out in accordance with the following specifications:

- EN 60115-1, generic specification
- EN 140400, sectional specification
- EN 140401-802, detail specification
- IEC 60068-2-x, environmental test procedures

Packaging of components is done in paper or blister tapes according to IEC 60286-3.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.