

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

AZ934

20 AMP MINIATURE AUTOMOTIVE RELAY, SINGLE OR DUAL

FEATURES

- Up to 20 Amp switching capability in a compact size
- Sealed
- Two separate relays in DPDT (dual) version
- Quiet operation
- Vibration and shock resistant
- ISO/TS 16949, ISO 14000
- Cost effective
- Designed for power windows, power seats and wiper applications



CONTACTS

Arrangement	DPDT (2 Form C) SPDT (1 Form C)
Ratings	Max. switched power: 280 W Max. switched voltage: 100 VDC Max. switched current (make/break), continuous: 1 Form C: 25A/20A, 20A 2 Form C: 25A/20A, 20A
Material	Silver tin oxide (silver nickel available - contact factory)
Resistance	< 100 milliohms at 1A, 5 VDC

COIL

Power At Pickup Voltage (typical)	203 mW
Max. Continuous Dissipation	2.2 W 20°C (68°F) ambient
Temperature Rise	32°C (58°F) nominal coil VDC
Max. Temperature	155°C (311°F)

NOTES

1. All values at 20°C (68°F).
2. Maximum make current refers to in-rush current of lamp load.
3. Relay may pull in with less than "Must Operate" value.
4. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁷ operations 2 x 10 ⁵ operations at 20 A 14 VDC Res.
Operate Time (typical)	3 ms at nominal coil voltage
Release Time (typical)	1.5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	500 Vrms coil to contact 500 Vrms between open contacts
Insulation Resistance	100 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	> 8.3% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C (-40°F) to 100°C (212°F) -40°C (-40°F) to 155°C (311°F)
Vibration	0.062" DA at 10–55Hz, 10 g at 55-200 Hz
Shock	30 g, 11 ms, functional
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	10 grams

AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM


12/12/12

AZ934

RELAY ORDERING DATA

COIL SPECIFICATIONS - DC Coil				ORDER NUMBER	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	1 Form C (SPDT)	2 Form C (DPDT)
12	7.2	24.0	255	AZ934-1C-12DET	AZ934-2C-12DET

MECHANICAL DATA



Dimensions in inches with metric equivalents in parentheses. Tolerance: ± 0.010 "

AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

12/12/12