

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

INTRODUCTION:

Adam Tech PC Series International Power Cordset series offers a wide range of cordsets with numerous international approvals for worldwide applications. Each is approved for use by all of the major safety organizations such as UL, CSA & VDE. This series is available in a wide range of cord types with choice of wire gauge and various shielding options. We offer numerous standard Power Cords designed to comply with specific world market requirements and an unlimited variety of custom cords manufactured to our customers specifications.

FEATURES:

- Sturdy, high reliability designs
- Worldwide Safety agency approvals
- Standard and Custom Power Cords
- Choice of cord types and shielding options

MATING CONNECTORS:

Adam Tech IEC series & power line filters, all international IEC 60320 power connectors.

SPECIFICATIONS:

Material:

Outer Jacket Color: Black, other colors optional

Temperature Rating:

Outer Jacket Temperature: 60°C (75°C and 105°C optional)

SAFETY AGENCY APPROVALS:

UL Recognized & CSA Certified, File no. E303525 & E256360
Consult factory for additional international safety agency approvals



ORDERING INFORMATION

PC

SERIES INDICATOR
PC = Power Cord

01 02

PLUG & SOCKET OPTIONS

- | | |
|---|---|
| 01 = American, NEMA 5-15P Straight | 15 = Jacket and Conductor Stripped, Jacket 2.0" / Conductors 0.37" (Consult factory for custom jacket and conductor strip lengths) |
| 01H = North American Hospital Grade NEMA 5-15 | 16 = Blunt Cut |
| 01HB = Color Black | 17 = International Female, IEC C7 |
| 01HC = Color Clear | 25 = American, NEMA 5-15P R/A |
| 01HG = Color Gray | 28 = European, CEE 7/16 Straight |
| 02 = International Female, IEC C13 straight | 29 = Italian, CEI 23-16 |
| 03 = International Female, IEC C13 R/A | 30 = International Female, IEC C5 |
| 04 = International Male, IEC C14 | 31 = Danish, SRAF |
| 06 = European, CEE 7/7 Straight | 32 = South African, BS-546 |
| 07 = European, CEE 7/7 R/A | 33 = South African, BS-546 R/A |
| 08 = United Kingdom Fused, BS 1363 | 34 = Israel, SI-32 R/A |
| 10 = American, NEMA 1-15P Straight Non Polarized | 35 = Australian, AS 3112 |
| 11 = Swiss, SEV 1011 Straight | 38 = European, CEE 7/17 Straight |
| 12 = Italian, CEI 23-16 Grounded | |
| 13 = Australian, AS 3112 Grounded | |

060

LENGTH
(Specified in ft/in)
060 = 6 FT 0 IN
076 = 7 FT 6 IN
State length as required

A

CORD TYPE

- A** = SVT, 60°C
- B** = SJT, 60°C
- C** = SJTW
- D** = SJTW-A
- E** = SPT-1
- F** = SPT-2
- G** = SPT-3
- H** = H03VV-F 3X0.75mm
- I** = H05VV-F 3X0.75mm
- J** = H05VV-F 3X1.00mm
- K** = H03VV-H 2X0.75mm
- L** = H05VV-F 3X1.50mm
- M** = SPT-1 NON-INTEGRAL
- N** = SPT-2 NON-INTEGRAL
- R** = SJT, CEE
- S** = SVT, CEE
- Q** = SJT, 105°C
- V** = SVT, 105°C
- W** = SJTO
- X** = H05VV-F 2X1.00mm
- Y** = H05RN-F 3x1.00mm
- Z** = SJO
- A1** = STW
- A3** = ST
- A4** = STO
- A5** = SJT, CEE, 75°C
- A6** = SVT, CEE, 75°C
- A7** = SPT-2, 105°C
- A8** = SJTO, 105°C
- A9** = SJTOW, 105°C
- B1** = SJTW, 105°C
- B2** = SVT, CEE, 105°C

C

WIRE AWG
J = 12 AWG
A = 14 AWG
B = 16 AWG
C = 18 AWG
G = H03 & H05

0

SHIELDING

- 0** = Non Shielded
- F** = Foil Shield
- S** = Copper Braid and Foil Shield

3

JACKET COLOR
3 = Black
4 = Gray
5 = Beige
6 = White
8 = Brown
11 = Putty

PLUG & SOCKET OPTIONS

