

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



D2-92683

Intelligent Digital Amplifier and Sound Processor

Key Features

- Advanced DAE-3™ Digital Audio Engine™ IC Family
- DAE-3™ Pin Compatible and Function/Feature Compatible with the D2Audio™ DAE-6™ Device Family
- DAE-3HT™ - Identical DAE-3 performance, in 72-QFN package
- Integrated DSP Digital Sound Processing
- Customizable audio path sound processing
- Fully configurable and routable audio signal paths and hardware function assignment
- Fully Supported with Audio Canvas™ III Design Tool
- Flexible Audio Input and Output Configurations
- 12 Independent PWM Engine Channels
- 4 Independent Asynchronous I²S Digital Inputs
- Integrated high-performance stereo ADC (DAE-3 only)
- S/PDIF™ Digital Audio Inputs supporting Linear IEC-61958 PCM or Compressed IEC-61937 Audio
- S/PDIF Digital Audio PCM Output
- Embedded 8-Channel Sample Rate Converter
- Real-Time Amplifier Control and Monitoring
- Supports Bridged, Half-Bridged, and Bridge-Tied Load (BTL) Topologies, Using Discrete or Integrated Power Stages
- Complete Fault Protection with Automatic Recovery
- D2Audio™ SoundSuite™ Enhancement and Virtualization
- Enhanced Audio Processing Decoders And Virtualization
- Dolby® Digital/AC3
- Dolby® Pro Logic IIx
- Dolby® Virtual Speaker
- SRS TruSurround HD4™ , SRS WOW HD™, SRS TruVolume™

Description

The D2-926xx family of the DAE-3™ and DAE-3HT™ Digital Audio Engine™ devices are complete System-on Chip (SoC) multi-channel digital sound processors and Class-D amplifier controllers.

The integrated DSP provides efficient and configurable audio signal path processing including equalization, dynamic range compression, mixing, and filtering that is completely configurable via the Audio Canvas™ III high level programming interface. The integrated PWM engine supports programmable and dynamic control of audio output, enabling a variety of multi-channel output configurations and output power capacity. Internal noise shaping, an embedded asynchronous sample rate converter, dynamic level-dependent timing, and high resolution operation supports power stage audio performances with SNR >110dB and THD+N < 0.01%.

The D2-926xx devices are provided in two package and feature configurations which include the 128-pin DAE-3, and the 72-pin DAE-3HT. Both the DAE-3 and DAE-3HT provide identical performance and enable an extremely flexible platform for feature rich and cost-affordable quality audio solutions, which benefit from the addition of Class-D amplifiers and DSP audio processing.

The 12 integrated digital PWM controllers can be used in a variety of multi-channel audio system configurations, supporting powered as well as line outputs. Fully protected amplifier control provides efficient and clean Class-D power output support.

Applications

- DTV and Blu-ray Soundbar
- DVD and Blu-ray Home Theater Systems
- Home Theater in a Box (HTiB)
- Audio Video Receiver (AVR)
- Multi-Channel Multi-Media (MM) Systems
- Multi-Room Distributed Audio (MRDA)
- Powered Speaker Systems
- Automotive Trunk/Amplified Solutions

Parameters	Alternatives			
	D2-92683	D2-92684	D2-74583	D2-71683
Input Channels	8	8	8	8
PWM Output Channels	12	12	12	12
Signal Flow	Configurable	Configurable	Configurable	Configurable
Supported Audio Inputs	4x I ² S, 1x S/PDIF, 8x fault INT	4x I ² S, 1x S/PDIF, 8x fault INT	4x I ² S, 2x S/PDIF, HDA, ADC (opt), 8x fault INT	4x I ² S, 2x S/PDIF, HDA, ADC (opt), 8x fault INT
Supported Audio Outputs	12x PWM, 1x I ² S, 1x S/PDIF	12x PWM, 1x I ² S, 1x S/PDIF	12x PWM, 4x I ² S, 1x S/PDIF	12x PWM, 4x I ² S, 1x S/PDIF
Features	D2Audio PWM Engine, Graceful Fault Recovery, 147 MHz DSP	D2Audio PWM Engine, Graceful Fault Recovery, Dolby Algorithm Support, 147 MHz DSP	D2Audio PWM Engine, Graceful Fault Recovery, Dolby, DTS [®] Algorithms, 160 MHz DSP, 32k P-memory	D2Audio PWM Engine, Graceful Fault Recovery, Dolby, DTS [®] Algorithms, 147 MHz DSP, 32k P-memory
Audio Canvas III Support	Yes	Yes	Yes	Yes