

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Universal Programmable Clock Generator (UPCG)


Features

- Spread Spectrum, VCXO, and Frequency Select
- Input frequency range:
 - Crystal: 8–30 MHz
 - CLKIN: 0.5–100 MHz
- Output frequency:
 - Commercial: 1–200 MHz
 - Industrial: 1–166 MHz
- Integrated phase-locked loop
- Low jitter, high accuracy outputs
- 3.3V operation
- 8-pin SOIC package

Benefits

- Inventory of only one device, CY22800, is needed in various applications such as HDTV, STB, DVDR, and so on.
- Multiple predefined configurations that can be programmed into a single chip.
- Eliminates the need for expensive and difficult to use higher-order crystal.
- High-performance PLL tailored for multiple applications.
- Meets critical timing requirements in complex system designs.
- Enables application compatibility.
- Allows up to three different frequency selects.

Logic Block Diagram



Pin Configuration

Figure 1. CY22800 8-Pin SOIC




Table 1. Pin Definition

| Name | Pin Number | Description |
|--------------|------------|---|
| XIN | 1 | Reference Input; Crystal or External Clock |
| VDD | 2 | 3.3V Voltage Supply |
| FS0/VCXO | 3 | Frequency Select 0/VCXO Analog Control Voltage ^[1] |
| VSS | 4 | Ground |
| CLKB/FS1 | 5 | Clock Output B/Frequency Select 1 ^[1] |
| CLKA/FS0 | 6 | Clock Output A/Frequency Select 0 ^[1] |
| CLKC/FS2/VSS | 7 | Clock Output C/Frequency Select 2/VSS ^[1] |
| XOUT | 8 | Reference Output (No Connect when the reference is a clock) |

Note

1. Pin definition changes for different configurations. Refer to the specific one-page data sheet for more details.

General Description

The CY22800 is a multi-function clock generator that supports various applications in consumer and communications markets. The device uses the Cypress proprietary PLL along with Spread Spectrum and VCXO technology to make it one of the most versatile clock synthesizers in the marketplace. The CY22800 is a field-programmable synthesizer that can be programmed using an easy-to-use programmer dongle, CY36800, with one of many predefined configuration files for fast sample generation of prototype builds. The CY22800 is a reprogrammable device that can be programmed up to 100 times. The latest configurations available for this device are summarized in [Table 2](#).

Spread Spectrum Clock Generation (SSCG)

The CY22800 can generate Spread Spectrum Clocks (SSCG) to reduce EMI found in today's high-speed digital electronic systems.

The device uses proprietary Spread Spectrum Clock (SSC) technology to synthesize and modulate the frequency of the input clock. By modulating the frequency of the clock, the measured EMI at the fundamental and harmonic frequencies is greatly reduced. This reduction in radiated energy can significantly reduce the cost of complying with regulatory agency (EMC) requirements and improve time to market without degrading system performance.

The CY22800 uses a preprogrammed configuration of memory arrays to synthesize output frequency and offers eight different spread percentages (refer to [Table 2](#) – Code numbers -015 to -022), and an additional option to turn the spread on and off.

For the above-mentioned configurations, the modulation frequency varies with the reference frequency as follows:

$$f_{\text{mod}} = \frac{f_{\text{ref}}}{1000}$$

Table 2. CY22800 Configurations

| Code # | Code name | Input Freq. (MHz) | Output Freq. (MHz) | SS | VCXO |
|-------------------------------------|--|--------------------------------|--|----|------|
| Commercial Temperature Range | | | | | |
| CY22800-001A | X2 Multiplier | CLKIN: 0.5–100 XTAL: 8–30 | CLKA: 1–200 or REFOUT | N | N |
| CY22800-002A | X3 Multiplier | CLKIN: 0.5–66.66 XTAL: 8–30 | CLKA: 1.5–200 or REFOUT | N | N |
| CY22800-003A | X4 Multiplier | CLKIN: 0.5–50 XTAL: 8–30 | CLKA: 2–200 or REFOUT | N | N |
| CY22800-004A | X5 Multiplier | CLKIN: 0.5–40 XTAL: 8–30 | CLKA: 2.5–200 or REFOUT | N | N |
| CY22800-005A | X6 Multiplier | CLKIN: 0.5–33.33 XTAL: 8–30 | CLKA: 3–200 CLKB: REFOUT | N | N |
| CY22800-006A | X8 Multiplier | CLKIN: 0.5–25 XTAL: 8–25 | CLKA: 4–200 CLKB: REFOUT | N | N |
| CY22800-007A | Clock multiplier for consumer & communication applications | 14.318 ^[2] | CLKA: 33.33, 66.66, 50, 75, 80, 100, 133.33 See D/S | N | N |
| CY22800-008A | Clock multiplier for consumer & communication applications | 14.318 ^[2] | CLKA: 12, 24, 48, 60, 62.5, 106.25, 125 See D/S | N | N |

Note

2. Fixed CLKIN/Xtal frequency. Refer to the one page data sheet corresponding to the Code # for detailed input and output ranges.

VCXO

One of the key components of the CY22800 device is the VCXO. The VCXO is used to “pull” the reference crystal higher or lower in order to lock the system frequency to an external source. This is ideal for applications where the output frequency needs to track along with an external reference frequency that is constantly shifting.

A special pullable crystal must be used in order to have adequate VCXO pull range. Pullable Crystal specifications are included in this data sheet.

VCXO Profile

[Figure 2](#) shows an example of what a VCXO profile looks like. The analog voltage input is on the X-axis and the PPM range is on the Y-axis. An increase in the VCXO input voltage results in a corresponding increase in the output frequency. This has the effect of moving the PPM from a negative to positive offset.

Figure 2. VCXO Profile




Table 2. CY22800 Configurations (continued)

| Code # | Code name | Input Freq. (MHz) | Output Freq. (MHz) | SS | VCXO |
|--------------|--|--------------------------------------|---|----|------|
| CY22800-009A | Clock multiplier for consumer & communication applications | 20 ^[2] | CLKA: 33.33, 66.66, 50, 75, 80, 100, 133.33 See D/S | N | N |
| CY22800-010A | Clock multiplier for consumer & communication applications | 20 ^[2] | CLKA: 12, 24, 48, 60, 62.5, 106.25, 125 See D/S | N | N |
| CY22800-011A | Clock multiplier for consumer & communication applications | 25 ^[2] | CLKA: 33.33, 66.66, 50, 75, 80, 100, 133.33 See D/S | N | N |
| CY22800-012A | Clock multiplier for consumer & communication applications | 25 ^[2] | CLKA: 12, 24, 48, 60, 62.5, 106.25, 125 See D/S | N | N |
| CY22800-013A | Clock multiplier for consumer & communication applications | 27 ^[2] | CLKA: 33.33, 66.66, 50, 75, 80, 100, 133.33 See D/S | N | N |
| CY22800-014A | Clock multiplier for consumer & communication applications | 27 ^[2] | CLKA: 12, 24, 48, 60, 62.5, 106.25, 125 See D/S | N | N |
| CY22800-015A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.0 | CLKA: REF (spread ±0.25% or off) CLKB: REF or REF/2 (spread ±0.25% or off) | Y | N |
| CY22800-016A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.1 | CLKA: REF (spread ±0.5% or off) CLKB: REF or REF/2 (spread ±0.5% or off) | Y | N |
| CY22800-017A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.0 | CLKA: REF (spread ±0.75% or off) CLKB: REF or REF/2 (spread ±0.75% or off) | Y | N |
| CY22800-018A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.3 | CLKA: REF (spread ±1.0% or off) CLKB: REF or REF/2 (spread ±1.0% or off) | Y | N |
| CY22800-019A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.0 | CLKA: REF (spread ±1.25% or off) CLKB: REF or REF/2 (spread ±1.25% or off) | Y | N |
| CY22800-020A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.0 | CLKA: REF (spread ±1.5% or off) CLKB: REF or REF/2 (spread ±1.5% or off) | Y | N |
| CY22800-021A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.1 | CLKA: REF (spread ±1.75% or off) CLKB: REF or REF/2 (spread ±1.75% or off) | Y | N |
| CY22800-022A | Spread spectrum for consumer and communication applications | CLKIN: 25.0–100.0 XTAL: 25.0–30.0 | CLKA: REF (spread ±2.0% or off) CLKB: REF or REF/2 (spread ±2.0% or off) | Y | N |
| CY22800-023A | MPEG-2 clock generator for DTV and STB w/ VCXO | XTAL: 13.5 | CLKA: 27 CLKB: 54 CLKC: 27 | N | Y |
| CY22800-024A | MPEG-2 clock generator for DTV and STB w/ VCXO | XTAL: 13.5 | CLKA: 13.5 CLKB: 54 CLKC: 27 | N | Y |
| CY22800-025A | MPEG-2 clock generator for DTV and STB w/ VCXO | XTAL: 13.5/27.0 (Selectable) | CLKB: 27, 27 | N | Y |
| CY22800-026A | MPEG-2 clock generator for DTV and STB w/ VCXO | XTAL: 13.5/27.0 (Selectable) | CLKB: 27, 27 CLKC: 27, 27 | N | Y |
| CY22800-027A | MPEG-2 clock generator for DTV and STB w/ VCXO | XTAL: 27 | CLKB: 27, 27 CLKC: 27, 27.027 (–1 ppm) | N | Y |
| CY22800-028A | MPEG-2 clock generator for DTV and STB w/ VCXO | XTAL: 27 | CLKB: 27, 27 CLKC: 27, 27.027 (0 ppm) | N | Y |
| CY22800-029A | HDTV, STB clock generator (USB/Ethernet/iLink clock) | XTAL/CLKIN: 27 | CLKA: 24.576, 25, 20, 48 CLKB: 27 | N | N |
| CY22800-030A | HDTV, STB clock generator (Ethernet/PCI/Microprocessor clock) | XTAL/CLKIN: 27 | CLKA: 25, 20 CLKB: 27 CLKC: 33.33, 66.66 | N | N |
| CY22800-031A | HDTV, STB clock generator (PCI/Microprocessor clock) | XTAL/CLKIN: 48 | CLKA: 33.33, 66.66, 100, 133.33 CLKB: 48 | N | N |
| CY22800-032A | HDTV, STB clock generator (pixel clocks) | XTAL/CLKIN: 27 | CLKA: 74.25, 74.175824, 148.5, 148.351648 CLKB: 27 | N | N |
| CY22800-033A | Audio clock generator for HDTV & STB (256fs) | XTAL/CLKIN: 27 | CLKA: (32K, 44.1K, 48K) X 256 CLKB: 27 | N | N |
| CY22800-034A | Audio clock generator for HDTV & STB (384fs) | XTAL/CLKIN: 27 | CLKA: (32K, 44.1K, 48K) X 384 CLKB: 27 | N | N |
| CY22800-035A | Audio clock generator for HDTV & STB (512fs) | XTAL/CLKIN: 27 | CLKA: (32K, 44.1K, 48K) X 512 CLKB: 27 | N | N |
| CY22800-036A | Audio clock generator for HDTV & STB (768fs) | XTAL/CLKIN: 27 | CLKA: (32K, 44.1K, 48K) X 768 CLKB: 27 | N | N |
| CY22800-037A | Spread spectrum clock generator for PCI and ASIC | XTAL/CLKIN: 14.31818 | CLKA: 33.33, 66.66, 100, 133.33 (–0.5% or off) | Y | N |
| CY22800-038A | Spread spectrum clock generator for PCI and ASIC | XTAL/CLKIN: 14.31818 | CLKA: 33.33, 66.66, 100, 133.33 (–1.0% or off) | Y | N |

Table 2. CY22800 Configurations (continued)

| Code # | Code name | Input Freq. (MHz) | Output Freq. (MHz) | SS | VCXO |
|--------------|--|-----------------------------------|---|----|------|
| CY22800-039A | Spread spectrum clock generator for PCI and ASIC | XTAL/CLKIN: 14.31818 | CLKA: 33.33, 66.66, 100, 133.33 (±0.25% or off) | Y | N |
| CY22800-040A | Spread spectrum clock generator for PCI and ASIC | XTAL/CLKIN: 14.31818 | CLKA: 33.33, 66.66, 100, 133.33 (±0.5% or off) | Y | N |
| CY22800-041A | Spread spectrum clock generator for Audio / Video Applications | XTAL/CLKIN: 27 | CLKA: 33, 66 (spread -0.5% or off) CLKB: 27 | Y | N |
| CY22800-042A | Spread spectrum clock generator for Audio / Video Applications | XTAL/CLKIN: 27 | CLKA: 33, 66 (spread -1.0% or off) CLKB: 27 | Y | N |
| CY22800-043A | Spread spectrum clock generator for Audio / Video Applications | XTAL/CLKIN: 27 | CLKA: 33, 66 (spread ±0.25% or off) CLKB: 27 | Y | N |
| CY22800-044A | Spread spectrum clock generator for Audio / Video Applications | XTAL/CLKIN: 27 | CLKA: 33, 66 (spread ±0.5% or off) CLKB: 27 | Y | N |
| CY22800-045A | Spread spectrum clock generator with Multiplier option | CLKIN: 35-100 | CLKA: 1x, 2x, 4x or /2 (spread -0.5%) CLKB: REFOUT | Y | N |
| CY22800-046A | Spread spectrum clock generator with Multiplier option | CLKIN: 35-100 | CLKA: 1x, 2x, 4x or /2 (spread -1.0%) CLKB: REFOUT | Y | N |
| CY22800-047A | Spread spectrum clock generator with Multiplier option | CLKIN: 35-100 | CLKA: 1x, 2x, 4x or /2 (spread -1.5%) CLKB: REFOUT | Y | N |
| CY22800-048A | Spread spectrum clock generator with Multiplier option | CLKIN: 35-100 | CLKA: 1x, 2x, 4x or /2 (spread -2.0%) CLKB: REFOUT | Y | N |
| CY22800-049A | Spread spectrum clock generator with Multiplier option | CLKIN: 35-100 | CLKA: 1x, 2x, 4x or /2 (spread -2.5%) CLKB: REFOUT | Y | N |
| CY22800-050A | Spread spectrum clock generator for PCI and ASIC | XTAL/CLKIN: 14.31818 | CLKA: 33.33, 66.66, 100, 133.33 (-1.5% or off) | Y | N |
| CY22800-051A | X10 Multiplier | CLKIN: 0.5-20 XTAL: 8-20 | CLKA: 5-200 CLKB: REFOUT | N | N |
| CY22800-052A | X12 Multiplier | CLKIN: 0.5-16.66 XTAL: 8-16.66 | CLKA: 6-200.0 CLKB: REFOUT | N | N |
| CY22800-053A | X15 Multiplier | CLKIN: 0.5-13.33 XTAL: 8-13.33 | CLKA: 7.5-200 CLKB: REFOUT | N | N |
| CY22800-054A | X20 Multiplier | CLKIN: 0.5-10 XTAL: 8-10 | CLKA: 10-200 CLKB: REFOUT | N | N |
| CY22800-055A | X25 Multiplier | CLKIN: 0.5-8 XTAL: 8 | CLKA: 12.5-200 CLKB: REFOUT | N | N |
| CY22800-056A | 2/3 Multiplier | CLKIN: 2.5-133 XTAL: 8-30 | CLKA: 1.67-88.67 CLKB: REFOUT | N | N |
| CY22800-057A | 4/3 Multiplier | CLKIN: 2-100 XTAL: 8-30 | CLKA: 2.66-133.33 CLKB: REFOUT | N | N |
| CY22800-058A | 3/4 Multiplier | CLKIN: 3.5-133 XTAL: 8-30 | CLKA: 2.625-99.75 CLKB: REFOUT | N | N |
| CY22800-059A | 3/2 Multiplier | CLKIN: 1.5-133 XTAL: 8-30 | CLKA: 2.25-199.5 CLKB: REFOUT | N | N |
| CY22800-060A | 2/5 Multiplier | CLKIN: 5-133 XTAL: 8-30 | CLKA: 2-53.2 CLKB: REFOUT | N | N |
| CY22800-061A | 3/5 Multiplier | CLKIN: 3.5-133 XTAL: 8-30 | CLKA: 2.1-80 CLKB: REFOUT | N | N |
| CY22800-062A | 5/6 Multiplier | CLKIN: 3-80 XTAL: 8-30 | CLKA: 2.5- 66.67 CLKB: REFOUT | N | N |
| CY22800-063A | 6/5 Multiplier | CLKIN: 2-66.67 XTAL: 8-30 | CLKA: 2.4-80 CLKB: REFOUT | N | N |
| CY22800-064A | 5/8 Multiplier | CLKIN: 2.5-80 XTAL: 8-30 | CLKA: 1.56-50 CLKB: REFOUT | N | N |
| CY22800-065A | 8/5 Multiplier | CLKIN: 2-50 XTAL: 8-30 | CLKA: 3.2-80 CLKB: REFOUT | N | N |
| CY22800-066A | Spread spectrum clock generator for Audio / Video Applications | XTAL/CLKIN: 27 | CLKA: 33, 66 (spread -1.5% or off) CLKB: 27 | Y | N |
| CY22800-067A | 5/4 Multiplier | CLKIN: 5-133 XTAL: 8-30 | CLKA: 6-166 CLKB: REFOUT | N | N |
| CY22800-068A | 4/5 Multiplier | CLKIN: 5-33 XTAL: 8-30 | CLKA: 4-106 CLKB: REFOUT | N | N |
| CY22800-069A | 66/64 Multiplier | CLKIN: 5-133 XTAL: 8-30 | CLKA: 5-137 CLKB: REFOUT | N | N |

Table 2. CY22800 Configurations (continued)

| Code # | Code name | Input Freq. (MHz) | Output Freq. (MHz) | SS | VCXO |
|-------------------------------------|---|-----------------------------------|---|----|------|
| CY22800-070A | 64/66 Multiplier | CLKIN: 5–133 XTAL: 8–30 | CLKA: 5–129 CLKB: REFOUT | N | N |
| CY22800-071A | 255/238 Multiplier | CLKIN: 5–133 XTAL: 8–30 | CLKA: 5–142 CLKB: REFOUT | N | N |
| CY22800-072A | 238/255 Multiplier | CLKIN: 5–133 XTAL: 8–30 | CLKA: 5–124 CLKB: REFOUT | N | N |
| CY22800-073A | 3-Output Fanout Buffer | CLKIN: 1–133 XTAL: 8–30 | CLKA = CLKB = CLKC: REFOUT | N | N |
| CY22800-074A | X2 Multiplier with Fanout and REFOUT | CLKIN: 9–100 XTAL: 8–30 | CLKA = CLKC: 18–200 CLKB: REFOUT | N | N |
| CY22800-075A | X3 Multiplier with Fanout and REFOUT | CLKIN: 6–66 XTAL: 8–30 | CLKA = CLKC: 18–200 CLKB: REFOUT | N | N |
| CY22800-076A | X4 Multiplier with Fanout and REFOUT | CLKIN: 5–50 XTAL: 8–30 | CLKA = CLKC: 20–200 CLKB: REFOUT | N | N |
| CY22800-077A | /2 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.25–66.5 CLKB = CLKC: 0.25–66.5 or off | N | N |
| CY22800-078A | /3 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.17–44.3 CLKB = CLKC: 0.17–44.3 or off | N | N |
| CY22800-079A | /4 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.125–33.25 CLKB = CLKC: 0.125–33.25 or off | N | N |
| CY22800-080A | /5 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.1–26.6 CLKB = CLKC: 0.1–26.6 or off | N | N |
| CY22800-081A | /6 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.083–22.2 CLKB = CLKC: 0.083–22.2 or off | N | N |
| CY22800-082A | /7 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.071–19 CLKB = CLKC: 0.071–19 or off | N | N |
| CY22800-083A | /8 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.063–16.6 CLKB = CLKC: 0.063–v16.6 or off | N | N |
| CY22800-084A | /9 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.056–14.8 CLKB = CLKC: 0.056–14.8 or off | N | N |
| CY22800-085A | /10 Clock Divider | CLKIN: 0.5–133 XTAL: 8–30 | CLKA: 0.05–13.3 CLKB = CLKC: 0.05–13.3 or off | N | N |
| Industrial Temperature Range | | | | | |
| CY22800-115A | Spread spectrum for consumer and communication applications | CLKIN: 25– 82.5 XTAL: 25–30 | CLKA: REF (spread ±0.25% or off) CLKB: REF or REF/2 (spread ±0.25% or off) | Y | N |
| CY22800-116A | Spread spectrum for consumer and communication applications | CLKIN: 25–82.5 XTAL: 25–30 | CLKA: REF (spread ±0.5% or off) CLKB: REF or REF/2 (spread ±0.5% or off) | Y | N |
| CY22800-117A | Spread spectrum for consumer and communication applications | CLKIN: 25–82.5 XTAL: 25 - 30 | CLKA: REF (spread ±0.75% or off) CLKB: REF or REF/2 (spread ±0.75% or off) | Y | N |
| CY22800-118A | Spread spectrum for consumer and communication applications | CLKIN: 25–82.5 XTAL: 25–30 | CLKA: REF (spread ±1.0% or off) CLKB: REF or REF/2 (spread ±1.0% or off) | Y | N |
| CY22800-119A | Spread spectrum for consumer and communication applications | CLKIN: 25–82.5 XTAL: 25–30 | CLKA: REF (spread ±1.25% or off) CLKB: REF or REF/2 (spread ±1.25% or off) | Y | N |
| CY22800-120A | Spread spectrum for consumer and communication applications | CLKIN: 25–82.5 XTAL: 25–30 | CLKA: REF (spread ±1.5% or off) CLKB: REF or REF/2 (spread ±1.5% or off) | Y | N |
| CY22800-121A | Spread spectrum for consumer and communication applications | CLKIN: 25–82.5 XTAL: 25–30 | CLKA: REF (spread ±1.75% or off) CLKB: REF or REF/2 (spread ±1.75% or off) | Y | N |
| CY22800-145A | Spread spectrum clock generator with Multiplier option | CLKIN: 35–82.5 | CLKA: 1x, 2x, 4x or /2 (spread –0.5%) CLKB: REFOUT | Y | N |
| CY22800-146A | Spread spectrum clock generator with Multiplier option | CLKIN: 35–82.5 | CLKA: 1x, 2x, 4x or /2 (spread –1.0%) CLKB: REFOUT | Y | N |
| CY22800-147A | Spread spectrum clock generator with Multiplier option | CLKIN: 35–82.5 | CLKA: 1x, 2x, 4x or /2 (spread –1.5%) CLKB: REFOUT | Y | N |
| CY22800-148A | Spread spectrum clock generator with Multiplier option | CLKIN: 35–82.5 | CLKA: 1x, 2x, 4x or /2 (spread –2.0%) CLKB: REFOUT | Y | N |
| CY22800-151A | X10 Multiplier | CLKIN: 0.5–16.5 XTAL: 8–16.5 | CLKA: 5–165 CLKB: REFOUT | N | N |
| CY22800-152A | X12 Multiplier | CLKIN: 0.5–13.75 XTAL: 8–13.75 | CLKA: 6–165 CLKB: REFOUT | N | N |
| CY22800-153A | X15 Multiplier | CLKIN: 0.5–11 XTAL: 8–11 | CLKA: 7.5–165 CLKB: REFOUT | N | N |
| CY22800-154A | X20 Multiplier | CLKIN: 0.5–8.25 XTAL: 8–8.25 | CLKA: 10–165 CLKB: REFOUT | N | N |

Table 2. CY22800 Configurations (continued)

| Code # | Code name | Input Freq. (MHz) | Output Freq. (MHz) | SS | VCXO |
|--------------|----------------|---------------------------------|----------------------------------|----|------|
| CY22800-155A | X25 Multiplier | CLKIN: 0.5–6.6 XTAL: 8–6.6 | CLKA: 12.5–165 CLKB: REFOUT | N | N |
| CY22800-156A | 2/3 Multiplier | CLKIN: 2.5–82.5 XTAL: 8–30 | CLKA: 1.67–55 CLKB: REFOUT | N | N |
| CY22800-157A | 4/3 Multiplier | CLKIN: 1.5–82.5 XTAL: 8–27.5 | CLKA: 2–110 CLKB: REFOUT | N | N |
| CY22800-158A | 3/4 Multiplier | CLKIN: 3.5–110 XTAL: 8–30 | CLKA: 2.625–82.5 CLKB: REFOUT | N | N |
| CY22800-159A | 3/2 Multiplier | CLKIN: 1.5–110 XTAL: 8–27.5 | CLKA: 2.25–165 CLKB: REFOUT | N | N |
| CY22800-160A | 2/5 Multiplier | CLKIN: 5–133 XTAL: 8–30 | CLKA: 2–53.2 CLKB: REFOUT | N | N |
| CY22800-161A | 3/5 Multiplier | CLKIN: 3.5–110 XTAL: 8–30 | CLKA: 2.1–66 CLKB: REFOUT | N | N |
| CY22800-162A | 5/6 Multiplier | CLKIN: 3–66 XTAL: 8–30 | CLKA: 2.5–55 CLKB: REFOUT | N | N |
| CY22800-163A | 6/5 Multiplier | CLKIN: 2–55 XTAL: 8–30 | CLKA: 2.4–66 CLKB: REFOUT | N | N |
| CY22800-164A | 5/8 Multiplier | CLKIN: 2.5–80 XTAL: 8–30 | CLKA: 1.56–50 CLKB: REFOUT | N | N |
| CY22800-165A | 8/5 Multiplier | CLKIN: 2–41.25 XTAL: 8–30 | CLKA: 3.2–66 CLKB: REFOUT | N | N |

Cypress offers a wide range of programmable clock synthesizers that can be used to generate any other frequencies not covered by the CY22800. [Table 3](#) summarizes all Cypress programmable devices including CY22800.

Table 3. Cypress Programmable Clocks^[3]

| Part # | No. of PLL | Input Freq. | Output Freq. | Package | No. of Outputs | Spread Spectrum | VCXO | I ² C |
|---------------|------------|-------------|--------------|------------------------|----------------|-----------------|------|------------------|
| CY22800 | 1 | 0.5–100 | 1–200 | 8-SOIC | up to 3 | Yes | Yes | No |
| CY22801 | 1 | 0.5–133 | 1–200 | 8-SOIC | up to 3 | No | No | No |
| CY22050 | 1 | 1–133 | 0.08–200 | 16-TSSOP | up to 6 | No | No | No |
| CY22150 | 1 | 1–133 | 0.08–200 | 16-TSSOP | up to 6 | No | No | Yes |
| CY25100 | 1 | 8–166 | 3–200 | 8-SOIC/TSSOP | up to 2 | Yes | No | No |
| CY25200 | 1 | 3–166 | 3–200 | 16-TSSOP | up to 6 | Yes | No | No |
| CY241V08 | 1 | 27/13.5 | 27/13.5 | 8-SOIC | up to 2 | No | Yes | No |
| CY22392 | 3 | 1–166 | 1–200 | 16-TSSOP | up to 6 | No | No | No |
| CY22381 | 3 | 1–166 | 1–200 | 8-SOIC | up to 3 | No | No | No |
| CY22393 | 3 | 1–166 | 1–200 | 16-TSSOP | up to 6 | No | No | Yes |
| CY22394/5 | 3 | 1–166 | 1–200 | 16-TSSOP | up to 5 | No | No | No |
| CY22388/89/91 | 4 | 1–100 | 4.2–166 | 16/20-TSSOP, 32-QFN | up to 8 | No | Yes | No |

Note

3. CY3672 can be used to program the clock devices listed in [“Cypress Programmable Clocks^{\[3\]}”](#) on page 6

Absolute Maximum Conditions

| Parameter | Description | Min | Max | Unit |
|-----------------|---|-----------------------|-----------------------|------|
| V _{DD} | Supply Voltage | -0.5 | 4.6 | V |
| T _S | Storage Temperature | -65 | 125 | °C |
| T _J | Junction Temperature | - | 125 | °C |
| | Digital Inputs | V _{SS} - 0.3 | V _{DD} + 0.3 | V |
| | Digital Outputs referred to V _{DD} | V _{SS} - 0.3 | V _{DD} + 0.3 | V |
| | Electro-Static Discharge | 2 | - | kV |

Recommended Operating Conditions

| Parameter | Description | Min | Typ | Max | Unit |
|---------------------------------|---|------|-----|------|------|
| V _{DD} | Operating Voltage | 3.14 | 3.3 | 3.47 | V |
| T _A | Ambient Temperature, Commercial Grade | 0 | - | 70 | °C |
| | Ambient Temperature, Industrial Grade | -40 | - | 85 | °C |
| C _{LOAD} | Max. Load Capacitance on the CLK output | - | - | 15 | pF |
| f _{REF} ^[4] | Reference Frequency | 0.5 | - | 100 | MHz |
| t _{PU} | Power up time for all VDDs to reach minimum specified voltage (power ramps must be monotonic) | 0.05 | - | 500 | ms |

Pullable Crystal Specifications for VCXO Application ONLY

| Parameter | Name | Min | Typ | Max | Unit |
|--------------------------------|--|------|-----|------|------|
| C _{LNOM} | Crystal Load Capacitance | - | 14 | - | pF |
| R ₁ | Equivalent Series Resistance | - | - | 25 | Ω |
| R ₃ /R ₁ | Ratio of Third Overtone Mode ESR to Fundamental Mode ESR. Ratio used because typical R ₁ values are much less than the maximum spec | 3 | - | - | - |
| DL | Crystal Drive Level. No external series resistor assumed | - | 0.5 | 2 | mW |
| F _{3SEPHI} | Third overtone separation from 3*F _{NOM} (High Side) | 300 | - | - | ppm |
| F _{3SEPLO} | Third overtone separation from 3*F _{NOM} (Low Side) | - | - | -150 | ppm |
| C ₀ | Crystal shunt capacitance | | | 7 | pF |
| C ₀ /C ₁ | Ratio of Shunt to motional capacitance | 180 | - | 250 | |
| C ₁ | Crystal motional capacitance | 14.4 | 18 | 21.6 | fF |

Recommended Crystal Specifications for ALL other Applications

| Parameter | Name | Description | Min | Typ | Max | Unit |
|-------------------|------------------------------------|--|-----|-----|-----|------|
| F _{NOM} | Nominal Crystal Frequency | Parallel resonance, fundamental mode, and AT cut | 8 | - | 30 | MHz |
| C _{LNOM} | Nominal Load Capacitance | | - | 12 | - | pF |
| R ₁ | Equivalent Series Resistance (ESR) | Fundamental mode | - | 35 | 50 | Ω |
| DL | Crystal Drive Level | No external series resistor assumed | - | 0.5 | 2 | mW |

Note

4. Configuration dependent, see the one-page documents.

DC Electrical Specifications


| Parameter | Name | Description | Min | Typ. | Max | Unit |
|-----------------|------------------------|--|-----------|------|----------|----------|
| I_{OH} | Output High Current | $V_{OH} = V_{DD} - 0.5$, $V_{DD} = 3.3V$ (source) | 12 | 24 | – | mA |
| I_{OL} | Output Low Current | $V_{OL} = 0.5$, $V_{DD} = 3.3V$ (sink) | 12 | 24 | – | mA |
| C_{IN1} | Input Capacitance | All input pins except XIN and XOUT | – | – | 7 | pF |
| C_{IN2} | Input Capacitance | XIN and XOUT pins for non-VCXO applications | – | 24 | – | pF |
| I_{IH} | Input High Current | $V_{IH} = V_{DD}$ | – | 5 | 10 | μA |
| I_{IL} | Input Low Current | $V_{IL} = 0V$ | – | – | 50 | μA |
| $f_{\Delta XO}$ | VCXO Pullability Range | | ± 150 | – | | ppm |
| V_{VCXO} | VCXO Input Range | | 0 | – | V_{DD} | V |
| V_{IH} | Input High Voltage | CMOS levels, 70% of V_{DD} | 0.7 | – | – | V_{DD} |
| V_{IL} | Input Low Voltage | CMOS levels, 30% of V_{DD} | – | – | 0.3 | V_{DD} |

AC Electrical Characteristics ($V_{DD} = 3.3V$)

| Parameter | Name | Description | Min | Typ. | Max | Unit |
|-----------|------------------------|--|-----|------|-----|------|
| DC | Output Duty Cycle | Duty Cycle is defined in Figure 4, 50% of V_{DD} | 45 | 50 | 55 | % |
| t_3 | Rising Edge Slew Rate | Output Clock Rise Time, 20% - 80% of V_{DD} | 0.8 | 1.4 | – | V/ns |
| t_4 | Falling Edge Slew Rate | Output Clock Fall Time, 80% - 20% of V_{DD} | 0.8 | 1.4 | – | V/ns |
| t_{10} | PLL Lock Time | | – | – | 3 | ms |

Test Circuit

Figure 3. Test Circuit Diagram



Timing Definitions

Figure 4. Duty Cycle Definition; $DC = t_2/t_1$





Figure 5. Rise and Fall Time Definitions




Ordering Information

| Ordering Code | Package Type | Operating Range | Operating Voltage |
|----------------------------|--------------------------|-----------------|-------------------|
| CY22800FXC ^[5] | 8-Pin SOIC | Commercial | 3.3V |
| CY22800FXCT ^[5] | 8-Pin SOIC–Tape and Reel | Commercial | 3.3V |
| CY22800FXI ^[5] | 8-Pin SOIC | Industrial | 3.3V |
| CY22800FXIT ^[5] | 8-Pin SOIC–Tape and Reel | Industrial | 3.3V |
| CY22800KFXC | 8-Pin SOIC | Commercial | 3.3V |
| CY22800KFXCT | 8-Pin SOIC–Tape and Reel | Commercial | 3.3V |
| CY22800KFXI | 8-Pin SOIC | Industrial | 3.3V |
| CY22800KFXIT | 8-Pin SOIC–Tape and Reel | Industrial | 3.3V |

Package Diagram

Figure 6. 8-Lead (150-Mil) SOIC S8



51-85066-°C

Note

5. Not recommended for new designs.

Document History Page

| Document Title: CY22800 Universal Programmable Clock Generator (UPCG) | | | | |
|---|---------|-----------------|-----------------|--|
| Document Number: 001-07704 | | | | |
| REV. | ECN NO. | Orig. of Change | Submission Date | Description of Change |
| ** | 478688 | KKVTMP | 07/10/2006 | New data sheet |
| *A | 1063800 | KKVTMP | 05/20/2007 | Add industrial temp option Add CY22801 to Table 2 Correct reprogrammability statement Update Table 1 (CY22800 Configurations) Corrected units for VCXO crystal C1 |
| *B | 2440628 | AESA | 05/25/2008 | Updated template. Updated note 3. Added Note "Not recommended for new designs." Added part number CY22800FXCT, CY22800FXIT, CY22800KFXC, CY22800KFXCT, CY22800KFXI, and CY22800KFXIT in ordering information table. |

Sales, Solutions, and Legal Information

Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at cypress.com/sales.

Products

| | |
|------------------|--|
| PSoC | psoc.cypress.com |
| Clocks & Buffers | clocks.cypress.com |
| Wireless | wireless.cypress.com |
| Memories | memory.cypress.com |
| Image Sensors | image.cypress.com |

PSoC Solutions

| | |
|-----------------------|--|
| General | psoc.cypress.com/solutions |
| Low Power/Low Voltage | psoc.cypress.com/low-power |
| Precision Analog | psoc.cypress.com/precision-analog |
| LCD Drive | psoc.cypress.com/lcd-drive |
| CAN 2.0b | psoc.cypress.com/can |
| USB | psoc.cypress.com/usb |

© Cypress Semiconductor Corporation, 2006-2008. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.