

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Master protocol chip - IBS UART - 2746391

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Protocol chip, in SOP 16 housing



Key commercial data

Packing unit	1 PCE
Minimum order quantity	45 PCE
Weight per Piece (excluding packing)	6.4 GRM
Custom tariff number	85423990
Country of origin	China

Technical data

Dimensions

Width	11 mm
Height	10 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Permissible humidity (storage/transport)	60 %

Data interfaces

Interface	INTERBUS
Connection method	Remote bus/local bus
Interface	User interface
Connection method	V.24, 1 start bit, 2 stop bits, 8 data bits, even parity

Power supply

Typical current consumption	10 mA (all inputs static, outputs unused)
Supply voltage	5 V DC ±10 %

Fieldbus function

Amount of process data	max. 4096 Byte
------------------------	----------------

Master protocol chip - IBS UART - 2746391

Technical data

Fieldbus function

Number of supported devices	512
Number of devices with parameter channel	62 (in preparation)

Classifications

eCl@ss

eCl@ss 4.0	27250201
eCl@ss 4.1	27250201
eCl@ss 5.0	27250203
eCl@ss 5.1	27249201
eCl@ss 6.0	27242605
eCl@ss 7.0	27242605
eCl@ss 8.0	27242605

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC001601
ETIM 5.0	EC001601

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

GOST


Ex Approvals

Master protocol chip - IBS UART - 2746391

Approvals

Approvals submitted

Approval details



Accessories

Accessories

Drivers and interfaces

Driver - IBS UART SDS - 2746443



Socket driver source code for IBS ECO-LINK and master protocol chip IBS UART (software and documentation D/GB)
