

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



[Home](#) / [Products](#) / [Part Numbers](#) / A8503

## A8503

### Ultra-Small WLED/RGB Driver for Medium Displays

Contact [Sales](#) for more information.

#### Features

- Active current sharing between LED strings for tight current matching and accuracy
- Drive up to 10 series, 6 parallel LEDs, ( $V_f = 3.7 \text{ V max}$ ,  $I_f = 25 \text{ mA}$ ).
- Boost converter with integrated 50 V DMOS
- LED sinks rated for 25 mA
- PWM dimming with LED duty cycle control
- Open LED protection
- Short LED string protection
- Boost current limit, OTP and soft start.
- Over Voltage Protection and open diode protection.
- Input UVLO protection
- Latch or Auto restart fault mode
- PACKAGE: 4 mm × 4 mm MLP-26

#### Applications

- LED backlight displays



#### Description

A8503 is a multi-output WLED/RGB driver for medium size display backlighting. The A8503 integrates a boost converter and 6 current-sinks to provide a WLED/RGB driver. It can work from single power supply 4.3 to 5.5 V. The boost converter can drive up to 60 LEDs at 20 mA per LED at 5 V battery voltage. The boost converter is constant frequency current mode converter. The integrated boost DMOS switch is rated for 50 V, 2 A.

PWM dimming allows LED currents to be controlled in 500:1 ratio.

A8503 provides protection against over voltage, open diode, open and short LED string, over temperature, pulse by pulse switch current limit and short circuit. With MODE pin low, IC latches on fault and can be re-enabled only by recycling input voltage  $V_{in}$  or toggling EN pin. When MODE pin connected to  $V_{in}$ , IC autorestart.

<b>Complete Part Numbers</b>
------------------------------

Part Number	Package Type	RoHS Compliant	Part Composition/ RoHS Data	Temperature	Comments	Samples	Distributor Stock
A8503EECTR-T	26-lead QFN/MLP	Yes	<a href="#">view data</a>	-40 °C to 85 °C	<i>new</i>	<a href="#">Contact Marketing Representative</a>	<input type="button" value="Check Stock"/>

*Allegro's products are not to be used in life support devices or systems, if a failure of an Allegro product can reasonably be expected to cause the failure of that life support device or system, or to affect the safety or effectiveness of that device or system.*

Copyright © 2008 Allegro MicroSystems, Inc. • 115 Northeast Cutoff, Worcester, MA 01606 USA •  
Phone: 1.508.853.5000 • Fax: 1.508.853.7895