

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Completely Assembled Relay Modules PR1-R... Including 1 or 2 PDT Miniature Relays – With Screw or Spring-Cage Connection

PR1-R... is a 16 mm wide, completely assembled, coupling relay series for universal use with screw or spring-cage connection, which consists of a relay base, a plug-in miniature power relay, a plug-in display module or interference suppression module, and a relay retaining bracket with eject function. Whether with free-wheeling diode or varistor, an LED is provided for status display on the interference suppression module. The relay base has a 1/3 story design and thus has a logical structure. It has coil and contact connections that are located opposite one another and thus meets the requirements of modern control cabinet concepts with clear isolation of control signals and load.

Advantages:

- Low ordering and storage costs
- High degree of flexibility and low maintenance costs through the use of plug-in relays


Input Voltages

PR1-R... is available on the coil side in popular industrial voltages.

Another advantage is the integrated input wiring, which consists of a status LED and a free-wheeling diode (DC types) or a varistor (AC types).

Rugged Miniature Relay

At the heart of the series is a rugged miniature power relay, which is one of the most modern and powerful models on the market. The types with hard gold-plated contacts are designed to provide increased contact reliability in low-current applications.



	Solid	Stranded		I	U
		[mm ²]	AWG	[A]	[V]
Screw connection	0.14 - 2.5	0.14 - 2.5	26 - 14	*	*
Spring-cage connection	0.2 - 1.5	0.2 - 1.5	25 - 16	*	*

* The electrical data is determined by the relay.

Completely Assembled Relay Modules With Screw Connection and Miniature Relay

PR1-RSC3...21.... (1 PDT Contact)

Description	Input Voltage U_N ¹⁾	Type	Order No.	Pcs. Pkt.	
Pre-assembled coupling relay with screw connection , consisting of relay base, plug-in miniature power relay, and plug-in display/interference suppression module, for mounting on τ , includes 5 removable MP1 markers	24 V DC	Includes power contact relay PR1-RSC3-LDP-24DC/21 PR1-RSC3-LV-24AC/21 PR1-RSC3-LV-120AC/21 PR1-RSC3-LV-230AC/21	2834326 2834339 2834342 2834355	5 5 5 5	
	24 V AC				
	120 V AC				
	230 V AC				
Pre-assembled coupling relay with screw connection , as above, but with solid gold coating on the contacts	24 V DC	Includes hard gold-plated contacts PR1-RSC3-LDP-24DC/21AU PR1-RSC3-LV-24AC/21AU PR1-RSC3-LV-120AC/21AU PR1-RSC3-LV-230AC/21AU	2834368 2834371 2834384 2834397	5 5 5 5	
	24 V AC				
	120 V AC				
	230 V AC				
Technical Data					
Input Data					
Nominal input voltage U_N		24 V DC	24 V AC	120 V AC	230 V AC
Permissible range with reference to U_N		See diagram in the INTERFACE catalog			
Typical input current at U_N (for AC: 50/60 Hz)		19 mA	34/26 mA	9/7mA	6/5.5 mA
Typical response time at U_N (for AC: depending on phase relation)		8 ms	3 - 12 ms	3 - 12 ms	3 - 12 ms
Typical release time at U_N (for AC: depending on phase relation)		10 ms	1.5 - 14 ms	1.5 - 16 ms	2 - 22 ms
Input wiring:		Operating indicator and free-wheeling diode in the plug-in module Operating indicator and varistor in the plug-in module			
		24, 120, 230 V AC			
Output Data					
Contact type		PR1-RSC3...21	PR1-RSC3...21AU		
Contact material		Single contact, 1 PDT	Single contact, 1 PDT		
Maximum switching voltage		AgNi	AgNi + 5 μ m Au ²⁾		
Minimum switching voltage		250 V AC/DC	30 V AC/36 V DC		
Limiting continuous current		12 V	100 mV		
Maximum inrush current		12 A	50 mA		
Minimum switching current		30 A (300 ms)	50 mA		
Maximum shutdown power, ohmic load:	250 V AC	100 mA	1 mA		
(For additional data, see INTERFACE catalog)		3000 VA	-		
Minimum switching power		1.2 W	100 μ W		
General Data					
Test voltage	Winding/contact	4 kV, 50 Hz, 1 minute			
Ambient operating temperature range		-25°C to +60°C			
Nominal operating mode		100% operating factor			
Mechanical service life		3 x 10 ⁷ cycles			
Standards/specifications		IEC 60 255/DIN VDE 0435 (in relevant parts), DIN EN 50 178/ VDE 0160 (in relevant parts), EN 60 730/DIN VDE 0631, IEC 60 664/IEC 60 664 A/DIN VDE 0110, pollution degree 3, Surge Voltage Category III			
Mounting position/mounting		Any/can be mounted without spacing			
Connection type		Screw connection			

¹⁾Additional input voltages available on request.

²⁾If the specified maximum values are exceeded, the gold coating will be damaged. In subsequent operation, the values of the AgNi contact will apply.

Insulating housing version

Polyamide PA fiber reinforced, PA-F


Color: green

For torque of terminal block screws, see INTERFACE catalog.


The dimensioning cross section (see INTERFACE catalog) refers to simple wires without ferrules.

Inductive loads must be attenuated with an effective protective circuit to protect inputs and outputs.

Connection diagram:



DC coils



AC coils

Completely Assembled Relay Modules With Screw Connection and Miniature Relay

PR1-RSC3...2x21... (2 PDT Contacts)

Description	Input Voltage $U_N^{1)}$	Type	Order No.	Pcs. Pkt.
Pre-assembled coupling relay with screw connection , consisting of relay base, plug-in miniature power relay, and plug-in display/interference suppression module, for mounting on τ_1 , includes 5 removable MP1 markers	24 V DC	Includes power contact relay PR1-RSC3-LDP-24DC/2x21 PR1-RSC3-LV-24AC/2x21 PR1-RSC3-LV-120AC/2x21 PR1-RSC3-LV-230AC/2x21	2834481 2834494 2834504 2834517	5 5 5 5
	24 V AC			
	120 V AC			
	230 V AC			
Pre-assembled coupling relay with screw connection , as above, but with solid gold coating on the contacts	24 V DC	Includes hard gold-plated contacts PR1-RSC3-LDP-24DC/2x21AU PR1-RSC3-LV-24AC/2x21AU PR1-RSC3-LV-120AC/2x21AU PR1-RSC3-LV-230AC/2x21AU	2834520 2834533 2834546 2834559	5 5 5 5
	24 V AC			
	120 V AC			
	230 V AC			

Technical Data

Input Data

Nominal input voltage U_N	24 V DC
Permissible range with reference to U_N	24, 120, 230 V AC
Typical input current at U_N (for AC: 50/60 Hz)	
Typical response time at U_N (for AC: depending on phase relation)	
Typical release time at U_N (for AC: depending on phase relation)	
Input wiring:	24 V DC
	24, 120, 230 V AC

Output Data

Contact type	Single contact, 2 PDT
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V
Limiting continuous current	8 A
Maximum inrush current	15 A (300 ms)
Minimum switching current	10 mA
Maximum shutdown power, ohmic load:	2000 VA
(For additional data, see INTERFACE catalog)	
Minimum switching power	50 mW

General Data

Test voltage	Winding/contact Contact/contact
Ambient operating temperature range	-25°C to +60°C
Nominal operating mode	100% operating factor
Mechanical service life	3×10^7 cycles
Standards/specifications	IEC 60 255/DIN VDE 0435 (in relevant parts), DIN EN 50 178/ VDE 0160 (in relevant parts), EN 60 730/DIN VDE 0631, IEC 60 664/IEC 60 664 A/DIN VDE 0110, pollution degree 3, Surge Voltage Category III
Mounting position/mounting	Any/can be mounted without spacing
Connection type	Screw connection

24 V DC	24 V AC	120 V AC	230 V AC
19 mA	34/26 mA	9/7mA	6/5.5 mA
8 ms	3 - 12 ms	3 - 12 ms	3 - 12 ms
10 ms	1.5 - 14 ms	1.5 - 16 ms	2 - 22 ms
Operating indicator and free-wheeling diode in the plug-in module			
Operating indicator and varistor in the plug-in module			

PR1-RSC3...2x21 PR1-RSC3...2x21AU

Single contact, 2 PDT	Single contact, 2 PDT
AgNi	AgNi + 5 μ m Au ²⁾
250 V AC/DC	30 V AC/36 V DC
5 V	100 mV
8 A	50 mA
15 A (300 ms)	50 mA
10 mA	1 mA
2000 VA	-
50 mW	100 μ W

¹⁾Additional input voltages available on request.

²⁾If the specified maximum values are exceeded, the gold coating will be damaged. In subsequent operation, the values of the AgNi contact will apply.

Insulating housing version


Polyamide PA fiber reinforced, PA-F
Color: green

For torque of terminal block screws, see
INTERFACE catalog.

The dimensioning cross section (see INTERFACE catalog) refers to simple wires without ferrules.

Inductive loads must be attenuated with an effective protective circuit to protect inputs and outputs.

Connection diagram:



Completely Assembled Relay Modules With Spring-Cage Connection and Miniature Relay

PR1-RSP3...21.... (1 PDT Contact)

Description	Input Voltage U_N ¹⁾	Type	Order No.	Pcs. Pkt.
Pre-assembled coupling relay with spring-cage connection , consisting of relay base, plug-in miniature power relay, and plug-in display or protection module, for mounting on τ , includes 5 removable MP1 markers	24 V DC	Includes power contact relay PR1-RSP3-LDP-24DC/21 PR1-RSP3-LV-24AC/21 PR1-RSP3-LV-120AC/21 PR1-RSP3-LV-230AC/21	2834407 2834410 2834423 2834436	5 5 5 5
	24 V AC			
	120 V AC			
	230 V AC			
Pre-assembled coupling relay with spring-cage connection , as above, but with solid gold coating on the contacts	24 V DC	Includes hard gold-plated contacts PR1-RSP3-LDP-24DC/21AU PR1-RSP3-LV-24AC/21AU PR1-RSP3-LV-120AC/21AU PR1-RSP3-LV-230AC/21AU	2834449 2834452 2834465 2834478	5 5 5 5
	24 V AC			
	120 V AC			
	230 V AC			

Technical Data

Input Data

Nominal input voltage U_N	
Permissible range with reference to U_N	
Typical input current at U_N (for AC: 50/60 Hz)	
Typical response time at U_N (for AC: depending on phase relation)	
Typical release time at U_N (for AC: depending on phase relation)	
Input wiring:	24 V DC 24, 120, 230 V AC

Output Data

Contact type	
Contact material	
Maximum switching voltage	
Minimum switching voltage	
Limiting continuous current	
Maximum inrush current	
Minimum switching current	
Maximum shutdown power, ohmic load:	250 V AC
(For additional data, see INTERFACE catalog)	
Minimum switching power	

General Data

Test voltage	Winding/contact
Ambient operating temperature range	
Nominal operating mode	
Mechanical service life	
Standards/specifications	

Mounting position/mounting
Connection type

24 V DC	24 V AC	120 V AC	230 V AC
See diagram in the INTERFACE catalog			
19 mA	34/26 mA	9/7mA	6/5.5 mA
8 ms	3 - 12 ms	3 - 12 ms	3 - 12 ms
10 ms	1.5 - 14 ms	1.5 - 16 ms	2 - 22 ms
Operating indicator and free-wheeling diode in the plug-in module			
Operating indicator and varistor in the plug-in module			

PR1-RSP3...21	PR1-RSP3...21AU
Single contact, 1 PDT	Single contact, 1 PDT
AgNi	AgNi + 5 μ m Au ²⁾
250 V AC/DC	30 V AC/36 V DC
12 V	100 mV
10 A	50 mA
30 A (300 ms)	50 mA
100 mA	1 mA
2500 VA	–
1.2 W	100 μ W

4 kV, 50 Hz, 1 minute
-25°C to +60°C
100% operating factor
3 x 10⁷ cycles
IEC 60 255/DIN VDE 0435 (in relevant parts), DIN EN 50 178/ VDE 0160 (in relevant parts), EN 60 730/DIN VDE 0631,
IEC 60 664/IEC 60 664 A/DIN VDE 0110, pollution degree 3,
Surge Voltage Category III
Any/can be mounted without spacing
Spring-cage connection

¹⁾Additional input voltages available on request.

²⁾If the specified maximum values are exceeded, the gold coating will be damaged. In subsequent operation, the values of the AgNi contact will apply.

Insulating housing version


Polyamide PA fiber reinforced, PA-F

Color: green

The dimensioning cross section (see INTERFACE catalog) refers to simple wires without ferrules.

Inductive loads must be attenuated with an effective protective circuit to protect inputs and outputs.

Connection diagram:



Completely Assembled Relay Modules With Spring-Cage Connection and Miniature Relay PR1-RSP3...2x21... (2 PDT Contacts)

Description	Input Voltage $U_N^{1)}$	Type	Order No.	Pcs. Pkt.
Pre-assembled coupling relay with spring-cage connection , consisting of relay base, plug-in miniature power relay, and plug-in display or protection module, for mounting on τ , includes 5 removable MP1 markers	24 V DC	Includes power contact relay PR1-RSP3-LDP-24DC/2x21 PR1-RSP3-LV-24AC/2x21 PR1-RSP3-LV-120AC/2x21 PR1-RSP3-LV-230AC/2x21	2834562 2834575 2834588 2834591	5 5 5 5
	24 V AC			
	120 V AC			
	230 V AC			
Pre-assembled coupling relay with spring-cage connection , as above, but with solid gold coating on the contacts	24 V DC	Includes hard gold-plated contacts PR1-RSP3-LDP-24DC/2x21AU PR1-RSP3-LV-24AC/2x21AU PR1-RSP3-LV-120AC/2x21AU PR1-RSP3-LV-230AC/2x21AU	2834601 2834614 2834627 2834630	5 5 5 5
	24 V AC			
	120 V AC			
	230 V AC			

Technical Data

Input Data

Nominal input voltage U_N	24 V DC
Permissible range with reference to U_N	24 V AC
Typical input current at U_N (for AC: 50/60 Hz)	120 V AC
Typical response time at U_N (for AC: depending on phase relation)	230 V AC
Typical release time at U_N (for AC: depending on phase relation)	
Input wiring:	24 V DC
	24, 120, 230 V AC

Output Data

Contact type	
Contact material	
Maximum switching voltage	
Minimum switching voltage	
Limiting continuous current	
Maximum inrush current	
Minimum switching current	
Maximum shutdown power, ohmic load:	250 V AC
(For additional data, see INTERFACE catalog)	
Minimum switching power	

General Data

Test voltage	Winding/contact
	Contact/contact
Ambient operating temperature range	
Nominal operating mode	
Mechanical service life	
Standards/specifications	
Mounting position/mounting	
Connection type	

24 V DC	24 V AC	120 V AC	230 V AC
See diagram in the INTERFACE catalog			
19 mA	34/26 mA	9/7mA	6/5.5 mA
8 ms	3 - 12 ms	3 - 12 ms	3 - 12 ms
10 ms	1.5 - 14 ms	1.5 - 16 ms	2 - 22 ms
Operating indicator and free-wheeling diode in the plug-in module			
Operating indicator and varistor in the plug-in module			

PR1-RSP3...2x21 PR1-RSP3...2x21AU

Single contact, 2 PDT	Single contact, 2 PDT
AgNi	AgNi + 5 μ m Au ²⁾
250 V AC/DC	30 V AC/36 V DC
5 V	100 mV
8 A	50 mA
15 A (300 ms)	50 mA
10 mA	1 mA
2000 VA	-
50 mW	100 μ W

4 kV, 50 Hz, 1 minute
2.5 kV, 50 Hz, 1 minute
-25°C to +60°C
100% operating factor
3 x 10 ⁷ cycles
IEC 60 255/DIN VDE 0435 (in relevant parts), DIN EN 50 178/ VDE 0160 (in relevant parts), EN 60 730/DIN VDE 0631,
IEC 60 664/IEC 60 664 A/DIN VDE 0110, pollution degree 3,
Surge Voltage Category III
Any/can be mounted without spacing
Spring-cage connection

¹⁾Additional input voltages available on request.

²⁾If the specified maximum values are exceeded, the gold coating will be damaged. In subsequent operation, the values of the AgNi contact will apply.

Insulating housing version

Polyamide PA fiber reinforced, PA-F
Color: green

The dimensioning cross section (see INTERFACE catalog) refers to simple wires without ferrules.

Inductive loads must be attenuated with an effective protective circuit to protect inputs and outputs.

Connection diagram:

