

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



SIP REED RELAY

SERIES 30

Because these relays are designed with consideration given to input-to-output voltage isolation, they can be very effective with the control signals as specified in such electrical safety standards UL, CSA, and VDE. The contact-to-coil insulation can withstand 4,000V AC and the contacts are rated to withstand 500 to 1,500V. Other foot-prints available on special order.

CONTACT FORM	RATING (W)	PART NUMBER	NOM. VTG. (VDC)	COIL RES. (Ω)	MAX. PICK UP (VDC)	MIN. DROP OUT (VDC)	CIRCUIT DIAGRAM AND PHYSICAL DIMENSION	
1A	10	SB1A05A	5	500	3.8	.5		
		SB1A12A	12	850	8.0	1.0		
		SB1A24A	24	1200	16.0	2.0		
	20	SB1A05B	5	500	3.8	.5		
		SB1A12B	12	850	8.0	1.0		
		SB1A24B	24	1200	16.0	2.0		
	10	SD1A05A	5	500	3.8	.5		
		SD1A12A	12	500	8.0	1.0		
		SD1A24A	24	2000	16.0	2.0		
	10 (HV)	SD1A05H	5	500	3.8	.5		
		SD1A12H	12	500	8.0	1.0		
		SD1A24H	24	2000	16.0	2.0		
	50	SD1A05D	5	500	3.8	.5		
		SD1A12D	12	500	8.0	1.0		
		SD1A24D	24	2000	16.0	2.0		
	10	SF1A05A	5	500	3.8	.5		
		SF1A12A	12	500	8.0	1.0		
		SF1A24A	24	2000	16.0	2.0		
	10 (HV)	SF1A05H	5	500	3.8	.5		
		SF1A12H	12	500	8.0	1.0		
		SF1A24H	24	2000	16.0	2.0		
	50	SF1A05D	5	500	3.8	.5		
		SF1A12D	12	500	8.0	1.0		
		SF1A24D	24	2000	16.0	2.0		

FREE CATALOGS ARE AVAILABLE BY REQUEST TELEPHONE OR WRITE TO US OF YOUR NEEDS.

PHONE (818)442-3212

TWX (910)587-3351

FAX (818)442-6873