

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。


## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

**Panasonic**  
ideas for life

**HIGHLY SENSITIVE 1500 V  
FCC SURGE BREAKDOWN  
VOLTAGE MINIATURE RELAY**

**DS RELAYS**



**FEATURES**

**1. Breakthrough height of 9.8 mm .386 inch beats the 10 mm .394 inch limit**

1c, 2c, and 4c all have the same height (9.8 mm .386 inch). The width of the relay is also the same (9.9 mm .390 inch). Since the only size variable is the length, the shared form makes mounting on printed printing wiring boards easy.

**2. Suitable for use in difficult environments**

Epoxy resin seals the parts and cut off the external atmosphere, thus enabling use in difficult environments.

**3. Can be used with automatic solder and automatic wash systems**

Automatic soldering and automatic washing can be carried out once the parts are mounted on PC boards.

**4. Gold-clad twin contacts ensure high reliability**

Highly stable gold cladding on the contacts ensures that contact resistance changes little over time. Furthermore, the use of twin contacts, a configuration that performs with superior contact reliability, ensures extremely low contact failure rates even under low level loads.

**5. Polarized magnetic circuits realize resistance to shock and vibration**

High-performance polarized magnetic circuits that utilize the energy of permanent magnets have made it possible to create relays with strong resistance to shock and vibration.

**6. DIL terminal array enables use of IC sockets**

**7. Widening scope of application with multicontact latching**

In addition to single side stable types, you can take advantage of the memory of functions of convenient 1 coil or 2 coil latching relays.

**RoHS Directive compatibility information**  
<http://www.mew.co.jp/ac/e/environment/>

**TYPICAL APPLICATIONS**

Besides telecommunications, measuring devices, office equipment, computers and related equipment, DS relays are also recommended for a broad range of applications including business devices, audio systems, and industrial equipment.

**ORDERING INFORMATION**

DS [ ] E - [ ] - [ ] - [ ] - [ ]

Contact arrangement

- 1: 1 Form C
- 2: 2 Form C
- 4: 4 Form C

Sensitivity

- M: 400 mW nominal operating power
- S: 200 mW nominal operating power

Operating function

- Nil: Single side stable
- L: 1 coil latching
- L2: 2 coil latching

Coil voltage

- DC 1.5, 3, 5, 6, 9, 12, 24, 48 V

Nil: Standard polarity type

- R: Reverse polarity type

Note: 1 coil latching type are manufactured by lot upon receipt of order.  
Reverse polarity types available (add suffix-R)

## TYPES

### 1. Standard type

| Contact arrangement | Nominal coil voltage | Single side stable type | 2 coil latching type |
|---------------------|----------------------|-------------------------|----------------------|
|                     |                      | Part No.                | Part No.             |
| 1 Form C            | 1.5V DC              | DS1E-M-DC1.5V           | DS1E-ML2-DC1.5V      |
|                     | 3V DC                | DS1E-M-DC3V             | DS1E-ML2-DC3V        |
|                     | 5V DC                | DS1E-M-DC5V             | DS1E-ML2-DC5V        |
|                     | 6V DC                | DS1E-M-DC6V             | DS1E-ML2-DC6V        |
|                     | 9V DC                | DS1E-M-DC9V             | DS1E-ML2-DC9V        |
|                     | 12V DC               | DS1E-M-DC12V            | DS1E-ML2-DC12V       |
|                     | 24V DC               | DS1E-M-DC24V            | DS1E-ML2-DC24V       |
| 2 Form C            | 48V DC               | DS1E-M-DC48V            | DS1E-ML2-DC48V       |
|                     | 1.5V DC              | DS2E-M-DC1.5V           | DS2E-ML2-DC1.5V      |
|                     | 3V DC                | DS2E-M-DC3V             | DS2E-ML2-DC3V        |
|                     | 5V DC                | DS2E-M-DC5V             | DS2E-ML2-DC5V        |
|                     | 6V DC                | DS2E-M-DC6V             | DS2E-ML2-DC6V        |
|                     | 9V DC                | DS2E-M-DC9V             | DS2E-ML2-DC9V        |
|                     | 12V DC               | DS2E-M-DC12V            | DS2E-ML2-DC12V       |
| 4 Form C            | 24V DC               | DS2E-M-DC24V            | DS2E-ML2-DC24V       |
|                     | 48V DC               | DS2E-M-DC48V            | DS2E-ML2-DC48V       |
|                     | 1.5V DC              | DS4E-M-DC1.5V           | DS4E-ML2-DC1.5V      |
|                     | 3V DC                | DS4E-M-DC3V             | DS4E-ML2-DC3V        |
|                     | 5V DC                | DS4E-M-DC5V             | DS4E-ML2-DC5V        |
|                     | 6V DC                | DS4E-M-DC6V             | DS4E-ML2-DC6V        |
|                     | 9V DC                | DS4E-M-DC9V             | DS4E-ML2-DC9V        |
| 4 Form C            | 12V DC               | DS4E-M-DC12V            | DS4E-ML2-DC12V       |
|                     | 24V DC               | DS4E-M-DC24V            | DS4E-ML2-DC24V       |
|                     | 48V DC               | DS4E-M-DC48V            | DS4E-ML2-DC48V       |

Standard packing: Tube: 50 pcs.; Case: 500 pcs.

### 2. High sensitivity type

| Contact arrangement | Nominal coil voltage | Single side stable type | 2 coil latching type |
|---------------------|----------------------|-------------------------|----------------------|
|                     |                      | Part No.                | Part No.             |
| 1 Form C            | 1.5V DC              | DS1E-S-DC1.5V           | DS1E-SL2-DC1.5V      |
|                     | 3V DC                | DS1E-S-DC3V             | DS1E-SL2-DC3V        |
|                     | 5V DC                | DS1E-S-DC5V             | DS1E-SL2-DC5V        |
|                     | 6V DC                | DS1E-S-DC6V             | DS1E-SL2-DC6V        |
|                     | 9V DC                | DS1E-S-DC9V             | DS1E-SL2-DC9V        |
|                     | 12V DC               | DS1E-S-DC12V            | DS1E-SL2-DC12V       |
|                     | 24V DC               | DS1E-S-DC24V            | DS1E-SL2-DC24V       |
| 2 Form C            | 48V DC               | DS1E-S-DC48V            | DS1E-SL2-DC48V       |
|                     | 1.5V DC              | DS2E-S-DC1.5V           | DS2E-SL2-DC1.5V      |
|                     | 3V DC                | DS2E-S-DC3V             | DS2E-SL2-DC3V        |
|                     | 5V DC                | DS2E-S-DC5V             | DS2E-SL2-DC5V        |
|                     | 6V DC                | DS2E-S-DC6V             | DS2E-SL2-DC6V        |
|                     | 9V DC                | DS2E-S-DC9V             | DS2E-SL2-DC9V        |
|                     | 12V DC               | DS2E-S-DC12V            | DS2E-SL2-DC12V       |
| 4 Form C            | 24V DC               | DS2E-S-DC24V            | DS2E-SL2-DC24V       |
|                     | 48V DC               | DS2E-S-DC48V            | DS2E-SL2-DC48V       |
|                     | 1.5V DC              | DS4E-S-DC1.5V           | DS4E-SL2-DC1.5V      |
|                     | 3V DC                | DS4E-S-DC3V             | DS4E-SL2-DC3V        |
|                     | 5V DC                | DS4E-S-DC5V             | DS4E-SL2-DC5V        |
|                     | 6V DC                | DS4E-S-DC6V             | DS4E-SL2-DC6V        |
|                     | 9V DC                | DS4E-S-DC9V             | DS4E-SL2-DC9V        |
| 4 Form C            | 12V DC               | DS4E-S-DC12V            | DS4E-SL2-DC12V       |
|                     | 24V DC               | DS4E-S-DC24V            | DS4E-SL2-DC24V       |
|                     | 48V DC               | DS4E-S-DC48V            | DS4E-SL2-DC48V       |

Standard packing: Tube: 50 pcs.; Case: 500 pcs.

Notes: 1. 1 coil latching type are manufactured by lot upon receipt of order.

2. Reverse polarity types available (add suffix-R)

## RATING

### 1. Coil data

#### 1) Single side stable type

| Type                      | Nominal coil voltage | Pick-up voltage (at 20°C 68°F)   | Drop-out voltage (at 20°C 68°F)           | Nominal operating current [ $\pm 10\%$ ] (at 20°C 68°F) | Coil resistance [ $\pm 10\%$ ] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 50°C 122°F)   |
|---------------------------|----------------------|--|---|---|---|-------------------------|--|
| Standard (M) type         | 1.5V DC              | 70%V or less of nominal voltage (Initial)  | 10%V or more of nominal voltage (Initial) | 266.7mA   | 5.63 $\Omega$                                 | 400mW                   | 1 Form C: 120%V of nominal voltage<br>2 Form C, 4 Form C: 150%V of nominal voltage |
|                           | 3V DC                |  |   | 133.3mA   | 22.5 $\Omega$                                 |                         |  |
|                           | 5V DC                |  |   | 80.0mA  | 62.5 $\Omega$                                 |                         |  |
|                           | 6V DC                |  |   | 66.7mA  | 90 $\Omega$                                   |                         |  |
|                           | 9V DC                |  |   | 44.4mA  | 203 $\Omega$                                  |                         |  |
|                           | 12V DC               |  |   | 33.3mA  | 360 $\Omega$                                  |                         |  |
|                           | 24V DC               |  |   | 16.7mA  | 1,440 $\Omega$                                |                         |  |
| 48V DC                    | 8.3mA                | 5,760 $\Omega$   |   |   |   |                         |  |
| High sensitivity (S) type | 1.5V DC              | 1 Form C: 80%V or less of nominal voltage<br>2 Form C, 4 Form C: 70%V or less of nominal voltage (Initial) | 10%V or more of nominal voltage (Initial) | 133.3mA   | 11.3 $\Omega$                                 | 200mW                   | 1 Form C: 160%V of nominal voltage<br>2 Form C, 4 Form C: 200%V of nominal voltage |
|                           | 3V DC                |  |   | 66.7mA  | 45 $\Omega$                                   |                         |  |
|                           | 5V DC                |  |   | 40.0mA  | 125 $\Omega$                                  |                         |  |
|                           | 6V DC                |  |   | 33.3mA  | 180 $\Omega$                                  |                         |  |
|                           | 9V DC                |  |   | 22.2mA  | 405 $\Omega$                                  |                         |  |
|                           | 12V DC               |  |   | 16.7mA  | 720 $\Omega$                                  |                         |  |
|                           | 24V DC               |  |   | 8.3mA   | 2,880 $\Omega$                                |                         |  |
| 48V DC                    | 4.2mA                | 11,520 $\Omega$  |   |   |   |                         |  |

#### 2) 2 coil latching type

| Type                      | Nominal coil voltage | Set voltage (at 20°C 68°F)   | Reset voltage (at 20°C 68°F)   | Nominal operating current [ $\pm 10\%$ ] (at 20°C 68°F) |            | Coil resistance [ $\pm 10\%$ ] (at 20°C 68°F) |                | Nominal operating power |            | Max. allowable voltage (at 50°C 122°F)   |
|---------------------------|----------------------|--|--|---|------------|---|----------------|-------------------------|------------|--|
|                           |                      |  |  | Set coil  | Reset coil | Set coil                                      | Reset coil     | Set coil                | Reset coil |  |
| Standard (M) type         | 1.5V DC              | 70%V or less of nominal voltage (Initial)  | 70%V or less of nominal voltage (Initial)  | 240mA   | 240mA      | 6.25 $\Omega$                                 | 6.25 $\Omega$  | 360mW                   | 360mW      | 1 Form C: 120%V of nominal voltage<br>2 Form C, 4 Form C: 150%V of nominal voltage |
|                           | 3V DC                |  |  | 120mA   | 120mA      | 25 $\Omega$                                   | 25 $\Omega$    |                         |            |  |
|                           | 5V DC                |  |  | 72mA  | 72mA       | 69.4 $\Omega$                                 | 69.4 $\Omega$  |                         |            |  |
|                           | 6V DC                |  |  | 60mA  | 60mA       | 100 $\Omega$                                  | 100 $\Omega$   |                         |            |  |
|                           | 9V DC                |  |  | 40mA  | 40mA       | 225 $\Omega$                                  | 225 $\Omega$   |                         |            |  |
|                           | 12V DC               |  |  | 30mA  | 30mA       | 400 $\Omega$                                  | 400 $\Omega$   |                         |            |  |
|                           | 24V DC               |  |  | 15mA  | 15mA       | 1,600 $\Omega$                                | 1,600 $\Omega$ |                         |            |  |
| 48V DC                    | 7.5mA                | 7.5mA  | 6,400 $\Omega$   | 6,400 $\Omega$  |            |   |                |                         |            |  |
| High sensitivity (S) type | 1.5V DC              | 1 Form C: 80%V or less of nominal voltage<br>2 Form C, 4 Form C: 70%V or less of nominal voltage (Initial) | 1 Form C: 80%V or less of nominal voltage<br>2 Form C, 4 Form C: 70%V or less of nominal voltage (Initial) | 120mA   | 120mA      | 12.5 $\Omega$                                 | 12.5 $\Omega$  | 180mW                   | 180mW      | 1 Form C: 160%V of nominal voltage<br>2 Form C, 4 Form C: 200%V of nominal voltage |
|                           | 3V DC                |  |  | 60mA  | 60mA       | 50 $\Omega$                                   | 50 $\Omega$    |                         |            |  |
|                           | 5V DC                |  |  | 36mA  | 36mA       | 139 $\Omega$                                  | 139 $\Omega$   |                         |            |  |
|                           | 6V DC                |  |  | 30mA  | 30mA       | 200 $\Omega$                                  | 200 $\Omega$   |                         |            |  |
|                           | 9V DC                |  |  | 20mA  | 20mA       | 450 $\Omega$                                  | 450 $\Omega$   |                         |            |  |
|                           | 12V DC               |  |  | 15mA  | 15mA       | 800 $\Omega$                                  | 800 $\Omega$   |                         |            |  |
|                           | 24V DC               |  |  | 7.5mA   | 7.5mA      | 3,200 $\Omega$                                | 3,200 $\Omega$ |                         |            |  |
| 48V DC                    | 3.75mA               | 3.75mA   | 12,800 $\Omega$  | 12,800 $\Omega$   |            |   |                |                         |            |  |


**2. Specifications**

| Characteristics            | Item  | Specifications  |   |                           |
|----------------------------|---|---|---|---------------------------|
|                            |   | 1 Form C  | 2 Form C  | <b>STOP</b> 4 Form C      |
| Contact                    | Arrangement                                       | 1 Form C  | 2 Form C  | <b>STOP</b> 4 Form C      |
|                            | Initial contact resistance, max.                  | Max. 50 mΩ (By voltage drop 6 V DC 1A)  |   |                           |
|                            | Contact material                                  | Ag+Au clad  |   |                           |
| Rating                     | Nominal switching capacity (resistive load)       | 2 A 30 V DC   |   |                           |
|                            | Max. switching power (resistive load)             | 60 W, 125 VA  |   |                           |
|                            | Max. switching voltage                            | 220 V DC, 250 V AC  |   |                           |
|                            | Max. carrying current                             | 3 A   |   |                           |
|                            | Min. switching capacity (Reference value)*1       | 10μA 10m V DC   |   |                           |
|                            | Nominal operating power                           | Single side stable (M type: 400 mW, S type: 200 mW);<br>latching (M type: 360 mW, S type: 180 mW) |   |                           |
| Electrical characteristics | Insulation resistance (Initial)                   |   | Min. 100MΩ (at 500V DC)<br>Measurement at same location as "Initial breakdown voltage" section.                                 |                           |
|                            | Breakdown voltage (Initial)                       | Between open contacts   | 1,000 Vrms for 1min.<br>(500 Vrms for 1min: 1 Form C high sensitivity type) (Detection current: 10mA.)                          |                           |
|                            |   | Between contact and coil  | 1,500 Vrms for 1min.<br>(1,000 Vrms for 1min: 1 Form C high sensitivity type) (Detection current: 10mA.)                        |                           |
|                            | Temperature rise                                  |   | Max. 65°C<br>(By resistive method, nominal voltage applied to the coil, contact carrying current: 2A.)                          |                           |
|                            | Operate time [Set time] (at 20°C 68°F)            |   | Max. 10 ms [10 ms] (Nominal voltage applied to the coil, excluding contact bounce time.)  |                           |
|                            | Release time [Reset time] (at 20°C 68°F)          |   | Max. 5 ms [10 ms] (Nominal voltage applied to the coil, excluding contact bounce time.)<br>(without diode)                      |                           |
|                            | Mechanical characteristics                        | Shock resistance  | Functional*2  | Min. 490 m/s <sup>2</sup> |
| Destructive                |   |   | Min. 980 m/s <sup>2</sup> (Half-wave pulse of sine wave: 6 ms.)   |                           |
| Vibration resistance       |   | Functional  | 10 to 55 Hz at double amplitude of 3.3 mm (Detection time: 10μs.)   |                           |
|                            |   | Destructive   | 10 to 55 Hz at double amplitude of 5 mm   |                           |
| Expected life              | Mechanical  | Min. 10 <sup>8</sup> (10 <sup>7</sup> : 1 Form C latching type) (at 600 cpm)                      |   |                           |
|                            | Electrical  | Min. 5×10 <sup>5</sup> rated load (at 60 cpm)   |   |                           |
| Conditions                 | Conditions for operation, transport and storage*3 |   | Ambient temperature: -40°C to +70°C -40°F to +158°F<br>Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature) |                           |
|                            | Max. operating speed (at rated load)              |   | 60 cpm  |                           |
| Unit weight                |   | Approx. 3 g .11 oz  | Approx. 4g .14oz  | Approx. 7g .25oz          |


Notes: \*1 This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.  
 (SX relays are available for low level load switching [10V DC, 10mA max. level])  
 \*2 Half-wave pulse of sine wave: 11ms; detection time: 10μs  
 \*3 Refer to 6. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT.

**REFERENCE DATA**

1. Maximum switching capacity




2. Life curve (Resistive load)




3. Contact reliability for AC loads


Tested sample: DS2E-M-DC24V 10 pcs.  
 Operating speed: 20 cpm.  
 Detection level: 200 mΩ




4-(1). Coil temperature rise  
 (2 Form C single side stable type)  
 Tested sample: DS2E-M-DC12V  
 Point measured: Inside the coil  
 Ambient temperature: 18° to 19°C 64° to 66°F




4-(2). Coil temperature rise  
 (4 Form C single side stable type) **STOP**  
 Tested sample: DS4E-M-DC12V  
 Point measured: Inside the coil  
 Ambient temperature: 17° to 18°C 63° to 64°F




4-(3). Coil temperature rise  
 (2 Form C 2 coil latching type)  
 Tested sample: DS2E-ML2-DC12V  
 Point measured: Inside the coil  
 Ambient temperature: 20° to 21°C 68° to 70°F




4-(4). Coil temperature rise  
 (4 Form C 2 coil latching type) **STOP**  
 Tested sample: DS4E-ML2-DC12V  
 Point measured: Inside the coil  
 Ambient temperature: 20°C 68°F




5. Operate and release time characteristics  
 (2 Form C single side stable type)  
 Test condition: Without diode connected to coil in parallel




6-(1). Influence of adjacent mounting  
 (1 Form C)



6-(2). Influence of adjacent mounting  
 (2 Form C)



6-(3). Influence of adjacent mounting  
 (4 Form C) **STOP**




# DS

## DIMENSIONS (Unit: mm inch)

### DS (1 Form C)


Single side stable, 2 coil latching

External dimensions




General tolerance:  $\pm 0.3 \pm 0.012$

PC board pattern (Bottom view)  
Single side stable      2 coil latching




Schematic (Bottom view)

Single side stable



(Deenergized condition)

2 coil latching



(Reset condition)


Tolerance:  $\pm 0.1 \pm 0.004$

Note: External dimensions of 1 coil latching types are same as single side stable type.

### DS (2 Form C)


Single side stable

External dimensions




General tolerance:  $\pm 0.3 \pm 0.012$

PC board pattern (Bottom view)



Schematic (Bottom view)



(Deenergized condition)


Note: External dimensions of 1 coil latching types are same as single side stable type.

Tolerance:  $\pm 0.1 \pm 0.004$

### DS (2 Form C)


2 coil latching

External dimensions




General tolerance:  $\pm 0.3 \pm 0.012$

PC board pattern (Bottom view)



Schematic (Bottom view)




(Reset condition)


Tolerance:  $\pm 0.1 \pm 0.004$

**DS (4 Form C)** **STOP**  
Single side stable

External dimensions




PC board pattern (Bottom view)



General tolerance:  $\pm 0.3 \pm 0.12$

Schematic (Bottom view)




(Deenergized condition)

Note: External dimensions of 1 coil latching types are same as single side stable type.


Tolerance:  $\pm 0.1 \pm 0.04$

**DS (4 Form C)** **STOP**  
2 coil latching

External dimensions




PC board pattern (Bottom view)



General tolerance:  $\pm 0.3 \pm 0.12$

Schematic (Bottom view)



(Reset condition)

Tolerance:  $\pm 0.1 \pm 0.04$

**NOTES**

**1. Coil connection**

When connecting coils, refer to the wiring diagram to prevent mis-operation or malfunction.

**2. External magnetic field**

Since DS relays are highly sensitive polarized relays, their characteristics will be affected by a strong external magnetic field. Avoid using the relay under that condition.

**For Cautions for Use, see Relay Technical Information.**