

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement


1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

NAIS

**GU (General Use) Type
SOP Series
Multi-function (1a1b MOSFET
& optocoupler) 16 Pin Type**

PhotoMOS RELAYS

1a1b MOSFET Relay and
1 optocoupler type



mm inch

FEATURES

1. SO package 16-Pin type in super miniature design

The device comes in a super-miniature SO package 16-Pin type measuring (W)4.4 x (L)10.37 x (H) 2.1mm (W).173 x (L).408 x (H).083inch

2. Ideal for PC card and Fax/Modem applications

The small size provides additional space for increased functionality. The new device has been specifically designed for the PCMCIA embedded and handheld device markets.

3. Tape and reel

The device comes standard in a tape and reel (1,000 pcs./reel) to facilitate automatic insertion machines.

TYPICAL APPLICATIONS

- PCMCIA Modem card (Data/fax modem)
- Laptop and notebook computers
- PDA's
- Mobile computing equipment
- Medical equipment
- Security systems
- Meters (Water, Gas, Vending machine)

TYPES

1 optocoupler type	Output rating*		Part No.		Packing quantity in tape and reel
	Load voltage	Load current	Picked from the 1/2/3/4/5/6/7/8-pin side	Picked from the 9/10/11/12/13/14/15/16-pin side	
AC/DC type	350 V	100 mA	AQS610TSX	AQS610TSZ	1,000 pcs.

* Indicate the peak AC and DC values.

Notes: (1) Tape package is the standard packing style. Also available in tube. (Part No. suffix "X" or "Z" is not needed when ordering; Tube: 50 pcs.; Case: 1,000 pcs.)

(2) For space reasons, the package type indicator "X" and "Z" are omitted from the seal.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

1) Relay portion (2, 3, 14, 15, 16 and 4, 5, 11, 12, 13 pins)

Item		Symbol	AQS610TS	Remarks
Input	LED forward current	I _F	50 mA	
	LED reverse voltage	V _R	3 V	
	Peak forward current	I _{FP}	1 A	f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P _{in}	75 mW	
Output	Load voltage	V _L	350 V	
	Continuous load current	I _L	0.1 A (0.12 A)	() : in case of using only 1 channel
	Peak load current	I _{peak}	0.36 A	100 ms (1 shot), V _L = DC
	Power dissipation	P _{out}	600 mW	

2) Detector portion (6, 7, 9, 10 pins)

Item		Symbol	AQS610TS	Remarks
Input	LED forward current	I _F	50 mA	
	Peak forward current	I _{FP}	1 A	f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P _{in}	75 mW	
Output	Output voltage	BV _{CEC}	30 V	
	Power dissipation	P _{out}	150 mW	

3) Others

Item		Symbol	AQS610TS	Remarks
Total power dissipation		P _T	650 mW	
I/O isolation voltage		V _{iso}	1500 V AC	
Temperature limits	Operating	T _{opr}	-40°C to +85°C -40°F to +185°F	Non-condensing at low temperatures
	Storage	T _{stg}	-40°C to +100°C -40°F to +212°F	

AQS610TS

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

1) Relay portion (2, 3, 14, 15, 16 and 4, 5, 11, 12, 13 pins)

Item		Symbol	AQS610TS	Condition	
Input	LED operate current	Typical	0.9 mA	$I_L = \text{Max.}$	
		Maximum	3 mA		
	LED reverse current	Minimum	0.4 mA	$I_L = \text{Max.}$	
		Typical	0.8 mA		
LED dropout voltage	Typical	1.14 (1.25 V at $I_F = 50\text{mA}$)		$I_F = 5\text{mA}$	
	Maximum	1.5 V			
Output	On resistance	Typical	18Ω	$I_F = 5\text{ mA (N.O.)}, I_F = 0\text{ mA (N.C.)}$ $I_L = \text{Max.}$ Within 1 s on time	
		Maximum	25Ω		
	Off state leakage current	Maximum	1μA		$I_F = 0\text{ mA (N.O.)}, I_F = 5\text{ mA (N.C.)}$ $V_L = \text{Max.}$
Transfer characteristics	Operate time*	Typical	0.23 ms (N.O.), 0.52 ms (N.C.)		$I_F = 0\text{ mA} \pm 5\text{ mA}$ $I_L = \text{Max.}$
		Maximum	1.0 ms		
	Reverse time*	Typical	0.04 ms (N.O.), 0.23 ms (N.C.)		$I_F = 5\text{ mA} \pm 0\text{ mA}$ $I_L = \text{Max.}$
		Maximum	1.0 ms		

Note: Recommendable LED forward current $I_F = 5\text{ mA}$


2) Detector portion (6, 7, 9, 10 pins)

Item		Symbol	AQS610TS	Condition
Input	LED operate current	Typical	2 mA	$I_C = 2\text{ mA}$ $V_{CE} = 0.5\text{ V}$
		Maximum	6 mA	
	LED turn off current	Minimum	5μA	$I_C = 1\text{ mA}$ $V_{CE} = 5\text{ V}$
		Typical	35μA	
LED dropout voltage	Typical	1.14 (1.25 V at $I_F = 50\text{ mA}$)		$I_F = 5\text{ mA}$
	Maximum	1.5 V		
Output	Saturation voltage	Typical	0.08 V	$I_F = 15\text{ mA}$ $I_C = 2\text{ mA}$
		Maximum	0.5 V	
	Off state leakage current	Typical	0.01 nA	$I_F = 0$ $V_{CE} = 5\text{ V}$
		Maximum	500 nA	
Current transfer ratio	Minimum	33%	$I_F = 5\text{ mA}$ $V_{CE} = 0.5\text{ V}$	
	Typical	100%		
Transfer characteristics	Turn on time*	Typical	0.01 ms	$I_F = 5\text{ mA}$ $V_{CE} = 5\text{ V}$ $I_C = 2\text{ mA}$
	Turn off time*	Typical	0.03ms	$I_F = 5\text{ mA}$ $V_{CE} = 5\text{ V}$ $I_C = 2\text{ mA}$

3) Others

Item		Symbol	AQS610TS	Condition
Transfer characteristics	I/O capacitance	Typical	0.8pF	$f = 1\text{ MHz}$ $V_B = 0$
		Maximum	1.5pF	
	Initial I/O isolation resistance	Minimum	1,000MΩ	500V DC

*Operate/Reverse time



■ For Dimensions, see Page 441.

■ For Schematic and Wiring Diagrams, see Page 447.


■ For Cautions for Use, see Page 449.

REFERENCE DATA

[1] Relay portion (2, 3, 14, 15, 16 and 4, 5, 11, 12, 13 pins)


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to $+85^{\circ}\text{C}$
 -40°F to $+185^{\circ}\text{F}$




2. On resistance vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);
 Continuous load current: Max. (DC)




3. Operate time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);
 Continuous load current: Max. (DC)




4. Reverse time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);
 Continuous load current: Max. (DC)




5. LED operate current vs. ambient temperature characteristics

Load voltage: Max. (DC);
 Continuous load current: Max. (DC)




6. LED reverse current vs. ambient temperature characteristics

Load voltage: Max. (DC);
 Continuous load current: Max. (DC)




7. LED dropout voltage vs. ambient temperature characteristics

LED current: 5 to 50 mA




8. Voltage vs. current characteristics of output at MOS portion

Ambient temperature: 25°C 77°F




9. Off state leakage current

Ambient temperature: 25°C 77°F




10. LED forward current vs. operate time characteristics

Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




11. LED forward current vs. reverse time characteristics

Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F



12. Applied voltage vs. output capacitance characteristics

Frequency: 1 MHz; Ambient temperature: 25°C 77°F




AQS610TS

[2] Detector portion (6, 7, 9, 10 pins)


1. Output loss vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to $+85^{\circ}\text{C}$
 -40°F to $+185^{\circ}\text{F}$




2. Relative output current vs. ambient temperature characteristics

Measured portion: between terminals 6 and 7
 $I_F = 5 \text{ mA}$, $V_{CE} = 0.5 \text{ V DC}$




3. LED dropout voltage vs. ambient temperature characteristics

LED current: 5 to 50 mA




4-1. Collector current vs. voltage between collector and emitter characteristics (I_C - V_{CE})

Measured portion: between terminals 6 and 7
 Ambient temperature: 25°C 77°F



4-2. Collector current vs. voltage between collector and emitter characteristics (I_C - V_{CE})

Measured portion: between terminals 6 and 7
 Ambient temperature: 25°C 77°F



5. Off state leakage current

Measured portion: between terminals 6 and 7
 $I_F = 0 \text{ mA}$
 $T_a = 25^{\circ}\text{C}$ 77°F

