

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

## General Speaker

### ■ Features

- Reproduces wide range of frequencies
- Wide variety of applications
- Wide product range

### ■ Recommended Applications

- CD-radio-cassette recorders, Radios
- Information and communication equipment






### ■ Specifications

Part No.	Input (W)		(Ω) Imp.	fo (Hz)	(Hz) Frequency Range	S.P.L.* (dB/1 W/ 0.5 m)	(g) Mass	Comments
	Rated	max.						
EAS-4P15SA	0.1	—	8	530	fo - 3k	92.0	25	
EAS-45P30S	0.1	—	8		fo - 3k	93.0	24	
EAS-6P22S	0.5	—	8		Full Range	92.0	75	
EAS-8P36S	0.63	—	25		Full Range	95.0	83	
EAS-4D02CO	1	—	16		Full Range	73.0	12	
EAS-G7D504A2	1.5	—	16		Full Range	90.0	107	
EAS-G9D550B2	1.5	—	16		Full Range	87.0	45	
EAS-G9D541A2	3	—	8		Full Range	88.5	135	
EAS-G12D531E2	3	—	8		Full Range	93.5	180	

EAS4P15SA

Dimensions in mm (not to scale)




EAS4P15SA



EAS45P30S


Dimensions in mm (not to scale)

EAS45P30S




EAS6P22S

Dimensions in mm (not to scale)




EAS8P36S

Dimensions in mm (not to scale)




EAS4D02C0

Dimensions in mm (not to scale)




EASG7D504A2

Dimensions in mm (not to scale)




EASG9D550B2

Dimensions in mm (not to scale)



EASG9D541A2

Dimensions in mm (not to scale)



EASG12D531E2

Dimensions in mm (not to scale)

