

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

ELECTRICALS

Velocity of Propagation	%	B5
RF Leakage Min. @ 18GHz	dB/ft	-100
Impedance	Nominal	50
Capacitance	pF/ft (pF/m)	24 (78.72)
Delay	ns/ft (ns/m)	1.20 (3.94)
Breakdown Voltage	kV	>15
Phase Stability vs Flexure	deg/deg of bend per GHz	<.0003

MECHANICAL/ENVIRONMENTAL

Nominal Diameter	inches (cm)	.290 (.737)
Minimum Bend Radius	inches (cm)	1.6 (4.064)
Temperature	DEG. C	-65/+200
Weight	lb./ft (g/m)	.09 (134)

MATERIALS AND FINISHES CONNECTOR

Body	Stainless steel
Nut	Stainless steel
Gasket	Silicone Rubber
Contact	BeCu / Gold plated
Insulator	PTFE

MATERIALS AND FINISHES CABLE

Cable Jacket	FEP
Outer Shield	Silver Copper
Inter Conductor	Silver Copper
Dielectric	Micro-porous PTFE
Center Conductor	Silver Copper

LA 290 CABLE
ATTENUATION vs FREQUENCY



JACKET OPTIONS




DESCRIPTION	CODE
FEP JACKET	BF
POLYURETHANE JACKET	BP

CONNECTOR CODES



CONNECTOR STYLE	FREQ GHz	MALE		FEMALE
		STR	RA	BULKHD
SMA	18	S1	S2	S4
N TYPE	18	N1	N2	N4
*ETNC	18	ET1	ET2	ET4

* EXTENDED FREQUENCY RANGE



HOW TO SPECIFY PART NUMBER



FOR EXAMPLE:

SMA STRAIGHT MALE TO SMA STRAIGHT FEMALE, FEP JACKET, 36 INCHES LONG.
NOTE: USE LEADING ZEROS WHEN SPECIFYING LENGTH.

PART NUMBER IS: 81 L29 BF 83 036