## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网,版权归原作者所有。如读者和版权方有任何异议请及时告之,我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译,其目的是协助用户阅读,该译文无法自动跟随原稿更新,同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料,来自厂商的技术支持或者使用者的心得体会等,其内容可能存在描 叙上的差异,建议读者做出适当判断。
- 4.如需与我们联系,请发邮件到marketing@iczoom.com,主题请标有"数据手册"字样。

## **Read Statement**

- 1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
- 2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
- 3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
- 4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets".

NOTIC:	335104-08-XXXX	REVISIO	ONS
NOTES:	DRAWING NO.	REV DESCRIPTION	DATE ECO APPR
I. PACKAGE CABLE ASSEMBLY IN BAG. TAG IN BAG WITH "AMPHENOL CONNEX, 335104-08-XXXX AND DATE CODE".	THIRD ANGLE PROJ. 🕀 🖯	A RELEASE TO MFG.	24-Sep-10 KR
. CABLE ASSEMBLY TO BE 100% TESTED FOR HI-POT, CONTINUITY, SHORTS AND OPEN.			
LENGTH XXXX MM (SEE	TABLE)		-
CONNEX NUMBER		ORIENT MICRO-COAXIAL IN RESPECT TO MICRO-COAXIAI AS SHOWN WITH IN ±10°	TERFACE WITH ————————————————————————————————————
335104-08-0100 335104-08-0100 335104-08-0200 335104-08-0250 335104-08-0300	0 3.936 ±0.150 100 = 0 5.905 ±0.150 150 = 0 7.873 ±0.200 200 = 0 9.842 ±0.200 250 =	±3.81 ±5.08 ±5.08	
* ADDI By C	ITIONAL LENGTHS CAN BE PROVIDED CHANGING XXXX TO DESIRED LEGNTH IN FACT CONNEX MARKETING FOR QUOTE		
DESIGN REQUIREMENTS:  FREQUENCY TO			
VSWR : I MAX			
INS. LOSS dB MAX OTHER			
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°  OTICE - These drawings, specifications, or other data (1) are, and remain the	RAWN DATE ARTHIK R 24-Sep NGINEER DATE	PLUG TO PLUG	Amphenol
roperty of Amphenol Corp. (2) must be returned upon request; and (3) are onfidential and not to be disclosed to any person other than those to whom they re given by Amphenol Corp. The furnishing of these drawings, specifications, or ther data by Amphenol Corp., or to any other person to anyone for any purpose is of to be regarded by implication or otherwise in any manner licensing, granting	PPROVED DATE	USING RG-178 CABLE XXXX MM, LENGTH	Connex
rights or permitting such holder or any other person to manufacture, use or sell any	AD FILE oot Folder/Cable_Assy/335104-08-X	DWG SIZE DRAWIN	NG NO. REV A