

阅读申明


- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement



1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

P		F		ZONE		LTR		REVISIONS		DATE	APP
								H	REVISED PER EC 051A-0054-99	27AUG99	JG

- ① UL RATED 94V-0 THERMOPLASTIC, BLACK.
- ② PHOSPHOR BRONZE PER QQ-B-750.
- ③ .000015 MIN GOLD ON LOCALIZED GOLD PLATE AREA, .000100-.000200 TIN-LEAD ON TERMINATION END, ALL OVER .000050 MIN NICKEL ON ENTIRE CONTACT.
- ④ POLARIZING FEATURE DOES NOT EXIST ON SAME END AS THE POSITION NUMBER 1 INDICATOR ON 10 AND 14 POSITION PRODUCT.



TERMINATED VIEW



DETAIL Z
SCALE 10:1
TYPICAL

1.125	2.100	2.380	2.150	43	44	1-746285-3
1.625	3.100	3.380	3.150	63	64	1- -2
1.525	2.900	3.180	2.950	59	60	1- -1
1.275	2.400	2.680	2.450	49	50	1- -0
1.025	1.900	2.180	1.950	39	40	-9
.875	1.600	1.880	1.650	33	34	-8
.775	1.400	1.680	1.450	29	30	-7
.675	1.200	1.480	1.250	25	26	-6
.625	1.100	1.380	1.150	23	24	-5
.525	.900	1.180	.950	19	20	-4
.425	.700	.980	.750	15	16	-3
.375	.600	.880	.650	13	14	-2
.275	.400	.680	.450	9	10	746285-1
E	D	C	B	A	NO OF POSN	PART NUMBER

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ON: DECIMALS ± .005 ANGLES ± 5°	CONTRACT NO		AMP INCORPORATED Harrisburg, Pa.			
	DR	J. PEACHEY 9-30-85				
	CHK	W.E. ZELKO 11-21-85	NAME		RECEPTACLE KIT, AMP-LATCH NOVO, CTR & MIL PLZN, 15 GOLD DUPLX CONTACTS, W/O STRAIN RLF	
	MATERIAL	APPD JAY SAUDER 11-21-85 APPD D. HOFFMAN 11-21-85	SIZE	FSCM NO	DRAWING NO	
MOLDED PARTS: ① CONTACTS: ②	OSGN APPD	D	00779	746285		
FINISH	OTHER APPD	SCALE	4:1	SHEET 1 of 1		