

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



Specifications

Items		Condition		Specifications			
Rated voltage (V)	–	–	–	10	16	25	35
Surge voltage (V)	125°C	–	–	12	18	29	40
Category temperature range (°C)	–	–	–	–55 to +125			
Capacitance tolerance (%)	120Hz/20°C	–	–	M : ±20			
Dissipation Factor (DF)	120Hz/20°C	–	–	Please see the attached characteristics list			
Leakage current*1	Rated voltage applied, after 2 minutes	–	–	Please see the attached characteristics list			
Equivalent series resistance (ESR)	100kHz to 300kHz/20°C	–	–	Please see the attached characteristics list			
Characteristics of impedance ratio at high temp. and low temp.	Based the value at 100kHz, +20°C	–55°C	Z/Z _{20°C}	0.75 to 1.25			
		+125°C	Z/Z _{20°C}	0.75 to 1.25			
Endurance	125°C, 2,000h, Rated voltage applied	ΔC/C		Within ±20% of the initial value			
		DF		Within 2 times of the initial limit			
		ESR		Within 2 times of the initial limit			
		LC		Within the initial limit			
Damp heat(Steady state)	85°C, 85 to 90%RH, 1,000h, Rated voltage applied	ΔC/C		Within ±20% of the initial value			
		DF		Within 2 times of the initial limit			
		ESR		Within 2 times of the initial limit			
		LC		Within the initial limit			
Resistance to soldering heat*2	VPS (230°C X 75s)	ΔC/C		Within ±10% of the initial value			
		DF		Within 1.3 times of the initial limit			
		ESR		Within 1.3 times of the initial limit			
		LC		Within the initial limit (after voltage processing)			

*1 In case of some problems for measured values, measure after applying rated voltage for 120 minutes at 125°C.

*2 Please refer to page 25 for reflow soldering conditions.

Marking and dimensions

Polarity marking (Cathode)

Case No.
Series
Rated capacitance
Rated voltage

(C6 size is PD, E7, F8, E12, F12 size is SVPD)

(unit : mm)

Size code	φD ±0.5	L ^{+0.1} _{-0.4}	W ±0.2	H ±0.2	C ±0.2	R	p ±0.2
C6	6.3	5.9	6.6	6.6	7.3	0.6~0.8	2.1
E7	8.0	6.9	8.3	8.3	9.0	0.6~0.8	3.2
F8	10.0	7.9	10.3	10.3	11.0	0.6~0.8	4.6
E12	8.0	11.9	8.3	8.3	9.0	0.8~1.1	3.2
F12	10.0	12.6	10.3	10.3	11.0	0.8~1.1	4.6

Size list

RV : Rated voltage


μF \ RV	10	16	25	35
8.2				E7
10			C6	
18				F8
22			E7	E12
39			F8	
47			E12	F12
56	C6			
82		E7	F12	

SVPD series characteristics list

Size code	Part number	Rated voltage (V)	Rated capacitance (μ F)	ESR(m Ω) (max) 100kHz to 300kHz/20 $^{\circ}$ C	Rated ripple current		DF (% max)	Leakage current (μ A) (max) After 2 minutes
					100kHz (mA _{rms})			
					105 $^{\circ}$ C < T _x \leq 125 $^{\circ}$ C*1	T _x \leq 105 $^{\circ}$ C*1		
C6	25SVPD10M	25	10	65	474	1500	10	50
	10SVPD56M	10	56	45	538	1700	12	112
E7	35SVPD8R2M	35	8.2	70	400	1300	10	57
	25SVPD22M	25	22	48	580	1835	10	110
	16SVPD82M	16	82	40	670	2120	12	262
F8	35SVPD18M	35	18	60	550	1800	10	126
	25SVPD39M	25	39	45	664	2100	10	195
E12	35SVPD22M	35	22	50	700	2300	12	154
	25SVPD47M	25	47	30	943	2980	12	235
F12	35SVPD47M	35	47	30	1150	3650	12	329
	25SVPD82M	25	82	28	1202	3800	12	410

※1 T_x : Ambient temperature

Recommended land pattern dimension of PWB



(unit : mm)			
Size code	a	b	c
C6	2.1	9.1	1.6
E7	2.8	11.1	1.9
F8	4.3	13.1	1.9
E12	2.8	11.1	1.9
F12	4.3	13.1	1.9

Frequency coefficient for ripple current

Frequency	120Hz \leq f < 1kHz	1kHz \leq f < 10kHz	10kHz \leq f < 100kHz	100kHz \leq f \leq 500kHz
Coefficient	0.05	0.3	0.7	1