

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Surface Mount Type **SP-Cap**

Series: **FD, CD, UD, UE**

Old series



[Our Requests]

Since this series is old, we don't recommend you to adopt it but CX & SX series for your new design.


■ Features

- Low ESR
- Excellent Noise-absorbent Characteristics
- RoHS directive compliant

■ Specifications

| Series & Size Code | FD | CD | UD | UE | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|------------------------|------------------|-------------------|
| Category Temp. Range | -40 °C to +105 °C | | | | |
| Rated Voltage Range | 2 V.DC to 12.5 V.DC | 2 V.DC to 16 V.DC | 2 V.DC to 8 V.DC | 2 V.DC to 8 V.DC | |
| Nominal Cap.Range | 15 μF to 68 μF | 2.2 μF to 220 μF | 68 μF to 470 μF | 100 μF to 560 μF | |
| Capacitance Tolerance | ±20 % | | | | |
| DC Leakage Current | Reflow 240 °C : I ≤ 0.06 CV (μA) 2minutes (2 V.DC to 4 V.DC) I ≤ 0.04 CV or 3 (μA) 2 minutes (6.3 V.DC to 16 V.DC) (Whichever is greater) Reflow 260 °C : I ≤ 0.1 CV (μA) 2 minutes | | | | |
| tan δ | ≤ 0.06 (120 Hz/+20 °C) | | ≤ 0.10 (120 Hz/+20 °C) | | |
| Surge Voltage | Rated Voltage × 1.25 (15 °C to 35 °C) | | | | |
| Endurance | After applying rated voltage for 1000 hours at 105 °C±2 °C, and then being stabilized at +20 °C, capacitor shall meet the following limits. | | | | |
| | Capacitance change | ±10% of initial measured value | | | |
| | tan δ | ≤ Initial specified value | | | |
| | DC leakage current | ≤ Initial specified value | | | |
| Moisture resistance | After storing for 500 hours at 60 °C, 90 % | | | | |
| | Capacitance change of initial measurd value | 2, 2.5 V.DC | 4 V.DC | 6.3 V.DC | 8 V.DC to 16 V.DC |
| | | +70, -20 % | +60, -20 % | +50, -20 % | +40, -20 % |
| | tan δ | ≤ 200 % of initial specified value | | | |
| DC leakage current | ≤ Initial specified value | | | | |

■ Marking



■ Dimensions in mm(not to scale)

(Unit : mm)

| Series & Size Code | L±0.2 | W1±0.2 | W2±0.1 | H | P±0.3 |
|--------------------|-------|--------|--------|---------|-------|
| FD | 7.3 | 4.3 | 2.4 | 1.1±0.1 | 1.3 |
| CD | 7.3 | 4.3 | 2.4 | 1.8±0.1 | 1.3 |
| UD | 7.3 | 4.3 | 2.4 | 2.8±0.2 | 1.3 |
| UE | 7.3 | 4.3 | 2.4 | 4.2±0.1 | 1.3 |

* Externals of figure are the reference.

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

Standard Products

Reflow *3 <260 °C>

| Series & Size Code | Rated Voltage (V.DC) | Capacitance (±20%) (μF) | Case Size | | | Specification | | Part number | Reflow | | Min. Packaging Qty (pcs) | |
|--------------------|----------------------|-------------------------|-----------|--------|--------|--------------------------------|---------------------|--------------|--------------|--------|--------------------------|------|
| | | | L (mm) | W (mm) | H (mm) | *1 Ripple current (Ar.m.s.) | *2 ESR (mΩ max.) | | *4 240 °C | 260 °C | | |
| FD | 2 | 68 | 7.3 | 4.3 | 1.1 | 2.0 | 28 | EEFFD0D680R | ○ | — | 3500 | |
| | 2.5 | 56 | 7.3 | 4.3 | 1.1 | 2.0 | 28 | EEFFD0E560R | ○ | — | 3500 | |
| | 4 | 39 | 7.3 | 4.3 | 1.1 | 2.0 | 28 | EEFFD0G390R | ○ | — | 3500 | |
| | | 47 | 7.3 | 4.3 | 1.1 | 2.0 | 28 | EEFFD0G470R | ○ | — | 3500 | |
| | 6.3 | 33 | 7.3 | 4.3 | 1.1 | 2.0 | 28 | EEFFD0J330R | ○ | — | 3500 | |
| | 8 | 22 | 7.3 | 4.3 | 1.1 | 2.0 | 28 | EEFFD0K220R | ○ | — | 3500 | |
| | 12.5 | 15 | 7.3 | 4.3 | 1.1 | 1.4 | 40 | EEFFD1B150R | ○ | — | 3500 | |
| CD | 2 | 100 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0D101ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0D101XE | — | ○ | 3500 | |
| | | 120 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0D121ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0D121XE | — | ○ | 3500 | |
| | | 150 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0D151ER | — | ○ | 3500 | |
| | | 180 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0D181ER | — | ○ | 3500 | |
| | 220 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0D221ER | — | ○ | 3500 | | |
| | 2.5 | 82 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0E820ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0E820XE | — | ○ | 3500 | |
| | | 100 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0E101ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0E101XE | — | ○ | 3500 | |
| | | 120 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0E121ER | — | ○ | 3500 | |
| | | 150 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0E151ER | — | ○ | 3500 | |
| | 4 | 56 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0G560ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0G560XE | — | ○ | 3500 | |
| | | 68 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0G680ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0G680XE | — | ○ | 3500 | |
| | | 82 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0G820ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0G820XE | — | ○ | 3500 | |
| | 100 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0G101ER | — | ○ | 3500 | | |
| | 6.3 | 10 | 7.3 | 4.3 | 1.8 | 1.4 | 55 | EEFCD0J100ER | — | ○ | 3500 | |
| | | 22 | 7.3 | 4.3 | 1.8 | 1.6 | 40 | EEFCD0J220ER | — | ○ | 3500 | |
| | | 33 | 7.3 | 4.3 | 1.8 | 2.0 | 28 | EEFCD0J330ER | — | ○ | 3500 | |
| | | 47 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0J470ER | — | ○ | 3500 | |
| | | | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0J470XE | — | ○ | 3500 | |
| | | 68 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0J680ER | — | ○ | 3500 | |
| | 7.3 | 4.3 | 1.8 | 2.7 | 15 | EEFCD0J680XE | — | ○ | 3500 | | | |
| | 8 | 8.2 | 7.3 | 4.3 | 1.8 | 1.4 | 55 | EEFCD0K8R2ER | — | ○ | 3500 | |
| | | 15 | 7.3 | 4.3 | 1.8 | 1.6 | 40 | EEFCD0K150ER | — | ○ | 3500 | |
| | | 22 | 7.3 | 4.3 | 1.8 | 2.0 | 28 | EEFCD0K220ER | — | ○ | 3500 | |
| | | 33 | 7.3 | 4.3 | 1.8 | 2.5 | 18 | EEFCD0K330ER | — | ○ | 3500 | |
| | | 47 | 7.3 | 4.3 | 1.8 | 1.8 | 25 | EEFCD0K470ER | — | ○ | 3500 | |
| | | 22 | 7.3 | 4.3 | 1.8 | 1.6 | 30 | EEFCD1A220ER | — | ○ | 3500 | |
| | 10 | 33 | 7.3 | 4.3 | 1.8 | 1.8 | 25 | EEFCD1A330ER | — | ○ | 3500 | |
| | | 39 | 7.3 | 4.3 | 1.8 | 1.8 | 25 | EEFCD1A390ER | — | ○ | 3500 | |
| | | 4.7 | 7.3 | 4.3 | 1.8 | 1.0 | 80 | EEFCD1B4R7R | ○ | — | 3500 | |
| | 12.5 | 10 | 7.3 | 4.3 | 1.8 | 1.0 | 60 | EEFCD1B100R | ○ | — | 3500 | |
| | | 15 | 7.3 | 4.3 | 1.8 | 1.3 | 50 | EEFCD1B150R | ○ | — | 3500 | |
| | | 22 | 7.3 | 4.3 | 1.8 | 1.6 | 30 | EEFCD1B220R | ○ | — | 3500 | |
| | 16 | 2.2 | 7.3 | 4.3 | 1.8 | 1.0 | 110 | EEFCD1C2R2R | ○ | — | 3500 | |
| | | 4.7 | 7.3 | 4.3 | 1.8 | 1.0 | 80 | EEFCD1C4R7R | ○ | — | 3500 | |
| | | 6.8 | 7.3 | 4.3 | 1.8 | 1.0 | 70 | EEFCD1C6R8R | ○ | — | 3500 | |
| | | 8.2 | 7.3 | 4.3 | 1.8 | 1.3 | 45 | EEFCD1C8R2R | ○ | — | 3500 | |
| | UD | 2 | 330 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0D331ER | — | ○ | 2000 |
| | | | | 7.3 | 4.3 | 2.8 | 3.3 | 12 | EEFUD0D331XE | — | ○ | 2000 |
| | | | | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0D331LE | — | ○ | 2000 |
| | | | 390 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0D391ER | — | ○ | 2000 |
| | | | | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0D391LE | — | ○ | 2000 |
| 7.3 | | | | 4.3 | 2.8 | 3.4 | 9 | EEFUD0D471LE | — | ○ | 2000 | |
| 2.5 | | 220 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0E221ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.3 | 12 | EEFUD0E221XE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0E221LE | — | ○ | 2000 | |
| | | 270 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0E271ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0E271LE | — | ○ | 2000 | |

*1: Ripple current (100 kHz/ +20 to +105 °C), *2: ESR (100 kHz/+20 °C)

*3: Please refer to the page of "Mounting Specifications".

*4: Please contact Panasonic for details of allowable 240 °C reflow condition.

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

Standard Products

Reflow *3 <260 °C>

| Series & Size Code | Rated Voltage (V.DC) | Capacitance (±20 %) (μF) | Case Size | | | Specification | | Part number | Reflow | | Min. Packaging Qty (pcs) | |
|--------------------|----------------------|--------------------------|-----------|--------|--------|--------------------------------|---------------------|--------------|--------------|--------|--------------------------|------|
| | | | L (mm) | W (mm) | H (mm) | *1 Ripple current (Ar.m.s.) | *2 ESR (mΩ max.) | | *4 240 °C | 260 °C | | |
| UD | 4 | 120 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0G121ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.4 | 12 | EEFUD0G121XE | — | ○ | 2000 | |
| | | 150 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0G151ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.3 | 12 | EEFUD0G151XE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0G151LE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 2.5 | 18 | EEFUD0G181ER | — | ○ | 2000 | |
| | 180 | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0G181LE | — | ○ | 2000 | | |
| | | 6.3 | 100 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0J101ER | — | ○ | 2000 |
| | 7.3 | | | 4.3 | 2.8 | 3.3 | 12 | EEFUD0J101XE | — | ○ | 2000 | |
| | 120 | | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0J121ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.3 | 12 | EEFUD0J121XE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0J121LR | ○ | — | 2000 | |
| | | | 7.3 | 4.3 | 2.8 | 2.5 | 18 | EEFUD0J151ER | — | ○ | 2000 | |
| | 150 | 7.3 | 4.3 | 2.8 | 3.4 | 9 | EEFUD0J151LR | ○ | — | 2000 | | |
| | | 8 | 68 | 7.3 | 4.3 | 2.8 | 3.0 | 15 | EEFUD0K680ER | — | ○ | 2000 |
| | 100 | | 7.3 | 4.3 | 2.8 | 2.5 | 18 | EEFUD0K101ER | — | ○ | 2000 | |
| UE | 2 | 270 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0D271ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0D271XE | — | ○ | 2000 | |
| | | 330 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0D331ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0D331XE | — | ○ | 2000 | |
| | | 390 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0D391ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0D391XE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0D391LE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0D471ER | — | ○ | 2000 | |
| | | 470 | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0D471XE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0D471LE | — | ○ | 2000 | |
| | | 560 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0D561ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0D561LE | — | ○ | 2000 | |
| | | 2.5 | 220 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0E221ER | — | ○ | 2000 |
| | | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0E221XE | — | ○ | 2000 |
| | | | 270 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0E271ER | — | ○ | 2000 |
| | | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0E271XE | — | ○ | 2000 |
| | | | 330 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0E331ER | — | ○ | 2000 |
| | | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0E331XE | — | ○ | 2000 |
| | 7.3 | | | 4.3 | 4.2 | 3.7 | 7 | EEFUE0E331LE | — | ○ | 2000 | |
| | 390 | | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0E391ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0E391LE | — | ○ | 2000 | |
| | 470 | | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0E471ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0E471LE | — | ○ | 2000 | |
| | 4 | | 180 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0G181ER | — | ○ | 2000 |
| | | 7.3 | | 4.3 | 4.2 | 3.5 | 10 | EEFUE0G181XE | — | ○ | 2000 | |
| | | 220 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0G221ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0G221XE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0G221LE | — | ○ | 2000 | |
| | | 270 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0G271ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0G271LE | — | ○ | 2000 | |
| | | 330 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0G331ER | — | ○ | 2000 | |
| | | 6.3 | 150 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0J151ER | — | ○ | 2000 |
| | 7.3 | | | 4.3 | 4.2 | 3.5 | 10 | EEFUE0J151XE | — | ○ | 2000 | |
| | 180 | | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0J181ER | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.5 | 10 | EEFUE0J181XE | — | ○ | 2000 | |
| | | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0J181LR | ○ | — | 2000 | |
| | 220 | | 7.3 | 4.3 | 4.2 | 3.0 | 15 | EEFUE0J221ER | — | ○ | 2000 | |
| | | 7.3 | 4.3 | 4.2 | 3.7 | 7 | EEFUE0J221LR | ○ | — | 2000 | | |
| | 8 | 100 | 7.3 | 4.3 | 4.2 | 3.3 | 12 | EEFUE0K101ER | — | ○ | 2000 | |
| | | 150 | 7.3 | 4.3 | 4.2 | 3.0 | 15 | EEFUE0K151ER | — | ○ | 2000 | |

*1: Ripple current (100 kHz/ +20 to +105 °C), *2: ESR (100 kHz/+20 °C)

*3: Please refer to the page of "Mounting Specifications".

*4: Please contact Panasonic for details of allowable 240 °C reflow condition.