

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



## Specifications

Items	Condition	Specifications				
		4.0	6.3	10	16	20
Rated voltage (V)	—	4.0	6.3	10	16	20
Surge voltage (V)	Room temperature	5.2	8.2	12	18	23
Category temperature range (°C)	—	-55 to +125				
Capacitance tolerance (%)	120Hz/20°C	M : ±20				
Dissipation Factor (DF)	120Hz/20°C	Please see the attached characteristics list				
Leakage current*1	Rated voltage applied, after 2 minutes	Please see the attached characteristics list				
Equivalent series resistance (ESR)	100kHz to 300kHz/20°C	Please see the attached characteristics list				
Characteristics of impedance ratio at high temp. and low temp.	Based the value at 100kHz, +20°C	-55°C	Z/Z <sub>20°C</sub>	0.75 to 1.25		
		+125°C	Z/Z <sub>20°C</sub>	0.75 to 1.25		
Endurance	125°C, 1,000h, Rated voltage applied	ΔC/C	Within ±20% of the initial value			
		DF	Within 2 times of the initial limit			
		ESR	Within 2 times of the initial limit			
		LC	Within the initial limit			
Damp heat(Steady state)	60°C, 90 to 95%RH, 1,000h, No-applied voltage	ΔC/C	Within ±20% of the initial value			
		DF	Within 1.5 times of the initial limit			
		ESR	Within 1.5 times of the initial limit			
		LC	Within the initial limit (after voltage processing)			
Resistance to soldering heat*2	VPS (230°C X 75s)	ΔC/C	Within ±10% of the initial value			
		DF	Within 1.3 times of the initial limit			
		ESR	Within 1.3 times of the initial limit			
		LC	Within the initial limit (after voltage processing)			

\*1 In case of some problems for measured values, measure after applying rated voltage for 120 minutes at 125°C.

\*2 Please refer to page 25 for reflow soldering conditions.

## Marking and dimensions

Polarity marking (Cathode)

(unit : mm)

Size code	φD ±0.5	L <sup>+0.1</sup> <sub>-0.4</sub>	W ±0.2	H ±0.2	C ±0.2	R	P ±0.2
C6	6.3	5.9	6.6	6.6	7.3	0.6~0.8	2.1
E7	8.0	6.9	8.3	8.3	9.0	0.6~0.8	3.2

## Size list

RV : Rated voltage

μF \ RV	4.0	6.3	10	16	20
22					C6
39				C6	
47					E7
56			C6		
82		C6		E7	
100		C6			
120			E7		
150	C6		E7		
220		E7			

OS-CON Line-up

Guidelines and precautions

Series system diagram

Image of case size

Products list

Packing specifications (SMD type)

Packing specifications (Radial lead type)

Recommended soldering condition

Fundamental structure

Characteristics

Reliability

Surface mount type

Radial lead type

Catalog Deletion and EOL series

POSCAP Line-up

Guidelines and precautions

Selection guide

Technical data


Surface mount type

## SVQP series characteristics list

Size code	Part number	Rated voltage (V)	Rated capacitance ( $\mu$ F)	ESR( $m\Omega$ ) (max) 100kHz to 300kHz/20°C	Rated ripple current	Allowable ripple current	DF (% max)	Leakage current ( $\mu$ A)(max) After 2 minutes
					100kHz (mArms)			
					105°C<Tx≤125°C※1	Tx≤105°C※1		
C6	20SVQP22M	20	22	60	459	1450	10	220
	16SVQP39M	16	39	50	512	1620	10	312
	10SVQP56M	10	56	45	538	1700	12	280
	6SVQP82M	6.3	82	45	538	1700	12	258
	6SVQP100M	6.3	100	40	572	1810	12	315
	4SVQP150M	4.0	150	40	572	1810	12	300
E7	20SVQP47M	20	47	45	598	1890	12	470
	16SVQP82M	16	82	40	670	2120	12	656
	10SVQP120M	10	120	35	810	2560	12	600
	10SVQP150M	10	150	35	810	2560	12	750
	6SVQP220M	6.3	220	35	810	2560	12	693

※1 Tx: Ambient temperature

## Recommended land pattern dimension of PWB



## Frequency coefficient for ripple current

Frequency	120Hz ≤ f < 1kHz	1kHz ≤ f < 10kHz	10kHz ≤ f < 100kHz	100kHz ≤ f ≤ 500kHz
Coefficient	0.05	0.3	0.7	1