



## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

1	2	3	4	5	6	7
---	---	---	---	---	---	---



Cores	Size of conductor AWG/Composition	A①	B①	Cores	Size of conductor AWG/Composition	A①	B①
08	28 7/0.127	7.00±0.18	8.00±0.18	24	28 7/0.127	23.0±0.22	24.0±0.22
09	28 7/0.127	8.00±0.18	9.00±0.18	25	28 7/0.127	24.0±0.22	25.0±0.22
10	28 7/0.127	9.00±0.18	10.0±0.18	26	28 7/0.127	25.0±0.22	26.0±0.22
12	28 7/0.127	11.0±0.18	12.0±0.18	30	28 7/0.127	29.0±0.25	30.0±0.25
14	28 7/0.127	13.0±0.18	14.0±0.18	34	28 7/0.127	33.0±0.25	34.0±0.25
16	28 7/0.127	15.0±0.22	16.0±0.22	40	28 7/0.127	39.0±0.25	40.0±0.25
18	28 7/0.127	17.0±0.22	18.0±0.22	44	28 7/0.127	43.0±0.28	44.0±0.28
20	28 7/0.127	19.0±0.22	20.0±0.22	50	28 7/0.127	49.0±0.28	50.0±0.28

**Material**  
Insulation: PVC Grey cable Red line  
Insulation thickness: 9mil ave ; 7mil min.

**Conduction**  
AWG size: 28AWG  
Number of stands in each conductor: 7/0.127mm TC  
Lay of strands in each conductor: 0.5 inch at least  
Cross section area: 156 circular mil

**Electronic characteristics**  
Spark test: 2500 V  
Dielectri strength test: 2000V min. in 1 minute  
Conductor resistance: 237Ω max./KM  
Insulation resistance: 100MΩ max./KM  
Capacity: 40pF/M  
Inductance: 1.45μH/M  
Impedance: 100Ω  
Propagation delay time: 4.2ns/m

**Cable physical properties**  
After seven days air oven at 136°C  
Average tensile strength: 1500 Tbs/inch²  
Percent of original: 70% at least  
Average elongation: 200%  
Percent of original: 65% at least

UL style: 2651  
Rated temperature: 105°C  
Rated voltage: 300V  
Passes VW-1 vertical flame test

**RoHS compliant**  
Unit: mm

Scale	Free	Customer-No.	
TOLERANCE		Date	Name
		24.04.2015	Amy
		04.11.2015	Amy
DIM		ASSMANN WSW-No.	
	TOL	AWG28-xx/G-1/300	
① Update the tolerance		Drawing-No.	
		ASS 7307 CA	
① Drawn		Replace	
		Sheet	
Angle	TOL	Id.	
		Modification	
		Date	
		Name	



1	2	3	4	5	6	7
---	---	---	---	---	---	---

H	G	F	E	D	C	B	A
---	---	---	---	---	---	---	---