

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



# CONDUCTIVE POLYMER ALUMINUM SOLID ELECTROLYTIC CAPACITORS

**LV** series Radial Lead Type, High Voltage / Long Life



**NEW**

- Low ESR, High ripple current.
- Long life of 3000 hours at 105°C.
- Radial lead type:  
Lead free flow soldering condition correspondence.
- Compliant to the RoHS directive (2002/95/EC).




## Specifications

Item	Performance Characteristics		
Category Temperature Range	-55 to +105°C		
Rated Voltage Range	16 to 50V		
Rated Capacitance Range	18 to 220μF		
Capacitance Tolerance	±20% at 120Hz, 20°C		
Tangent of loss angle (tan δ)	Less than or equal to the specified value at 120Hz, 20°C		
ESR (※1)	Less than or equal to the specified value at 100kHz, 20°C		
Leakage Current (※2)	Less than or equal to the specified value. After 2 minutes' application of rated voltage at 20°C		
Temperature Characteristics (Max. Impedance Ratio)	Z+105°C / Z+20°C ≤ 1.25 (100kHz) Z-55°C / Z+20°C ≤ 1.25		
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 3000 hours at 105°C.	Capacitance Change	Within ± 20% of the initial capacitance value (※3)
		tan δ	150% or less than the initial specified value
		ESR (※1)	150% or less than the initial specified value
		Leakage current (※2)	Less than or equal to the initial specified value
Damp Heat (Steady State)	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 1500 hours at 60°C, 90% RH.	Capacitance Change	Within ± 20% of the initial capacitance value (※3)
		tan δ	150% or less than the initial specified value
		ESR (※1)	150% or less than the initial specified value
		Leakage current (※2)	Less than or equal to the initial specified value
Resistance to Soldering Heat	After soldering the capacitor under the soldering conditions prescribed here as preheat at 150 to 200°C for 60 to 180 seconds and peak temperature at 265°C for 10 seconds or less, the capacitor shall meet the specifications listed at right, provided that its temperature profile is measured at both of terminal ends facing the soldering side.	Capacitance Change	Within ± 10% of the initial capacitance value (※3)
		tan δ	130% or less than the initial specified value
		ESR (※1)	130% or less than the initial specified value
		Leakage current (※2)	Less than or equal to the initial specified value
Marking	Navy blue print on the case top		

(※1) ESR should be measured at both of the terminal ends closest to the capacitor body.  
 (※2) Conditioning: If any doubt arises, measure the leakage current after the voltage treatment of applying DC rated voltage continuously to the capacitor for 120 minutes at 105°C.  
 (※3) Initial value: The value before test of examination of resistance to soldering.


## Dimensions



Size	φ8 × 9L	φ8 × 12L	φ10 × 13L
φD	8.0	8.0	10.0
L	8.5	11.5	12.5
P	3.5	3.5	5.0
φd	0.6	0.6	0.6

Voltage	16	20	25	35	50
V					
Code	C	D	E	V	H

## Type numbering system (Example : 35V 39μF)



φ D × L	Code
8 × 9	CL
8 × 12	DL
10 × 13	DL

# CONDUCTIVE POLYMER ALUMINUM SOLID ELECTROLYTIC CAPACITORS



## Standard ratings

Rated Voltage (V) (code)	Surge Voltage (V)	Rated Capacitance (μF)	Case Size φ D × L (mm)	tan δ	Leakage Current (μA)	ESR (mΩ) (at 100kHz 20° C)	Rated Ripple (mA <sub>rms</sub> )	Part Number
16 (1C)	18.4	82	8 × 9	0.12	262	35	1800	PLV1C820MCL1
		120	8 × 12	0.12	384	26	2400	PLV1C121MDL1
		220	10 × 13	0.12	704	23	2900	PLV1C221MDL1
20 (1D)	23.0	68	8 × 9	0.12	272	37	1700	PLV1D680MCL1
		100	8 × 12	0.12	400	28	2300	PLV1D101MDL1
		180	10 × 13	0.12	720	25	2800	PLV1D181MDL1
25 (1E)	28.7	56	8 × 9	0.12	280	38	1700	PLV1E560MCL1
		82	8 × 12	0.12	410	28	2300	PLV1E820MDL1
		120	10 × 13	0.12	600	25	2800	PLV1E121MDL1
35 (1V)	40.2	27	8 × 9	0.12	189	42	1600	PLV1V270MCL1
		39	8 × 12	0.12	273	31	2100	PLV1V390MDL1
		68	10 × 13	0.12	476	28	2700	PLV1V680MDL1
50 (1H)	57.5	18	8 × 9	0.12	180	48	1500	PLV1H180MCL1
		27	8 × 12	0.12	270	36	2000	PLV1H270MDL1
		47	10 × 13	0.12	470	31	2500	PLV1H470MDL1

Rated ripple current (mA<sub>rms</sub>) at 105° C 100kHz

Design, Specifications are subject to change without notice.