

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

# UL Type AWM

## 90°C 1000 Volts UL Listed


**Product Construction:****Conductor:**

- 14 AWG fully annealed stranded bare copper per ASTM B-8

**Insulation:**

- Premium-grade, color-coded PVC
- Temperature range: -20°C to +90°C
- Color code: See chart below

**Jacket Marking:**

- CAROL (SIZE) 90°C 1000V  AWM

**Applications:**

- Motor and transformer lead
- External wiring of machinery

**Features:**

- Outstanding oil, flame and moisture resistance
- Extra-flexible

**Industry Approvals:**

- UL Type AWM

**Packaging:**

- 500' (152.4 m) spools
- Other put-ups available on special order

**AWM - 1000 VOLT - UL**

CATALOG NUMBER	AWG SIZE	COND. STRAND	NOMINAL INS. THICKNESS		NOMINAL O.D.		STOCK COLORS	APPROX. NET WT. LBS/M <sup>(6)</sup>
			INCHES	mm	INCHES	mm		
76422*	14	19/0147	0.032	0.81	0.138	3.51	1-8	20

<sup>(6)</sup> Actual shipping weight may vary.

\* Non-stock item; minimum quantity purchase required.

**COLOR CODE CHART**

STOCK COLORS	ORDERING SUFFIX	STOCK COLORS	ORDERING SUFFIX
Black	01	Green	06
White	02	Yellow	05
Red	03	Orange	04
Blue	07	Brown	08