

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

# Customer Specification

## PART NO. 781816

### Construction

|                |   | Diameters (In) |
|----------------|---|----------------|
| 1) Component 1 | 1 X 1 HOOKUP  |                |
| a) Conductor   | 18 (16/30) AWG TC   | 0.047          |
| b) Insulation  | 0.032" Wall, Nom. PVC   | 0.111+/- 0.004 |
| (1) Print      | 18 AWG<br>EXXXXXX (UL) MTW OR AWM 1015/1230<br>105C 600V VW-1 LLXXXXX CSA AWM I A/B<br>105C 600V FT1 OR TEW 105C 600V FT1<br><i>[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]</i> |                |
| (2) Color(s)   | WHITE, BLACK, RED, GREEN, YELLOW, BLUE, BROWN<br>ORANGE, SLATE, VOILET, PINK  |                |

### Applicable Specifications

|                      |                |  |
|----------------------|----------------|--|
| 1) UL                | AWM/STYLE 1015 | 105°C / 600 V <sub>RMS</sub>               |
|                      | VW-1           |  |
|                      | AWM/STYLE 1230 | 105°C / 600 V <sub>RMS</sub>               |
| 2) CSA International | MTW            | 90°C Dry / 60°C Wet / 600 V <sub>RMS</sub> |
|                      | AWM I A/B      | 105°C / 600 V <sub>RMS</sub>               |
|                      | FT1            |  |
|                      | TEW-105        | 105°C / 600 V <sub>RMS</sub>               |

### Environmental

|                                     |  |
|-------------------------------------|--|
| 1) EU Directive 2002/95/EC(RoHS):   |  |
|                                     | All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture. |
| 2) REACH Regulation (EC 1907/2006): |  |
|                                     | This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.  |
| 3) California Proposition 65:       |  |
|                                     | The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.   |

### Properties

|                                  |                                 |
|----------------------------------|---------------------------------|
| Physical & Mechanical Properties |                                 |
| 1) Temperature Range             | -20 to 105°C                    |
| 2) Bend Radius                   | 10X Cable Diameter              |
| 3) Pull Tension                  | 12.6 Lbs, Maximum               |
| Electrical Properties            | (For Engineering purposes only) |
| 1) Voltage Rating                | 600 V <sub>RMS</sub>            |
| 2) Inductance                    | 0.07 μH/ft, Nominal             |
| 3) Conductor DCR                 | 7.1 /1000ft @20°C, Nominal      |

## Other

|   |   |
|---|---|
| <b>Packaging</b>  | Flange x Traverse x Barrel (inches)         |
| a) 5000 FT  | 12 x 12 x 3.5 Continuous length             |
| b) 2000 FT  | 12 x 4.5 x 3.5 Continuous length            |
| c) 1000 FT  | 10 x 4 x 3.5 Continuous length              |
| d) 500 FT   | 6.5 x 4 x 2.5 Continuous length             |
| e) 100 FT   | 6.5 x 2 x 1.9 Continuous length             |
| f) Bulk(Made-to-order)  |   |
|   | <i>[Spool dimensions may vary slightly]</i> |
| <b>Notes:</b>   |   |
| a) Pink and put-ups other than 1000 and 500 ft. are available by special order only and minimums may apply. |   |

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207  
Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure the accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.



Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207  
Tel: 1-800-52 ALPHA (25742), Web: www.alphawire.com

## RoHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number:781816

781816 , RoHS-Compliant Commencing With11/21/2006Production

*This document certifies that the Alpha part numbers cited above are manufactured in accordance with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003, better known as the RoHS Directives, with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The reader is referred to these Directives for the specific definitions and extents of these Directives. **No Exemptions are required for RoHS Compliance on this item.***

| <b>Substance</b>                      | <b>Maximum Control Value</b> |
|---------------------------------------|------------------------------|
| Lead                                  | 0.1% by weight (1000 ppm)    |
| Mercury                               | 0.1% by weight (1000 ppm)    |
| Cadmium                               | 0.01% by weight (100 ppm)    |
| Hexavalent Chromium                   | 0.1% by weight (1000 ppm)    |
| Polybrominated Biphenyls (PBB)        | 0.1% by weight (1000 ppm)    |
| Polybrominated Diphenyl Ethers (PBDE) | 0.1% by weight (1000 ppm)    |
| Including Deca-BDE                    | 0.1% by weight (1000 ppm)    |

*The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.*

Authorized Signatory for the Alpha Wire Company:



Dave Watson, Director of Engineering & QA

11/1/2012