

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



TEL: 973-328-3200 FAX: 973-328-313

#D130 DAFLEX Vinyl Coated Fiberglass Tubing 130°C

**Description:** Made from an inorganic fiberglass base sleeving with a heat resistant extremely flexible, tough plastic insulation coating. DAFLEX 130 Class B (4000V), Grade B-1 is recommended for continuous temperatures of -20°C up to 130°C. It is constructed to provide a tough, flexible, heat resistant sleeving. Daflex 130 cuts cleanly. It will not fray or support combustion.

Meets MIL-I-3190C, NEMA VSI ASTM D372. MIL-I-21557.

Passes UL VW-1 flame test. UL standard 1441.

DAFLEX Part No.	Size	MIL-I-3190 Size	Inside Diameter (IN.)			Std. Spool or Coil
			MIN.	NOM.	MAX.	
D130-24	24	01	0.02	.022	0.027	100', 1000'
D130-22	22	02	0.025	.027	0.032	100', 1000'
D130-20	20	03	0.032	.034	0.039	25', 100', 1000'
D130-18	18	04	0.036	.042	0.049	25', 100', 1000'
D130-17	17	05	0.040	.047	0.054	100', 1000'
D130-16	16	06	0.051	.053	0.061	25', 100', 1000'
D130-15	15	07	0.057	.059	0.067	100', 1000'
D130-14	14	08	0.064	.066	0.074	25', 100', 1000'
D130-13	13	09	0.072	.076	0.082	100', 500', 1000'
D130-12	12	10	0.081	.085	0.091	25', 100', 500', 1000'
D130-11	11	11	0.091	.095	0.101	100'
D130-10	10	12	0.102	.106	0.112	25', 100', 500', 1000'
D130-9	9	13	0.114	.118	0.124	100'
D130-8	8	14	0.129	.133	0.141	25', 100', 500'
D130-7	7	15	0.144	.148	0.158	100'
D130-6	6	16	0.162	.166	0.178	100', 250'
D130-5	5	17	0.182	.186	0.198	100'
D130-4	4	18	0.204	.208	0.224	100', 250'
D130-3	3	19	0.229	.234	0.249	100'
D130-2	2	20	0.258	.263	0.278	100', 250'
D130-1	1	21	0.289	.294	0.311	100'
D130-0	0	22	0.325	.330	0.347	100'
D130-3/8	3/8"	23	0.375	.387	0.399	100'
D130-7/16	7/16"	24	0.438	.450	0.462	100'
D130-1/2	1/2"	25	0.500	.512	0.524	100'
D130-5/8	5/8"	26	0.625	.640	0.655	100'
D130-3/4	3/4"	27	0.750	.768	0.786	100'
D130-7/8	7/8"	28	0.875	.893	0.911	100'
D130-1"	1"	29	1.000	1.006	1.036	100'

**Stock Colors:** Black, Yellow. Other colors available.

All the above tubing can be ordered cut to your specifications.

\*Please call for quantities less than 100'.

**Specifications:** NEMA VS-1, ASTM D372 Grade B-B-1 (4000V), UL standard 1441. Grade A & Mil-1-21557 constructions available to order.

**DAFLEX Vinyl Coated  
Fiberglass Tubing Assortments**

These handy assortments are ideal for labs and experimentation.

Vinyl Coated Fiberglass Kits		
DAFLEX Cat. No.	No. of 6" Lengths/Pack	Tubing Size
D130PA-1	30	#24 Thru 12
D130PA-2	15	#11 Thru 0
D130PA-3	10	#3/8 Thru 1"