

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



TEL: 973-328-3200 FAX: 973-328-3130

[Home](#) > [Tubing](#) > [Non-Shrinkable Tubing](#) > #D200 DAFLEX Silicone Rubber Coated Fiberglass Sleeving MIL-I-3190/6

#D200 DAFLEX Silicone Rubber Coated Fiberglass Sleeving MIL-I-3190/6

Description: Braided fiberglass sleeving with a uniform coating of silicone rubber. Cuts cleanly and will not fray. The tubing remains flexible from -55°C to +200°C. Can be "pushed-back" easily; has high cut through resistance, and is unaffected by corona, ozone, radiation, weathering and fungus, with excellent abrasion, chemical and moisture resistance, self-extinguishes flame. UL Rated: 600V.

This series is RoHS compliant.

DAFLEX Cat. No.	Size	MIL-I-3190 Size	Inside Diameter (IN.)			Stock Spool or Coil
			Min.	Nom.	Max.	
D200-24	24	01	0.02	0.022	0.027	100', 500', 1000'
D200-22	22	02	0.025	0.027	0.032	100', 500', 1000'
D200-20	20	03	0.032	0.034	0.039	100', 500', 1000'
D200-18	18	04	0.040	0.042	0.049	100', 500', 1000'
D200-16	16	06	0.051	0.053	0.061	100', 500', 1000'
D200-15	15	07	0.057	0.059	0.067	100', 500', 1000'
D200-14	14	08	0.064	0.066	0.074	100', 500'
D200-13	13	09	0.072	0.076	0.082	100', 500'
D200-12	12	10	0.081	0.085	0.091	100', 500'
D200-11	11	11	0.091	0.095	0.101	100', 500'
D200-10	10	12	0.102	0.106	0.112	100', 500'
D200-9	9	13	0.114	0.118	0.124	100', 500'
D200-8	8	14	0.129	0.133	0.141	100', 500'
D200-7	7	15	0.144	0.148	0.158	100', 500'
D200-6	6	16	0.162	0.166	0.178	100'
D200-5	5	17	0.182	0.186	0.198	100'
D200-4	4	18	0.204	0.208	0.224	100'
D200-3	3	19	0.229	0.234	0.249	100'
D200-2	2	20	0.258	0.263	0.278	100'
D200-1	1	21	0.289	0.294	0.311	100'
D200-0	0	22	0.325	0.330	0.347	100'
D200-3/8	3/8"	23	0.375	0.387	0.399	100'
D200-7/16	7/16"	24	0.438	0.450	0.462	100'
D200-1/2	1/2"	25	0.500	0.512	0.524	100'
D200-5/8	5/8"	26	0.625	0.640	0.655	100'
D200-3/4	3/4"	27	0.750	0.768	0.786	100'
D200-7/8	7/8"	28	0.875	0.893	0.911	100'
D200-1"	1"	29	1.000	1.006	1.036	100'

Stock Color: White. Additional colors and grades available to order.

Specifications: NEMA Grade A, (7000V) Class "R", VS-1, ASTM-D372, UL Standard 1441, MIL-I-3190/6 Grade A.