

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Ultra Low Inductance Multilayer Ceramic Chip Capacitors CLL Series

FEATURES

- Features a unique internal structure that cancels magnetic fields to reduce inductance.
- Compact and lightweight
- This product contains no lead and supports lead-free soldering.

APPLICATIONS

Power supply circuits for CPUs and high-speed digital ICs.

PRODUCT IDENTIFICATION

CLL D11 X7R 1C 473 M □
(1) (2) (3) (4) (5) (6) (7)

(1) Series name

(2) Dimension code

D11	2.0×1.25mm
-----	------------

(3) Capacitance temperature characteristics

Class 2

Temperature characteristics	Capacitance change	Temperature range
X7R	±15%	-55 to +125°C
X7S	±22%	-55 to +125°C

(4) Rated voltage Edc

1C	16V
1A	10V
0J	6.3V
0G	4V

(5) Nominal capacitance

The capacitance is expressed in three digit codes and in units of pico farads (pF).

The first and second digits identify the first and second significant figures of the capacitance.

The third digit identifies the multiplier.

R designates a decimal point.

473	47,000pF
-----	----------

(6) Capacitance tolerance


Symbol	Tolerance
M	±20%

(7) Packaging style

T	Taping (reel)
B	Bulk

CLLD11 TYPE

SHAPES AND DIMENSIONS



Dimensions in mm



CAPACITANCE RANGES: CLASS 2

TEMPERATURE CHARACTERISTICS: EIA X7R(±15%)

RATED VOLTAGE Edc: 16V

Capacitance (pF)	Tolerance	Thickness T (mm)max.	Part number
47,000	±20%	0.55	CLLD11X7R1C473M
68,000	±20%	0.55	CLLD11X7R1C683M

RATED VOLTAGE Edc: 10V

Capacitance (pF)	Tolerance	Thickness T (mm)max.	Part number
100,000	±20%	0.55	CLLD11X7R1A104M
220,000	±20%	0.55	CLLD11X7R1A224M
330,000	±20%	0.95	CLLD11X7R1A334M
470,000	±20%	0.95	CLLD11X7R1A474M

RATED VOLTAGE Edc: 6.3V

Capacitance (pF)	Tolerance	Thickness T (mm)max.	Part number
330,000	±20%	0.55	CLLD11X7R0J334M
680,000	±20%	0.95	CLLD11X7R0J684M

TEMPERATURE CHARACTERISTICS: EIA X7S(±22%)

RATED VOLTAGE Edc: 6.3V

Capacitance (pF)	Tolerance	Thickness T (mm)max.	Part number
470,000	±20%	0.55	CLLD11X7S0J474M

RATED VOLTAGE Edc: 4V

Capacitance (pF)	Tolerance	Thickness T (mm)max.	Part number
680,000	±20%	0.55	CLLD11X7S0G684M
1,000,000 [1μF]	±20%	0.95	CLLD11X7S0G105M
1,500,000	±20%	0.95	CLLD11X7S0G155M
2,200,000	±20%	0.95	CLLD11X7S0G225M

- For more information about the products of other capacitance or data, please contact us.