

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。


Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Mid-high Voltage Ceramic Capacitors(Disk with Lead) Low Dissipation at High Frequency CK45-RR Series

Conformity to RoHS Directive

SHAPES AND DIMENSIONS



CAPACITANCE TEMPERATURE CHARACTERISTICS AND TOLERANCE

Temperature characteristics	Temperature range	Capacitance tolerance
R(+15, -30%)	-25 to +125°C	K(±10%)

CAPACITANCE AND DIMENSIONS

RATED VOLTAGE Edc: 1kV

Part No.	Capacitance (pF)	Dimensions (mm)		
		øD max.	T max.	F
CK45-R3AD101K-NR	100*	6	5	5±1.5
CK45-R3AD121K-NR	120	6	5	5±1.5
CK45-R3AD151K-NR	150*	6	5	5±1.5
CK45-R3AD181K-NR	180	6	5	5±1.5
CK45-R3AD221K-NR	220*	6	5	5±1.5
CK45-R3AD271K-NR	270	6	5	5±1.5
CK45-R3AD331K-NR	330*	6.5	5	5±1.5
CK45-R3AD391K-NR	390	6.5	5	5±1.5
CK45-R3AD471K-NR	470*	7	5	5±1.5
CK45-R3AD561K-NR	560	7.5	5	5±1.5
CK45-R3AD681K-NR	680*	8	5	5±1.5
CK45-R3AD821K-NR	820	8.5	5	5±1.5
CK45-R3AD102K-NR	1,000*	9	5	5±1.5
CK45-R3AD122K-NR	1,200	9.5	5	5±1.5
CK45-R3AD152K-NR	1,500*	10	5	5±1.5
CK45-R3AD182K-NR	1,800	10.5	5	5±1.5
CK45-R3AD222K-NR	2,200*	11.5	5	7.5±1.5
CK45-R3AD272K-NR	2,700	12.5	5	7.5±1.5
CK45-R3AD332K-NR	3,300*	13.5	5	7.5±1.5
CK45-R3AD392K-NR	3,900	14.5	5	7.5±1.5
CK45-R3AD472K-NR	4,700*	15.5	5	10±2

* 1kV and 2kV are E6 series standard products.

RATED VOLTAGE Edc: 2kV

Part No.	Capacitance (pF)	Dimensions (mm)		
		øD max.	T max.	F
CK45-R3DD101K-NR	100*	6	5	5±1.5
CK45-R3DD121K-NR	120	6	5	5±1.5
CK45-R3DD151K-NR	150*	6	5	5±1.5
CK45-R3DD181K-NR	180	6.5	5	5±1.5
CK45-R3DD221K-NR	220*	7	5	5±1.5
CK45-R3DD271K-NR	270	7	5	5±1.5
CK45-R3DD331K-NR	330*	7.5	5	5±1.5
CK45-R3DD391K-NR	390	8	5	5±1.5
CK45-R3DD471K-NR	470*	8.5	5	5±1.5
CK45-R3DD561K-NR	560	9	5	5±1.5
CK45-R3DD681K-NR	680*	9.5	5	5±1.5
CK45-R3DD821K-NR	820	10	5	5±1.5
CK45-R3DD102K-NR	1,000*	11	5	5±1.5
CK45-R3DD122K-NR	1,200	11.5	5	7.5±1.5
CK45-R3DD152K-NR	1,500*	12	5	7.5±1.5
CK45-R3DD182K-NR	1,800	13.5	5	7.5±1.5
CK45-R3DD222K-NR	2,200*	14.5	5	7.5±1.5
CK45-R3DD272K-NR	2,700	15.5	5	10±2
CK45-R3DD332K-NR	3,300*	17	5	10±2
CK45-R3DD392K-NR	3,900	18	5	10±2
CK45-R3DD472K-NR	4,700*	19.5	5	10±2

* 1kV and 2kV are E6 series standard products.

RATED VOLTAGE Edc: 3kV

Part No.	Capacitance (pF)	Dimensions (mm)		
		øD max.	T max.	F
CK45-R3FD101K-NR	100	6	6	7.5±1.5
CK45-R3FD121K-NR	120	6.5	6	7.5±1.5
CK45-R3FD151K-NR	150	7	6	7.5±1.5
CK45-R3FD181K-NR	180	7	6	7.5±1.5
CK45-R3FD221K-NR	220	7.5	6	7.5±1.5
CK45-R3FD271K-NR	270	8	6	7.5±1.5
CK45-R3FD331K-NR	330	8.5	6	7.5±1.5
CK45-R3FD391K-NR	390	9	6	7.5±1.5
CK45-R3FD471K-NR	470	9.5	6	7.5±1.5
CK45-R3FD561K-NR	560	10	6	7.5±1.5
CK45-R3FD681K-NR	680	10.5	6	7.5±1.5
CK45-R3FD821K-NR	820	11.5	6	7.5±1.5
CK45-R3FD102K-NR	1,000	12	6	7.5±1.5
CK45-R3FD122K-NR	1,200	13	6	7.5±1.5
CK45-R3FD152K-NR	1,500	14.5	6	7.5±1.5
CK45-R3FD182K-NR	1,800	15.5	6	10±2
CK45-R3FD222K-NR	2,200	16.5	6	10±2
CK45-R3FD272K-NR	2,700	18	6	10±2

- For more information about the products of other capacitance or data, please contact us.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.
- All specifications are subject to change without notice.