

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Series 516 Tools for Contacts and Connectors

Crimp Tools, Contact Insertion and Ejection Tools, Round Nut Driver



CONTACT CRIMP MACHINE

- Part Number 516-280-100
- Crimps Contact Part Number 516-290-591
- Guards and Microswitches for Operator Safety
- Easy Access for Quick Crimp Setting Changes
- Foot Switch Operation to Initiate Machine Cycle
- Cycle Speed Control (with Set-up Speed Option) on Circuit Board
- Each Cycle Crimps Contact, Cuts the Contact Away from the Carrier and Feeds a New Contact into Position
- Separate Crimp Settings for Conductor and Insulation
- Infinite Adjustment to Crimp Setting Between 18 and 28 AWG
- High Mechanical Advantage with Reliable Toggle Action for Precise Crimp Dimensional Control, 1" (25.4mm) Die Stroke, Effective Capacity 3 Tons (9.8 kN)
- Mounts with Bolts to any Bench Surface
- 80 psi (552 kPa) Minimum Air Supply and 117 V Electrical Supply Required, Voltage Transformers Available upon Request

CONTACT HAND CRIMP TOOL (1)

- Part Number 516-280-200
- Crimps Contact Part Number 516-290-590
- Precise Tool for Hand Crimping Loose Contacts
- Built-in Ratchet to Prevent Under Crimping

CONTACT EJECTION TOOL (2)

- Part Number 516-280-300
- For Use with All 516 Series Contact Styles
- Provides Easy Positive Ejection without Damage to the Insulator

CRIMP CONTACT INSERTION TOOL (3)

- Part Number 516-280-400
- For Installing 516-290-590 & -591 Crimp Contacts
- Wire Groove Locates the Tool onto the End of the Crimp Form

POLARIZING HARDWARE ROUND NUT DRIVER (4)

- Part Number 516-280-500
- For Removing and Tightening Round Nuts when Changing Orientation of Metal Polarizing Guide Pins and Sockets

WIRE WRAP & PC TAIL CONTACT INSERTION TOOL (5)

- Part Number 516-280-600
- For Installing 516-290-520, -540, -541 & -542 Contacts
- Slender Tube Protects Contact Tail during Insertion without Interfering with Adjacent Contacts

