

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。


## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

**NEW**

Small, High voltage resistant, 3.8 mm diameter Capacitor

# XH311HG



XH311HG is a coin type capacitor (D: 3.8mm / H: 1.1mm), with a unique quality of large current discharge, ranging from 3.3V to 0V. It is Pb-free reflowable with a high temperature heat resistance (Peak temperature of 260°C).

It is most suitable for cellphones or other mobile equipment, especially where space is limited.

## Features

- RoHs Compliant
- WEEE not applicable
- 3.3V constant charging
- Space reduction: 41% (Compared with our XH414-II06E and XH311HG-II42E)
- Pb-free reflowable
- Long cycle life

## Applications


Backup power supply for RTC(Real-time Clock) and Memory

Cellphone, Digital Still Camera, MP3 Player, PDA etc.

## Specifications

Type	Maximum Charge Voltage	Capacity (Voltage Range) Capacitance	Internal Impedance	Size		Weight
				Diameter	Height	
XH311HG	3.3V	6.5μAh (3.3V-2.0V) 0.02F	300Ω	3.8mm	1.1mm	0.04g

## Characteristics



### <APPLICATION NOTES>

- Prohibition ripple charging** : A ripple (high frequency fluctuation of voltage) in the charge voltage extremely lowers the capacitor performance. Be sure to charge capacitors with a stable voltage.
- Charge voltage** : The age deterioration of the capacitor depends on the charge voltage. The age deterioration is accelerated as charge voltage goes higher.
- Usage environment** : Aging degradation of the capacitor varies depending on the usage environment (temperature and humidity). Contact us for further details.

The information herein is subject to change without notice.

[www.sii-components.com](http://www.sii-components.com)

Seiko Instruments Inc. Micro Energy Division

1-8, Nakase, Mihama-ku, Chiba-shi, Chiba 261-8507 Japan  
TEL:+81-43-211-1735 FAX:+81-43-211-8034

