

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement



1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

NESSCAP 20F/2.3V

PSHLR-0020C0-002R3

■ Features

- Cylindrical cell
- Radial lead terminals



■ Specifications

Rated Capacitance, C (DCC⁽¹⁾, 25°C)		20 Farads	(1) Discharging with constant current
Capacitance Tolerance		-10% / +20%	
Rated Voltage, V_R		2.3 V	
Surge Voltage		2.5 V	
Rated Current (25°C)		0.016 A	About 30 min discharge rate from 2.3V to 0.9V
Max. Current-continuous (25°C)		0.5 A	40sec discharge current from V_R to 0.5 V_R
Max. Stored Energy (at V_R)		52.9J (0.0147Wh)	
Specific Energy	Gravimetric	3.7 Wh/kg	
	Volumetric	6.2 Wh/l	
Specific Power⁽²⁾ (at matched load)	Gravimetric	6.6 kW/kg	(2) Power density at which one-half the energy of the discharge is in the form of electricity and one-half is in heat.
	Volumetric	11.0 kW/l	
Maximum Internal Resistance (ESR)	AC (1kHz)	40 mΩ	
	DC (1.8A)	55 mΩ	
Dimensions		φ10 x / 30 mm	
Volume		2.4 ml	
Weight		4.0 g	
Operating temperature range⁽³⁾		-25 ~ 60 °C	(3) ΔC < 30% and ESR < 5 times of initially measured value at 25°C, respectively
Storage temperature range		-30 ~ 70 °C	
Max. Leakage Current, L_C(12h, 25°C)		300 μA	
Life Time at RT⁽⁴⁾		10 years	(4) ΔC < 30% and ESR < three times of initially measured value, respectively and LC < specified value
Cycle Life (25°C)^{(4), (5)}		100,000 cycles	(5) 1 cycle: charging to V_R for 40s, constant voltage charging for 10s, discharging to 1/2V_R for 40s, rest for 10s

© NESSCAP 2003. All Rights reserved. Design, Specifications are subject to change without notice.