

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .


F38

Conductive Polymer
Resin-molded Chip, High Capacitance Series


FRAMELESS™




● Adapted to the RoHS directive (2002/95/EC).



■ Type numbering system (Example : 6.3V 10μF)




■ Drawing



Case code	L	W ₁	W ₂	H	S ₁	S ₂
M	1.6±0.1	0.85±0.1	0.65±0.1	0.8±0.1	0.5±0.1	0.6±0.1
S	2.0±0.1	1.25±0.1	0.9±0.1	0.8±0.1	0.5±0.1	1.0±0.1

■ Marking



■ Standard ratings

Cap. (μF)	V	Code			Capacitance code
		4	6.3	10	
4.7	475	0G	0J	1A	S
10	106	M	M	M·S	a
22	226	M	M·S	(S)	J
33	336	S	S		n
47	476	S	(S)		s

() The series in parentheses are being developed. Please contact to your local Nichicon sales office when these series are being designed in your application.

■ Standard rating

Rated Volt (V)	Rated Capacitance (μF)	Case code	Part Number	Leakage Current (μF)	Dissipation Factor (%@120Hz)	ESR (mΩ@100kHz)	Rated Ripple (mAmps@100kHz)
4	10	M	F380G106MMA	4.0	6	200	350
	22	M	F380G226MMA	8.8	6	200	350
	33	S	F380G336MSA	13.2	6	200	450
	47	S	F380G476MSA	18.8	6	200	450
6.3	10	M	F380J106MMA	6.3	6	200	350
	22	M	F380J226MMA	13.9	6	200	350
	22	S	F380J226MSA	13.9	6	200	450
	33	S	F380J336MSA	20.8	6	200	450
10	4.7	M	F381A475MMA	4.7	6	200	350
	10	M	F381A106MMA	10.0	6	200	350
	10	S	F381A106MSA	10.0	6	200	450

■ Specifications

Item	Performance Characteristics
Category Temperature Range	-55 to +105°C (Rated temperature + 85°C)
Capacitance Tolerance	±20% (120Hz)
Dissipation Factor (at 120Hz)	Refer to the list below
ESR (100kHz)	Refer to the list below
Leakage Current	After 5 minute's application of rated voltage, leakage current at 20°C is not more than 0.1CV
Ripple Current	Refer to the list below
Damp Heat (No voltage applied)	At 60°C, 90 to 95% R.H. 500hours Capacitance Change Within -20 to +30% of initial value Dissipation Factor.....1.5 times initial specified value or less Leakage Current.....Initial specified value or less
Temperature Cycles	-55°C / +105°C 30 minutes each 5 cycle Capacitance Change Within ±20% of initial value Dissipation Factor.....Initial specified value or less Leakage Current.....Initial specified value or less
Resistance to Soldering Heat	Test Condition ; 10 second reflow at 240°C Capacitance Change Within ±20% of initial value Dissipation Factor.....1.3 times initial specified value or less Leakage Current.....Initial specified value or less
Surge	After application of surge voltage in series with a 1kΩ resistor at the rate of 30 seconds ON, 30 seconds OFF, for 1000 successive test cycles at 85°C, capacitors meet the characteristics requirements listed below. Capacitance Change...Within ±20% of initial value Dissipation Factor.....Initial specified value or less Leakage Current.....Initial specified value or less
Endurance 1	After 1000 hours' application of rated voltage in series with a 3Ω resistor at 85°C. Capacitance Change...Within ±20% of initial value Dissipation Factor...1.5 times initial specified value or less Leakage Current...Initial specified value or less
Endurance 2	After 1000 hours' application of derated voltage in series with a 3Ω resistor at 105°C, capacitors meet the characteristic requirements listed below Capacitance Change...Within ±20% of initial value Dissipation Factor...3 times initial specified value or less Leakage Current...Initial specified value or less
Shear Test	After applying the pressure load of 5N for 10±1 seconds horizontally to the center of capacitor side body which has no electrode and has been soldered beforehand on an aluminum substrate, there shall be found neither exfoliation nor its sign at the terminal electrode. 5N (0.51kg·f) For 10±1 seconds
Terminal Strength	Keeping a capacitor surface-mounted on a substrate upside down and supporting the substrate at both of the opposite bottom points 45mm apart from the center of the capacitor, the pressure strength is applied with a specified jig at the center of the substrate so that the substrate may bend by 1mm as illustrated. Then, there shall be found no remarkable abnormality on the capacitor terminals. R230 20 45 45 1mm

* As for the surge voltage refer to page 301 for details.