

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



Datasheet for part number VIP02Y1

Our Descriptive Part Number: VIP02Y1
Our Global Manufacturing Part Number: 000L04990
Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR

Product Datasheet	
SERIES	Panel Source (male contact)
SHELL STYLE	Panel Receptacle
LABLE COLOR	Blue
CONTACT TYPE	700 A threaded post
MAXIMUM CURRENT RATING	700 A
MAXIMUM RATED VOLTAGE TO EARTH	1,5K Vac / 2K Vdc
MINIMUM FLASHOVER	9K Vdc or Ac peak
OPERATING TEMPERATURE RANGE	-40°/+100°
INSULATION RESISTANCE	up to 5000 Mohms
INGRESS PROTECTION (MATED)	IP67
PROTECTION AGAINST ELECTRICAL SHOCK	IP2X
FLAMMABILITY	UNI 11170 Compliant (I2F2 grade)
CONTACT RETENTION	Mechanical
MATING METHOD	Double start thread
MATING CYCLES	500
OPERATING VOLTAGE	1,5K Vac / 2K Vdc
SHELL MATERIAL FINISH	Thermoplastic
CABLE RANGE	up to 240 sqmm
KEYS ORIENTATION	120°