





阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .


APPLICABLE STANDARD				
RATING	Operating Temperature Range	-55 °C to 105 °C ⁽¹⁾	Storage Temperature Range	-10 °C to 60 °C ⁽²⁾
	Voltage	600 V AC/DC	Storage Humidity Range	40 % to 70 % ⁽²⁾
	Current	15A	Operating Humidity Range	Relative Humidity 85% max (Not dewed)
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
General Examination	Visually and by measuring instrument.	According to drawing.	×	×
Marking	Confirmed visually.		×	×
ELECTRIC CHARACTERISTICS				
Contact Resistance	10 mA(DC or 1000Hz)	2 mΩ MAX.	×	—
Insulation Resistance	1000 V DC.	1000 MΩ MIN.	×	—
Voltage Proof	1800 V AC for 1 min.	No flashover or breakdown.	×	—
MECHANICAL CHARACTERISTICS				
Insertion and Withdrawal Forces	Measured by applicable connector.	Insertion Force: 10 N MAX. Withdrawal Force: 0.4 N MIN.	×	—
Mechanical Operation	100 times insertions and extractions.	① Contact Resistance: 5 mΩ MAX. ② No damage, crack and looseness of parts.	×	—
Vibration	Frequency 10 to 55 to 10Hz, approx 5min Single amplitude : 0.75 mm, 10 cycles for 3 axial directions.	① No electrical discontinuity of 1 μs. ② No damage, crack and looseness of parts.	×	—
Shock	490 m/s ² , duration of pulse 11 ms, 3 times to both directions in 3 axial directions.		×	—
ENVIRONMENTAL CHARACTERISTICS				
Damp Heat (Steady State)	Exposed at 40±2 °C, 90 ~ 95 %, 96 ±4h.	① Contact Resistance: 5mΩ MAX. ② Insulation Resistance: 1000 MΩ MIN. ③ No damage, crack and looseness of parts.	×	—
Rapid Change of Temperature	Temperature -55 → +105 °C Time 30 → 30 min. under 5 cycles. (Relocation time to chamber: within 2~3 MIN)		×	—
Dry heat	Exposed at +105±2°C for 96±4h.		×	—
Cold	Exposed at -55±2°C for 96±4h.		×	—
Sulfur Dioxide	Exposed at 25±2°C, 75±5%RH, 25 PPM for 96h±4h.	① Contact Resistance: 5mΩ MAX. ② No defect such as corrosion which impairs the function of connector.	×	—
Resistance to Soldering Heat	Solder bath : Solder temperature 260±5°C for immersion, duration 10±1sec. Soldering irons : 380°C MAX. for 10 sec.	No deformation of case of excessive looseness of the terminal.	×	—
Solderability	Soldered at solder temperature 240±3°C for immersion, duration 3 sec.	A new uniform coating of solder shall cover a minimum of 95 % of the surface being immersed.	×	—
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				
REMARKS ⁽¹⁾ Include temperature rise caused by current-carrying. ⁽²⁾ "Storage" means a long-term storage state for the unused product before assembly to PCB.		APPROVED	HS. OKAWA	14. 09. 12
		CHECKED	KN. SHIBUYA	14. 09. 11
		DESIGNED	DK. AIMOTO	14. 09. 11
		DRAWN	DK. AIMOTO	14. 09. 11
Unless otherwise specified, refer to JIS-C-5402, IEC60512.				
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-359161-00	
HRS	SPECIFICATION SHEET	PART NO.	FX30B-2P-7. 62DSA30	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL570-3304-3-00	△ 1/1




- NOTE
- 1 This product is packaged in tray. (42pcs/tray)
 - 2 Blemish and hit mark can be occurred through out the manufacturing process which doesn't affect quality level. Also, black spot could be observed on the surface of housing.
 - 3 For the contact NO., adjacent two pairs of leads placed back-to-back (4 leads in total) Compose one line.
 - 4 Misalignment absorbing range: ± 0.3mm max.
 - 5 The dimension in parentheses are for references.
 - 6 Lot NO. is indicated at either one of the position as shown.

2	Copper alloy	Contact area: Gold-plating 0.1 μm	4	Polystyrene			
		Lead area: Tin-plating 1.0 μm					
		Under plating: Nickel 1.0 μm	3	Phosphor bronze	Tin-plating 3.0 μm		
1	Polyamide	Black UL94V-0			Under plating: Nickel 1.0 μm		
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA	14. 09. 12	DRAWING NO.	EDC3-359161-00		
		CHECED : KN. SHIBUYA	14. 09. 12	PART NO.	FX30B-2P-7. 62DSA30		
		DESIGNED : DK. AIMOTO	14. 09. 12	CODE NO.	CL570-3304-3-00		
		DRAWN : DK. AIMOTO	14. 09. 12		1/2		


Recommended hole pattern dimension of PCB(5:1)
(Connector mounting side, PCB thickness: t=1.6mm)



1 Drawing for packaging(1:2)



A(1:1)



HRS	DRAWING NO.	EDC3-359161-00	
	PART NO.	FX30B-2P-7.62DSA30	
	CODE NO.	CL570-3304-3-00	