



阅读申明


- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement


1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



PCB LAYOUT



- Note: Not end stackable.
- Accepts JEDEC PLCCs MS-016 & MS-018 leaded plastic substrates.
- Insulator material is glass reinforced PPS.
- Standoffs provide clearance for heat dissipation and cleaning.
- Internal standoffs insure proper positioning of chip carrier in socket.
- Contacts are plated with 150 μ " tin/lead.
- Pre-lubricated available.



Application of Pre-Lubricated Sockets:

Intended as a general-purpose lubricant for tin/lead connectors, Nyetact 502M-20-UV is a solvent dispersion of a water-resistant, non-melting grease based on a plastic-compatible, synthetic hydrocarbon oil. Useful temperature range: -40° to 120°C. The active lubricant is present at 20% (by weight) in mineral spirits.

Pre-lubricated sockets are designed to meet Bellcore GR-1217-CORE specifications.

The pre-lubrication increases the reliability of standard sockets by preventing fretting corrosion.

Pre-lubricated sockets can be used for any long life applications having a tin-tin interface.

There is no degradation of lubrication during soldering or final wash. Contact the factory for other pre-lubricated products.

See page 96 for lubrication specifications.

No. of Cont-acts	A	B	C	Quantity per Tube	Ordering Information	
20	0.613	0.200	0.400	38		940-99-020-24-00X
28	0.713	0.300	0.500	33		940-99-028-24-00X
32*	.813/.713	.400/.300	.600/.500	29	*RECTANGULAR	940-99-032-24-00X
44	0.913	0.500	0.700	26		940-99-044-24-00X
52	1.013	0.600	0.800	23		940-99-052-24-00X
68	1.213	0.800	1.000	19		940-99-068-24-00X
84	1.413	1.000	1.200	16		940-99-084-24-00X
100	1.603	1.200	1.400	25		940-99-100-24-00X

X = 0 Not Lubricated
X = 1 Pre-Lubricated