

阅读申明














- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Direct Mount Terminals

Feed Through

	ADK 1		ADK 1 F ADK 3 F		MK 2/12	MK 1/3...22
						
Available Options (thickness mm) For Sheet Metal Version	1.5	2.5	1.5	2.5	Part No.	Part No.
PA	0303860000	0301060000	0476060000	0478660000		
3 pole KrG						0261620000
12 pole KrG						0261820000
12 pole PA					0241460000	
22 pole KrG						0301920000
All types except ADK 1 FT and MK 1/3... internal pin 0.8 x 2.8						
Dimensions						
Width / Length / Height with pins	mm (in.)	6/22/36.5 (.236/.87/1.44)	6/22/36.5 (.236/.87/1.44)	86/15/23 (2.68/.59/.91)	See table below	
Length of solder lug/pin	mm (in.)	8.4 (.33)	8.5/7.5 (.33/.30)	8 (.32)	5 (.20)	
Insulation stripping length	mm (in.)	9 (.35)	11 (.43)	5 (.20)	6 (.24)	
Technical Data						
Rated voltage / rated current / wire size	UL	300 V / 16 A / #22...12 AWG	300 V / 15 A / #26...14 AWG	300 V / 10 A / #24...12 AWG	300 V / 10 A / #24...12 AWG	
	CSA	300 V / 10 A / #26...12 AWG	300 V / 10 A / #22 ...14 AWG	300 V / 10 A / #24...12 AWG	300 V / 10 A / #22...16 AWG	
	VDE	380 VAC / 16 A / 4/1.5 mm ²	380 VAC / 20 A / 2.5/1.5 mm ²	6 VAC / 20 A / 2.5/1.5 mm ²	380 VAC / 20 A / 2.5/1.5 mm ²	
Torque	Nm (lb. in.)	0.5 (5.0)	0.9 (8.0)	0.4 (4.0)	0.4 (4.0)	
Clamping screw	M	3	2.5	2.5	2.5	
End Plate (thickness mm)	Type	Part No.	Type	Part No.	Dimensions	
	PA	AP (3) 0476260000	AP (3)	0476260000	MK 1/3	
	EP		AP (3)	0360000000		
Spacer (thickness mm)						
						
Test Plugs / Sockets						
	PS 2.3	0180400000				
Fuse Pin / Insulating Sleeves / Expansion Rivet					Type Part No.	
	SST 1.3	0306600000	SST 1.3	0306600000		
	IH 2.8	0386060000	IH 2.8	0386060000		
					SN 0200100000	
Marking Tags	Print				Type Dim. a b b₁ c	
Note: Part numbers shown are for a single card of pre-printed tags numbered 1-50. For additional information, see Accessories section.	Consecutive horizontal	DEK 5/6 0468660001	DEK 5/6 0468660001	BSTb 10/12 0245700000	MK 1/3 25 19 19 19	
	Consecutive vertical	DEK 5/6 0468760001	DEK 5/6 0468760001	BSTo 10/12 0245600000	MK 1/12 70 64 64 64.5	
					MK 1/22 120 114 114 114.5	