

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .




MVK TYPE TERMINALS ARE MANUFACTURED FROM THERMOPLASTIC RAW MATERIAL. GREY BEING THE MAIN COLOR.

MVK SERIES

MINI TERMINAL BLOCKS
FOR USE WITH
15MM WIDE DIN RAIL

MVK 2.5

WIDTH 5 MM
304 429



TORQUE: 1.2 NM

COLORS	TERMINALS	END PLATE
	PART NUMBER	PART NUMBER
	MVK 2.5	NPP
GREY	304 429	444 429
BEIGE	304 420	444 420
	MVK 4	NPP
GREY	304 439	444 429
BEIGE	304 430	444 420



ELECTRICAL RATINGS

TSE / CE (EN 60947-7-1 / EN60947-7-2)

UL

ATEX

CONNECTION DATA

SOLID STRAND, SCREW CON. - FINE STRAND, SCREW CON.

AWG CONDUCTOR / FINE STRAND WITH FERRULE

INSULATION STRIPPING LENGTH / TORQUE

ORDERING DATA

POLYAMIDE 66

GREY

YELLOW-GREEN

END BRACKET

THICKNESS 8MM

KD 5



GREY

END PLATE - DISCONNECT PLATE

WIDTH 1.5 MM -

POLYAMIDE 66



GREY

YELLOW-GREEN

SMALL PARTITION



GREY

CROSS CONNECTION



TEST PLUG-SOC. / INS. TEST SOC.

TF

ITK

T5K



WARNING LABEL

IP



WITH SYMBOL

WITHOUT SYMBOL

GROUP MARKING

GE



GE2



GREY

TECHNICAL DATA

- MAX.CLAMPING RANGE / MAX. TECHNICAL DATA
- RATED IMPULSE VOLTAGE / POLLUTION SEVERITY
- INSULATION MATERIAL GROUP / GAUGE PIN CODE ACCORDING TO IEC 60947-1
- PROTECTION CLASS / PROTECTION CONDUCTOR TYPE

MARKING TAGS

SEE PAGES 104 & 105 FOR FURTHER DETAIL

VOLTAGE/CURRENT/CROSS-SECTION

400 V ~ / 24 A / 2.5 MM²

300 V ~ / 20 A / AWG 26-12

400 V ~ / 23 A

0.5 - 4 MM² / 0.5 - 4 MM²

16 - 8 / 0.5 - 2.5 MM²

12 MM / 1.2 NM

TYPE	PART. NO.	QTY.
MVK 2.5	304 429	100

KD 5	495 069	100
------	----------------	-----

NPP MVK	444 429	100
---------	----------------	-----

AD1	467 919	100
-----	----------------	-----

UK 2.5/2	476 222	25
----------	----------------	----

UK 2.5/3	476 223	20
----------	----------------	----

UK 2.5/4	476 224	15
----------	----------------	----

UK 2.5/10	476 229	5
-----------	----------------	---

TF (Ø2)	493 020	5
---------	----------------	---

IP 2 S	498 130	25
--------	----------------	----

IP 2	498 140	25
------	----------------	----

GE	496 119	50
----	----------------	----

GE 2	496 250	25
------	----------------	----

0.2 - 4 MM² / 4 MM² / 32 A

6 KV / 3

1 / B3

IP 20 / -