


阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



General ordering data

Order No.	0518960011
Part designation	DEK 6 FWZ 11-20
Version	Connector markers, L x W: 6 x 5 mm, Polyamide, white
EAN	4008190104948
Qty.	500 pc(s).

Markings

Cadmium	no
Can be labelled with thermal transfer printers	No
Can be printed with plotter	No
Can be written with dot-matrix printer	No
Can be written with laser printer	No
Colour of printing	black
Function	Connector markers
Halogen	no
Length	6 mm
Material	Polyamide
Material colour	white
Material colour according to resistance code	9
Max. temperature, continuous	100 °C
Min. temperature, continuous	-40 °C
Orientation of print	horizontal
Pin can be written (STI)	No
Pitch	6 mm
PrintJet	No
Printed characters	Numbers
Printing method	MC Laser
Silicone	no
Speed marking laser	No
Type of printing	Standard
UL 94 flammability class	V2
Width	5 mm

Classifications

ETIM 2.0	EC000761
ETIM 3.0	EC000761
eClass 4.1	24-19-02-19
eClass 5.0	27-14-11-37
eClass 5.1	27-14-11-37

Similar products

Order No.	Part designation	Version
0518960001	DEK 6 FWZ 1 TO 10	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960021	DEK 6 FWZ 21-30	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960031	DEK 6 FWZ 31-40	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960041	DEK 6 FWZ 41-50	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960051	DEK 6 FWZ 51-60	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960061	DEK 6 FWZ 61-70	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960071	DEK 6 FWZ 71-80	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960081	DEK 6 FWZ 81-90	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960091	DEK 6 FWZ 91-100	Connector markers, L x W: 6 x 5 mm, Polyamide, white
0518960151	DEK 6 FWZ 151-160	Connector markers, L x W: 6 x 5 mm, Polyamide, white