

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

General ordering data

Order No.	9129920000
Part designation	SAK 4/EN RT
Version	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, red, TS 35 + TS 32
EAN	4008190465483
Qty.	100 pc(s).

Product notes

Note, technical data	With twin ferrules ZH 0.5 to ZH 2.5, rated voltage is 690 V.
----------------------	--

PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA97ATEX1798U
IECEX Certificate of Conformity	IECEXKEM06.0014U
ATEX voltage	690 V
ATEX current	28 A
ATEX conductor cross-section	4 mm ²
IECEX voltage	690 V
IECEX current	28 A
IECEX conductor cross-section	4 mm ²
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

Additional technical data

Colour of insulating material	red
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35 + TS 32
Insulating material	Polyamide
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Feed-through terminal

CSA rating data

Min. cross-section (CSA)	AWG 26
--------------------------	--------

Conductors for clamping (additional connection)

Min. conductor cross-section (UL)	AWG 12
Max. conductor cross-section (UL)	AWG 22
Min. conductor cross-section (CSA)	AWG 10
Max. conductor cross-section (CSA)	AWG 26

Conductors for clamping (rated connection)

Clamping range, min.	0.13 mm ²
Clamping range, max.	6 mm ²
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	12 mm
Clamping screw	M 3
Blade size	0.6 x 3.5 mm
Tightening torque range	0.5...1.0 Nm
Torque level with DMS electric screwdriver	2
Gauge to IEC 60947-1	A4
Solid, min.	0.5 mm ²
Solid, max.	6 mm ²
Stranded, min.	0.5 mm ²
Stranded, max.	4 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	4 mm ²
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228/1)	4 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm ²
Twin wire-end ferrule, min.	0.5 mm ²
Twin wire end ferrule, max.	2.5 mm ²
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 10
AWG conductor size, min.	0.13 mm ²
AWG conductor size, max.	5.26 mm ²

Dimensions

Width	6.5 mm
Height of lowest version	47.5 mm
Length	42 mm
Weight	11.73 g
TS 32 offset	6 mm
TS 35 offset	0 mm

Disconnect terminals

Torque level with DMS electric screwdriver	2
--	---

Rating data

Rated cross-section	4 mm ²
Rated voltage	800 V
Rated impulse voltage	8 kV
Rated current	32 A
Standards	IEC 60947-7-1
Current with max. conductor	41 A
Pollution severity	3

UL rating data

Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

Approvals

Approvals institutes



Classifications

eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Similar products

Order No.	Part designation	Version
1907040000	DK 4 Q/EN	Feed-through terminal, 4 mm ² , Screw connection, PA 66, beige, TS 35 + TS 32
1907030000	DK 4 Q/EN BL	Feed-through terminal, 4 mm ² , Screw connection, PA 66, blue, TS 35 + TS 32
1907020000	DK 4 QV/EN	Feed-through terminal, 4 mm ² , Screw connection, PA 66, beige, TS 35 + TS 32
1784410000	SAK 10/EN BL	Feed-through terminal, 10 mm ² , Screw connection, PA 66, blue, TS 35 + TS 32
1772830000	SAK 10/EN OR	Feed-through terminal, 10 mm ² , Screw connection, PA 66, TS 35 + TS 32
1773900000	SAK 10/EN SW	Feed-through terminal, 10 mm ² , Screw connection, PA 66, TS 35 + TS 32
0218660000	SAK 2.5/EN	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, beige, TS 35 + TS 32
0218680000	SAK 2.5/EN BL	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, blue, TS 35 + TS 32
0467460000	SAK 4/EN	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, beige, TS 35 + TS 32
0337660000	SAK 10/EN	Feed-through terminal, 10 mm ² , Screw connection, PA 66, beige, TS 35 + TS 32
1853960000	SAK 10/EN GR RAL 7042	Feed-through terminal, 10 mm ² , Screw connection, PA 66, TS 35 + TS 32
0339760000	SAK 16/EN	Feed-through terminal, 16 mm ² , Screw connection, PA 66, beige, TS 35 + TS 32
1784390000	SAK 16/EN BL	Feed-through terminal, 16 mm ² , Screw connection, PA 66, blue, TS 35 + TS 32
1880870000	SAK 2.5/EN RT	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, red, TS 35 + TS 32

1858440000	SAK 2.5/EN SW	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, black, TS 35 + TS 32
1858460000	SAK 2.5/EN WS	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, white, TS 35 + TS 32
0467480000	SAK 4/EN BL	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, blue/light blue, TS 35 + TS 32
0339860000	SAK 35/EN	Feed-through terminal, 35 mm ² , Screw connection, PA 66, beige, TS 35 + TS 32
1784400000	SAK 35/EN BL	Feed-through terminal, 35 mm ² , Screw connection, PA 66, blue, TS 35 + TS 32
9130990000	SAK 4/EN BR	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, brown, TS 35 + TS 32
9129930000	SAK 4/EN GE	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, yellow, TS 35 + TS 32
9129950000	SAK 4/EN GN	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, green, TS 35 + TS 32
9129960000	SAK 4/EN GR	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, grey, TS 35 + TS 32
1853950000	SAK 4/EN GR 7042	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, grey, TS 35 + TS 32
0467400000	SAK 4/EN OR	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, Orange, TS 35 + TS 32
9130980000	SAK 4/EN SW	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, black, TS 35 + TS 32
1773340000	SAK 4/EN WS	Feed-through terminal, 4 mm ² , Screw connection, Polyamide, white, TS 35 + TS 32
0212860000	SAK 6/EN	Feed-through terminal, 6 mm ² , Screw connection, PA 66, beige, TS 35 + TS 32
0212880000	SAK 6/EN BL	Feed-through terminal, 6 mm ² , Screw connection, PA 66, blue, TS 35 + TS 32
1772820000	SAK 6/EN GE	Feed-through terminal, 6 mm ² , Screw connection, PA 66, TS 35 + TS 32
1772810000	SAK 6/EN OR	Feed-through terminal, 6 mm ² , Screw connection, PA 66, TS 35 + TS 32
0212840000	SAK 6/EN RT	Feed-through terminal, 6 mm ² , Screw connection, PA 66, TS 35 + TS 32
0212810000	SAK 6/EN SW	Feed-through terminal, 6 mm ² , Screw connection, PA 66, TS 35 + TS 32
1773350000	SAK 6/EN WS	Feed-through terminal, 6 mm ² , Screw connection, PA 66, white, TS 35 + TS 32