


阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



tightening torque/thread 1.0 Nm/M 3 Inspection Test Pattern Size A 4

Type	Cat.-No.		Qty.p.pck.
SR 4 DRL	41211.2	beige	100
SR 4 DRL	41211.5	blue	100


Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	500 V	500 V
Rated Current	20 A AWG 12	26 A	26 A	24 A

Max Rated Cross Section

Single Wire (solid)	0.2-4 mm ²
Stranded Wire (flexible)	0.2-2.4 mm ²
Wire Size	AWG 22-12

Dimensions	TS 32	TS 35
LxBxH (mm)	67x6x52	67x6x47
Stripped Length	9 mm	



tightening torque/thread 2.0 Nm/M 4 Inspection Test Pattern Size A 5

Type	Cat.-No.		Qty.p.pck.
SR 10	41005.2	beige	100
SR 10	41005.5	blue	100

Additional colors available. See page 114.

Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	750 V	800 V
Rated Current	65 A AWG 8	55 A	61 A	57 A

Max Rated Cross Section

Single Wire (solid)	0.2-10 mm ²
Stranded Wire (flexible)	0.2-10 mm ²
Wire Size	AWG 22-8

Dimensions	TS 32	TS 35
LxBxH (mm)	48x8x52	48x8x47
Stripped Length	12 mm	

Type:	Cat.-No.	Qty.p.pck.	Terminal accessories	Type:	Cat.-No.	Qty.p.pck.
AP 2.5 RL	2575.2 beige 2575.5 blue	50	End plate	AP 2.5-10	2001.2 beige 2001.5 blue	50
			Isolation partition	TW 2.5-10	2002.2 beige 2002.5 blue	50
TRS 1	2003.2 beige	100	Separator	TRS 1	2003.2 beige	100
ES 32/35 Combi	1424.2 beige		End bracket	ES 32/35 Combi	1424.2 beige	
ES 32/K/ST	2827.0	50		ES 32/K/ST	2827.0	50
ES 35/2/K	2826.2 beige		End bracket	ES 35/2/K	2826.2 beige	
ES 35/K/ST	2828.0	50		ES 35/K/ST	2828.0	50
STB 14/2.3	2006.0	50	Test socket	STB 14/4	2050.0	50
PS 2.3	2007.0	20	Test plug	PS 4	2051.0	20
QL 2	2008.0	50	Switchable link	QL 2	2053.0	50
VH 19	2009.0	100	Connection sleeve	VH 19	2009.0	100
BS M 3x25	2010.0	100	Screw	BS M 3x25	2010.0	100
AD 4	2011.0	50	Warning tag (German)	AD 4	2054.0	50
AD 4 E	2494.0	50	Warning tag (English)	AD 4 E	2495.0	50
BSK M 3x22	2012.0	100	Plastic screw for warning tag	BSK M 3x22	2012.0	100
Q2/Q1 2	2019.0/2740.2	50	Cross-connection/Insulated cross-connection	Q2/Q1 2	2060.0/2750.2	50
Q3/Q1 3	2020.0/2741.2	50	Cross-connection/Insulated cross-connection	Q3/Q1 3	2061.0/2751.2	50
Q4/Q1 4	2021.0/2742.2	20	Cross-connection/Insulated cross-connection	Q4/Q1 4	2062.0/2752.2	20
Q10/Q1 10	2022.0/2743.2	10	Cross-connection/Insulated cross-connection	Q10/Q1 10	2063.0/2753.2	10