

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

General ordering data

Order No.	0322860000
Part designation	SAK 2.5/10
Version	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, beige, TS 32
EAN	4008190050252
Qty.	10 pc(s).

Product notes

Note, technical data	With twin ferrules ZH 0.5 to ZH 1.5, rated voltage is 690 V.
----------------------	--

PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA97ATEX1798U
Download, German	KEMA97ATEX1798U_d.pdf
Download English	KEMA97ATEX1798U_e.pdf
IECEX Certificate of Conformity	IECEXKEM06.0014U
ATEX voltage	550 V
ATEX current	21 A
ATEX conductor cross-section	2.5 mm ²
IECEX voltage	550 V
IECEX current	21 A
IECEX conductor cross-section	2.5 mm ²
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

Additional technical data

Colour of insulating material	beige
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	Yes
Installation advice	TS 32
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	10
No. of levels	1
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Feed-through terminal

CSA rating data

Voltage (CSA)	600 V
CSA current	25 A
Min. cross-section (CSA)	AWG 26

CSA rating data

Max. cross-section (CSA) AWG 10

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1) 0.5 mm²

Flexible with ferrule, max. (DIN 46228 pt 1) 4 mm²

Conductors for clamping (rated connection)

Clamping range, min. 0.13 mm²

Clamping range, max. 6 mm²

Type of connection Screw connection

2nd type of connection screwed

Connection direction on side

No. of connections 2

Stripping length 10 mm

Clamping screw M 2.5

Blade size 0.6 x 3.5 mm

Tightening torque range 0.4...0.6 Nm

Torque level with DMS electric screwdriver 1

Gauge to IEC 60947-1 A3

Solid, min. 0.5 mm²

Solid, max. 6 mm²

Stranded, min. 0.5 mm²

Stranded, max. 4 mm²

Flexible, min. 0.5 mm²

Flexible, max. 4 mm²

Flexible with ferrule, min. (DIN 46228/1) 0.5 mm²

Flexible with ferrule, max. (DIN 46228/1) 4 mm²

Flexible, min., ferrule with plastic collar (DIN 46228 pt 4) 0.5 mm²

Flexible, max., ferrule with plastic collar (DIN 46228 pt 4) 4 mm²

Twin wire-end ferrule, min. 0.5 mm²

Twin wire end ferrule, max. 1.5 mm²

AWG conductor size, min. AWG 26

AWG conductor size, max. AWG 10

AWG conductor size, min. 0.13 mm²

AWG conductor size, max. 5.26 mm²

Dimensions

Width 6 mm

Height of lowest version 46.5 mm

Length 36.5 mm

TS 32 offset 18.5 mm

Disconnect terminals

Torque level with DMS electric screwdriver 1

Rating data

Rated cross-section 2.5 mm²

Rated voltage 800 V

Rating data

Rated impulse voltage	8 kV
Rated current	24 A
Standards	IEC 60947-7-1
Current with max. conductor	41 A
Pollution severity	3

UL rating data

Voltage (UL)	600 V
Current (UL)	20 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Similar products

Order No.	Part designation	Version
0269660000	SAK 2.5 (TSCH/32)	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, beige, TS 32
0279660000	SAK 2.5	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, beige, TS 32
0215560000	SAKD 2.5N	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, beige, TS 32
0215580000	SAKD 2.5N BL	Feed-through terminal, 2.5 mm ² , Screw connection, PA 66, blue, TS 32