

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



General ordering data

Order No.	0321320000
Part designation	SAKS 4
Version	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
EAN	4008190005313
Qty.	20 pc(s).

Product notes

Note, technical data	Connections for stranded conductors from 10 mm ² and 7-wire AWG conductors require a tightening torque of 2 Nm.
----------------------	--

Additional technical data

Colour of insulating material	Medium yellow
Connection direction	on side
End plate required	No
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	KrG
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	closed
Operating temperature range	- 60 °C, + 130 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	5VA
Version	Fuse terminal

CSA rating data

Voltage (CSA)	600 V
CSA current	30 A
Min. cross-section (CSA)	AWG 22
Max. cross-section (CSA)	AWG 8

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm ²
--	---------------------

Conductors for clamping (additional connection)

Flexible with ferrule, max. (DIN 46228 pt 1) 10 mm²

Conductors for clamping (rated connection)

Clamping range, min. 0.33 mm²
 Clamping range, max. 16 mm²
 Type of connection Screw connection
 2nd type of connection screwed
 Connection direction on side
 No. of connections 2
 Stripping length 14 mm
 Clamping screw M 4
 Blade size 1.0 x 5.5 mm
 Tightening torque range 1.2...2.4 Nm
 Torque level with DMS electric screwdriver 4
 Gauge to IEC 60947-1 B6
 Solid, min. 0.5 mm²
 Solid, max. 16 mm²
 Stranded, min. 1.5 mm²
 Stranded, max. 10 mm²
 Flexible, min. 0.5 mm²
 Flexible, max. 10 mm²
 Flexible with ferrule, min. (DIN 46228/1) 0.5 mm²
 Flexible with ferrule, max. (DIN 46228/1) 10 mm²
 AWG conductor size, min. AWG 22
 AWG conductor size, max. AWG 8
 AWG conductor size, min. 0.33 mm²
 AWG conductor size, max. 8.37 mm²

Dimensions

Width 24 mm
 Height of lowest version 66 mm
 Length 75 mm
 TS 32 offset 37.5 mm

Disconnect terminals

Torque level with DMS electric screwdriver 4

Display element

Operating voltage for display, max. 400 V
 Type of voltage for indicator AC/DC

Fuse terminals

Cartridge fuse E14
 Display Without LED
 Fuse holder (cartridge holder) Screwable
 Operating voltage, max. 230 V
 Type of voltage for indicator AC/DC

Rating data

Rated cross-section 10 mm²

Rating data

Rated voltage	400 V
Rated impulse voltage	6 kV
Rated current	16 A
Standards	IEC 60947-7-3
Current with max. conductor	16 A
Pollution severity	3

Approvals

Approvals institutes



Downloads

DXF	03403_SAKS_4_DXF.dxf
STEP	0321320000_03403_SAKS_4_STP.stp

Classifications

ETIM 2.0	EC000899
ETIM 3.0	EC000899
eClass 4.1	27-14-11-16
eClass 5.0	27-14-11-16
eClass 5.1	27-14-11-16

Similar products

Order No.	Part designation	Version
0385320000	SAKS 1/32 G20 GL 115VAC	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0306120000	SAKS 1/32 G20 GL 230VAC	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0309320000	SAKS 1/32 G25 GL 230VAC	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0191220000	SAKS 1/G20	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0191120000	SAKS 1/G25	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0206820000	SAKS 2	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0297520000	SAKS 3 G/5X30 500V	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0162220000	SAKS 4 USA	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32
0531820000	SAKS 6/GZ 500AC	Fuse terminal, 10 mm ² , Screw connection, KrG, Medium yellow, TS 32