

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Surge protection device - TT-UK5/ 60DC - 2794712

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Modular terminal block with surge voltage fine protection between clamping connector and DIN rail, nominal voltage: 60 V DC, for mounting on NS 32 or NS 35/7.5, terminal width: 6.2 mm, terminal height: 47 mm

The illustration shows version TT-UK5- 24 DC



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 072896
Weight per Piece (excluding packing)	11.17 GRM
Custom tariff number	85363030
Country of origin	Greece

Technical data

Dimensions

Height	47 mm
Width	6.2 mm
Length	42.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	PA
Inflammability class according to UL 94	V2
Color	black
Mounting type	DIN rail/G-profile rail

Surge protection device - TT-UK5/ 60DC - 2794712

Technical data

General

Type	Single-level terminal block
Number of positions	1
Direction of action	Line-Earth Ground

Protective circuit

IEC test classification	C3
VDE requirement class	C3
Nominal voltage U_N	60 V DC
Maximum continuous operating voltage U_C	70 V DC
	49 V AC
Maximum continuous voltage U_C (wire-ground)	70 V DC
	49 V AC
Nominal current I_N	32 A (50 °C)
Residual current I_{PE}	$\leq 5 \mu A$
Nominal discharge current I_n (8/20) μs (Core-Earth)	69 A
Total surge current (8/20) μs	69 A
Max. discharge current I_{max} (8/20) μs maximum (Core-Earth)	69 A
Nominal pulse current I_{an} (10/1000) μs (Core-Earth)	13.3 A
Output voltage limitation at 1 kV/ μs (Core-Earth) spike	$\leq 100 V$
Output voltage limitation at 1 kV/ μs (Core-Earth) static	$\leq 100 V$
Residual voltage at I_n , (conductor-ground)	$\leq 120 V$
Response time t_A (Core-Earth)	$\leq 1 ns$
Cut-off frequency f_g (3 dB), asym. (PE) in 150 Ohm system	typ. 3.2 MHz
Capacity (Core-Earth)	$\leq 0.65 nF$
Surge carrying capacity in acc. with IEC 61643-21 (Core-Earth)	C3 - 10 A

Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	4 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	24

Surge protection device - TT-UK5/ 60DC - 2794712

Technical data

Connection data

Conductor cross section AWG/kcmil max	12
---------------------------------------	----

Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized

Ex Approvals

Surge protection device - TT-UK5/ 60DC - 2794712

Approvals

Approvals submitted

Approval details

CSA	
mm ² /AWG/kcmil	28-10
Nominal current I _N	34 A
Nominal voltage U _N	60 V

UL Recognized	
mm ² /AWG/kcmil	26-10
Nominal current I _N	30 A
Nominal voltage U _N	60 V

cUL Recognized	
mm ² /AWG/kcmil	26-10
Nominal current I _N	30 A
Nominal voltage U _N	60 V

GOST	
------	--

GOST	
------	--


Surge protection device - TT-UK5/ 60DC - 2794712

Approvals



Drawings

Circuit diagram



Surge protection device - TT-UK5/ 60DC - 2794712

Schematic diagram

