

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



General ordering data

Order No.	0323100000
Part designation	EK 2
Version	Earth terminal, 10 mm ² , Screw connection, PA 66, TS 32
EAN	4008190013585
Qty.	20 pc(s).

Additional technical data

Connection direction	on side
End plate required	No
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	closed
Operating temperature range	- 50 °C, + 100 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Screwed
UL 94 flammability rating of insulation material	---
Version	PE terminal

CSA rating data

Min. cross-section (CSA)	AWG 16
Max. cross-section (CSA)	AWG 8

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	1.5 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	10 mm ²

Conductors for clamping (rated connection)

Clamping range, min.	1.5 mm ²
Clamping range, max.	10 mm ²
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side

Conductors for clamping (rated connection)

No. of connections	2
Stripping length	14 mm
Clamping screw	M 4
Blade size	1.0 x 5.5 mm
Tightening torque range	1.2...1.6 Nm
Torque level with DMS electric screwdriver	4
Gauge to IEC 60947-1	B6
Solid, min.	1.5 mm ²
Solid, max.	10 mm ²
Stranded, min.	1.5 mm ²
Stranded, max.	10 mm ²
Flexible, min.	1.5 mm ²
Flexible, max.	10 mm ²
Flexible with ferrule, min. (DIN 46228/1)	1.5 mm ²
Flexible with ferrule, max. (DIN 46228/1)	10 mm ²
AWG conductor size, min.	AWG 16
AWG conductor size, max.	AWG 8
AWG conductor size, min.	1.31 mm ²
AWG conductor size, max.	8.37 mm ²

Dimensions

Width	10.2 mm
Height of lowest version	38 mm
Length	52 mm
Weight	32.55 g
TS 32 offset	26 mm

Disconnect terminals

Torque level with DMS electric screwdriver	4
--	---

PE rating data

Centre screw on PE terminals	M 5
PEN function	No
Rated cross-section	10 mm ²
Rated short-time current	1200 A (10 mm ²)
Standards	IEC 60947-7-2
Tightening torque range for fixing screw	2.0...4.0 Nm
Torque level with DMS electric screwdriver	4

Rating data

Rated cross-section	10 mm ²
Standards	IEC 60947-7-2

UL rating data

Min. cross-section (UL)	AWG 16
Max. cross-section (UL)	AWG 8

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC000901
ETIM 3.0	EC000901
eClass 4.1	27-14-03-05
eClass 5.0	27-14-03-05
eClass 5.1	27-14-03-05

Similar products

Order No.	Part designation	Version
0354660000	EK 10	Earth terminal, 10 mm ² , Screw connection, PA 66, green/yellow, TS 32
0374660000	EK 16	Earth terminal, 16 mm ² , Screw connection, PA 66, green/yellow, TS 32
0474360000	EK 2.5N	Earth terminal, 2.5 mm ² , Screw connection, Polyamide, green/yellow, TS 32
0354760000	EK 35	Earth terminal, 35 mm ² , Screw connection, PA 66, green/yellow, TS 32
0354560000	EK 4	Earth terminal, 4 mm ² , Screw connection, PA 66, green/yellow, TS 32
0144400000	SAKE 35	Earth terminal, 35 mm ² , Screw connection, TS 32
0213200000	SAKE 70/32	Earth terminal, 70 mm ² , Screw connection, TS 32