

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



#### General ordering data

Order No.	0170420000
Part designation	SAKG 32 II
Version	Special terminal, special connections, 50 mm <sup>2</sup> , Screw connection, KrG, Medium yellow, TS 32
EAN	4008190011369
Qty.	10 pc(s).

#### Product notes

Note, technical data	Conductor connection with cable lugs according to DIN 46234 and DIN 46235, from 10 .. 70 mm <sup>2</sup>
----------------------	--

#### Additional technical data

Colour of insulating material	Medium yellow
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	KrG
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	Open
Operating temperature range	- 60 °C, + 130 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	5VA
Version	Stud terminal

#### CSA rating data

Voltage (CSA)	600 V
CSA current	170 A
Min. cross-section (CSA)	AWG 1
Max. cross-section (CSA)	AWG 2/0

#### Conductors for clamping (rated connection)

Clamping range, min.	10 mm <sup>2</sup>
Clamping range, max.	70 mm <sup>2</sup>
Type of connection	Screw connection

#### Conductors for clamping (rated connection)

2nd type of connection	screwed
Connection direction	on side
No. of connections	1
Clamping screw	M 8
Tightening torque range	6.0...12 Nm
AWG conductor size, min.	AWG 6
AWG conductor size, max.	AWG 3/0
AWG conductor size, min.	26.67 mm <sup>2</sup>
AWG conductor size, max.	67.44 mm <sup>2</sup>

#### Dimensions

Width	32 mm
Height of lowest version	53 mm
Length	80 mm
Weight	154 g
TS 32 offset	40 mm

#### Rating data

Rated cross-section	50 mm <sup>2</sup>
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	150 A
Standards	IEC 60947-7-1
Current with max. conductor	192 A
Pollution severity	3

#### UL rating data

Voltage (UL)	600 V
Current (UL)	200 A
Min. cross-section (UL)	AWG 6
Max. cross-section (UL)	AWG 3/0

#### Approvals

Approvals institutes



#### Downloads

STEP	0170420000_01088_SAKG_32_II_STP.stp
------	-------------------------------------

#### Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-31
eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31

## Classifications

### Similar products

Order No.	Part designation	Version
0185120000	SAKG 32 II/GW	Special terminal, special connections, 50 mm <sup>2</sup> , Screw connection, KrG, Medium yellow, TS 32
0286720000	SAKG 32 III	Special terminal, special connections, 50 mm <sup>2</sup> , Screw connection, KrG, Medium yellow, TS 32