

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

**.200"** (5.08mm)

# EL1M/2M/3M Heavy-Duty Terminal Blocks Multi-Tier, Left Offset (Standard)



## Heavy Duty

Multi-tier, .200" spacing heavy duty terminal blocks are rated at 20A, and combine a larger wire accommodation range and higher current rating with the enhanced board density provided by the multi-tier design. Moving cage clamp wire termination ensures high reliability.

## Interlocking Modules

Blocks are available in 1-, 2- and 3-tier configurations. Each configuration consists of precision molded 2- and 3-position-wide modules with interlocking dovetails. Modules can be easily assembled to length. Users have the option of purchasing and stocking only the 2- and 3-position modules, and assembling to size in-house, in order to minimize inventory and maintain flexibility; or ordering product already assembled to size.

## Options and Variations

Terminations are available in black or green. Contact Amphenol Pcd for information on marking and other application-specific variations.


### APPROVALS:




Consult factory for specific product recognitions




**EL1M 1-Tier**



**EL2M 2-Tier**



**E3LM 3-Tier**



Catalog #		Catalog #		L (In.)	Catalog #		Catalog #		L (In.)	Catalog #		Catalog #		L (In.)
Pos	Black	Green	Pos		Black	Green	Pos	Black		Green	Pos	Black	Green	
<b>EL1M Modules</b>														
2	EL1M022B00	EL1M022G00	.40											
3	EL1M032B00	EL1M032G00	.60											
<b>EL2M Modules</b>														
4	EL2M042B00	EL2M042G00	.50											
6	EL2M062B00	EL2M062G00	.70											
<b>EL3M Modules</b>														
6	EL3M062B00	EL3M062G00	.50											
9	EL3M092B00	EL3M092G00	.70											
<b>EL1M Assemblies</b>														
4	EL1M042B00	EL1M042G00	.80											
5	EL1M052B00	EL1M052G00	1.00											
6	EL1M062B00	EL1M062G00	1.20											
7	EL1M072B00	EL1M072G00	1.40											
8	EL1M082B00	EL1M082G00	1.60											
9	EL1M092B00	EL1M092G00	1.80											
10	EL1M102B00	EL1M102G00	2.00											
11	EL1M112B00	EL1M112G00	2.20											
12	EL1M122B00	EL1M122G00	2.40											
13	EL1M132B00	EL1M132G00	2.60											
14	EL1M142B00	EL1M142G00	2.80											
15	EL1M152B00	EL1M152G00	3.00											
16	EL1M162B00	EL1M162G00	3.20											
17	EL1M172B00	EL1M172G00	3.40											
18	EL1M182B00	EL1M182G00	3.60											
19	EL1M192B00	EL1M192G00	3.80											
20	EL1M202B00	EL1M202G00	4.00											
21	EL1M212B00	EL1M212G00	4.20											
22	EL1M222B00	EL1M222G00	4.40											
<b>EL2M Assemblies</b>														
8	EL2M082B00	EL2M082G00	.90											
10	EL2M102B00	EL2M102G00	1.10											
12	EL2M122B00	EL2M122G00	1.30											
14	EL2M142B00	EL2M142G00	1.50											
16	EL2M162B00	EL2M162G00	1.70											
18	EL2M182B00	EL2M182G00	1.90											
20	EL2M202B00	EL2M202G00	2.10											
22	EL2M222B00	EL2M222G00	2.30											
24	EL2M242B00	EL2M242G00	2.50											
26	EL2M262B00	EL2M262G00	2.70											
28	EL2M282B00	EL2M282G00	2.90											
30	EL2M302B00	EL2M302G00	3.10											
32	EL2M322B00	EL2M322G00	3.30											
34	EL2M342B00	EL2M342G00	3.50											
36	EL2M362B00	EL2M362G00	3.70											
38	EL2M382B00	EL2M382G00	3.90											
40	EL2M402B00	EL2M402G00	4.10											
42	EL2M422B00	EL2M422G00	4.30											
44	EL2M442B00	EL2M442G00	4.50											
<b>EL3M Assemblies</b>														
12	EL3M122B00	EL3M122G00	.90											
15	EL3M152B00	EL3M152G00	1.10											
18	EL3M182B00	EL3M182G00	1.30											
21	EL3M212B00	EL3M212G00	1.50											
24	EL3M242B00	EL3M242G00	1.70											
27	EL3M272B00	EL3M272G00	1.90											
30	EL3M302B00	EL3M302G00	2.10											
33	EL3M332B00	EL3M332G00	2.30											
36	EL3M362B00	EL3M362G00	2.50											
39	EL3M392B00	EL3M392G00	2.70											
42	EL3M422B00	EL3M422G00	2.90											
45	EL3M452B00	EL3M452G00	3.10											
48	EL3M482B00	EL3M482G00	3.30											
51	EL3M512B00	EL3M512G00	3.50											
54	EL3M542B00	EL3M542G00	3.70											
57	EL3M572B00	EL3M572G00	3.90											
60	EL3M602B00	EL3M602G00	4.10											
63	EL3M632B00	EL3M632G00	4.30											
66	EL3M662B00	EL3M662G00	4.50											

### SPECIFICATIONS:

**Current Rating:** 20A  
**Operating Voltage:** 300V  
**Insulation Resistance:** >10<sup>5</sup> Megohms  
**Dielectric Withstanding:** <3000V  
**Wire Pullout Force:**  
 Per UL 486E, Section 14

### MATERIALS:

**Housing:** PA, UL 94V-0, black or green  
**Contact:** Copper alloy, tin-lead finish  
**Clamp Screw:** Copper alloy, nickel finish  
**Wire clamp:** Copper alloy, nickel finish

### INSTALLATION:

**Wire Range:** 12-30 AWG  
**Wire Strip Length:** .310"  
**Recommended Tightening Torque:**  
 7 lb-in. (0.79N-m)  
**Hole Diameter:** .051 min.