

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。


## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

## Table of Contents


### **P-CONN™ SIDEWINDER™** Screw-on Wire Connectors (Hex Style)

|                                  |        |
|----------------------------------|--------|
| Features and benefits .....      | Page 2 |
| Wire ranges and capacities ..... | Page 3 |



### **P-CONN™ HAWK™** Screw-on Wire Connectors (Wing Style)

|                                  |        |
|----------------------------------|--------|
| Features and benefits .....      | Page 4 |
| Wire ranges and capacities ..... | Page 5 |




### **P-CONN™ SHARK™** Screw-on Wire Connectors (Fin Style)

|                                  |        |
|----------------------------------|--------|
| Features and benefits .....      | Page 6 |
| Wire ranges and capacities ..... | Page 7 |



### **P-CONN™ PYTHON™** Screw-on Wire Connectors (Nut Style)

|                                  |        |
|----------------------------------|--------|
| Features and benefits .....      | Page 8 |
| Wire ranges and capacities ..... | Page 9 |



### **Capacity Comparisons**

|                                      |         |
|--------------------------------------|---------|
| Fin, Hex and Wing Style Tables ..... | Page 10 |
| Nut Style Table .....                | Page 11 |
| Wire Combination Table .....         | Page 11 |


|   |         |
|---|---------|
| <b>PICK-A-P-CONN™</b> Assortment Kits ..... | Page 12 |
|---|---------|

|   |         |
|---|---------|
| <b>QUICK-SPIN™</b> Twist-on Tools ..... | Page 12 |
|---|---------|


|   |         |
|---|---------|
| <b>PAN-TERM®</b> Crimp-on Wire Joints ..... | Page 12 |
|---|---------|



## Hex Style . . . Features



- ▲ Ribbed design for easy, comfortable installation
- ▲ Two sizes cover full range of wire sizes and combinations
- ▲ Funnel entry guides wires into connector
- ▲ Tough nylon housing resists breakage
- ▲ Excellent electrical insulation
- ▲ Standard industry colors



### SIDEWINDER™ Hex Style

These high-quality connectors provide an expanded wire range capability which can reduce inventory. Twist them on by hand, or utilize a nut driver on the hexagonal shaped head for easy installation. They are UL and CSA approved and designed for optimum performance in a variety of applications.




| Insulation Color | Panduit Part Number | Wire Range                 |                           | CMA Range |        | Pkg. Qty./ Type    |
|------------------|---------------------|----------------------------|---------------------------|-----------|--------|--------------------|
|                  |                     | Min.                       | Max.                      | Min.      | Max.   |                    |
| Tan              | PH1-C<br>PH1-D      | (3) #22 AWG                | (5) #12 AWG               | 1,920     | 35,250 | 100 Box<br>500 Bag |
| Gray             | PH2-L<br>PH2-TL     | (1) #12 AWG<br>(1) #14 AWG | (2) #8 AWG<br>(2) #12 AWG | 9,060     | 46,080 | 50 Box<br>250 Bag  |

### SIDEWINDER™ Capacity Chart

| CMA* | WIRE COMBINATIONS   |       |       |       |       |       |       |       |       |       |       |       |       |
|------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|      | 3 #22   | 3 #20 | 2 #18 | 2 #14 | 2 #12 | 1 #12 | 3 #12 | 3 #10 | 2 #8  | 4 #10 | 2 #6  | 2 #6  | 1 #10 |
|      | 1920  | 3060  | 3240  | 8220  | 13060 | 16850 | 19590 | 30960 | 33020 | 41280 | 52540 | 52540 | 62860 |
| PH1  | [Bar chart showing capacity for PH1 connector across all wire combinations] |       |       |       |       |       |       |       |       |       |       |       |       |
| PH2  | [Bar chart showing capacity for PH2 connector across all wire combinations] |       |       |       |       |       |       |       |       |       |       |       |       |

\* CMA = Circular Mil Area (See Wire Combination Table, Page 10)





#### Hex Shaped Head

Makes twisting multiple wires quick and easy with the use of a nut driver.



**HAWK™ Wing Style . . . Features**



- ▲ Ribbed grip surface
- ▲ Three convenient sizes, plus grounding wire connectors
- ▲ Funnel entry simplifies installation
- ▲ Tough nylon housing provides excellent electrical insulating properties
- ▲ Available in yellow, red, blue and green

**PRODUCT MARKINGS**  
easily identify wire  
range and approvals




**EXPANDING SQUARE WIRE SPRING**  
ensures low resistance

**FUNNEL ENTRY**  
guides wires into connector

**DEEP SKIRT**  
protects against  
flashover and shorts

**OFFSET WINGS**  
offers large  
gripping services

**TOUGH NYLON  
HOUSING** offers  
excellent insulation  
properties




## HAWK™ Wing Style

These screw-on connectors are both economical and reusable. The wide wire range of each connector minimizes inventory requirements. They save installation time because they do not require any pre-twisting of wires.



| Insulation Color | Panduit Part Number | Wire Range                 |                           | CMA Range |        | Pkg. Qty./ Type    |
|------------------|---------------------|----------------------------|---------------------------|-----------|--------|--------------------|
|                  |                     | Min.                       | Max.                      | Min.      | Max.   |                    |
| Yellow           | P1-C<br>P1-D        | (3) #22 AWG                | (3) #12 AWG               | 1,920     | 19,590 | 100 Box<br>500 Bag |
| Red              | P2-C<br>P2-D        | (3) #22 AWG                | (3) #12 AWG<br>(1) #8 AWG | 1,920     | 36,100 | 100 Box<br>500 Bag |
| Blue             | P4-L<br>P4-TL       | (1) #12 AWG<br>(1) #14 AWG | (2) #6 AWG<br>(1) #10 AWG | 10,640    | 62,860 | 50 Box<br>250 Bag  |
| Green            | P2G-C<br>P2G-D      | (2) #14 AWG                | (5) # 12 AWG              | 8,220     | 32,650 | 100 Box<br>500 Box |

Color-coded Green for quick identification as grounding connector.



How grounding wire connector is typically used . . .

- A. System grounding wire
- B. System grounding wire
- C. "Through" wire between device and box ground




## HAWK™ Capacity Chart


| CMA* | WIRE COMBINATIONS |       |             |            |                |       |       |       |       |       |               |
|------|-------------------|-------|-------------|------------|----------------|-------|-------|-------|-------|-------|---------------|
|      | 3 #22             | 2 #18 | 2 #14       | 2 #12      | 1 #10<br>1 #12 | 3 #12 | 3 #10 | 2 #8  | 4 #10 | 2 #6  | 2 #6<br>1 #10 |
|      | 1920              | 3240  | 8220        | 13060      | 16850          | 19590 | 30960 | 33020 | 41280 | 52540 | 62860         |
| P1   | [Yellow bar]      |       |             |            |                |       |       |       |       |       |               |
| P2   | [Red bar]         |       |             |            |                |       |       |       |       |       |               |
| P4   |                   |       |             | [Blue bar] |                |       |       |       |       |       |               |
| P2G  |                   |       | [Green bar] |            |                |       |       |       |       |       |               |

\* CMA = Circular Mil Area (See Wire Combination Table, Page 10)

**SHARK™ Fin Style . . . Features**



- ▲ Large grip area for easy-on-the-fingers installation
- ▲ Three sizes cover full range of wire sizes and combinations
- ▲ Funnel entry guides wires into connector
- ▲ Tough nylon housing resists breakage
- ▲ Excellent electrical insulation
- ▲ Standard industry colors





## SHARK™ Fin Style


These high-quality wire connectors provide an expanded wire range capability and are fully UL and CSA Approved. They are designed for optimum performance in a variety of applications including manufacturing, maintenance and new construction.



| Insulation Color | Panduit Part Number | Wire Range                 |                          | CMA Range |        | Pkg. Qty./ Type    |
|------------------|---------------------|----------------------------|--------------------------|-----------|--------|--------------------|
|                  |                     | Min.                       | Max.                     | Min.      | Max.   |                    |
| Yellow           | PF1-C<br>PF1-D      | (3) #22 AWG                | (3) #12 AWG              | 1,920     | 19,590 | 100 Box<br>500 Bag |
| Red              | PF2-C<br>PF2-D      | (3) #22 AWG                | (5) #12 AWG              | 1,920     | 32,650 | 100 Box<br>500 Bag |
| Blue             | PF4-L<br>PF4-TL     | (1) #12 AWG<br>(1) #14 AWG | (1) #6 AWG<br>(2) #8 AWG | 10,640    | 59,290 | 50 Box<br>250 Bag  |


|       |                  |             |             |       |        |                    |
|-------|------------------|-------------|-------------|-------|--------|--------------------|
| Green | PF2G-C<br>PF2G-D | (2) #14 AWG | (5) #12 AWG | 8,220 | 32,650 | 100 Box<br>500 Box |
|-------|------------------|-------------|-------------|-------|--------|--------------------|

Color-coded Green for quick identification as grounding connector.



How grounding wire connector is typically used . . .

- A. System grounding wire
- B. System grounding wire
- C. "Through" wire between device and box ground



## SHARK™ Capacity Chart

| CMA* | WIRE COMBINATIONS |       |       |             |       |       |       |       |       |       |       |       |       |
|------|-------------------|-------|-------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|      | 3 #22             | 3 #20 | 2 #18 | 2 #14       | 2 #12 | 1 #12 | 3 #12 | 3 #10 | 2 #8  | 4 #10 | 2 #6  | 2 #6  | 1 #10 |
|      | 1920              | 3060  | 3240  | 8220        | 13060 | 16850 | 19590 | 30960 | 33020 | 41280 | 52540 | 62860 |       |
| PF1  | [Yellow bar]      |       |       |             |       |       |       |       |       |       |       |       |       |
| PF2  | [Red bar]         |       |       |             |       |       |       |       |       |       |       |       |       |
| PF4  |                   |       |       | [Blue bar]  |       |       |       |       |       |       |       |       |       |
| PF2G |                   |       |       | [Green bar] |       |       |       |       |       |       |       |       |       |

\* CMA = Circular Mil Area (See Wire Combination Table, Page 10)




**PYTHON™ Nut Style . . . Features**



- ▲ Space-saving design
- ▲ Deep ribs for improved grip
- ▲ Four convenient sizes plus high-temperature style
- ▲ Tough nylon housing
- ▲ Available in blue, orange, yellow, red and black

**REUSABLE** for greater convenience and economy



**PRODUCT MARKINGS** easily identify wire range and approvals



**EXPANDING "LIVE" SPRING** for a large wire range capacity

**DEEP CONTOURED RIBS** improve grip and comfort

**TOUGH NYLON HOUSING** offers excellent insulation properties

**DEEP SKIRT** protects against flashover and shorts

**FUNNEL ENTRY** guides wires into connector

**Typical Applications**



Fluorescent lighting fixtures...commercial, industrial.



Home appliances... lamps, washing machines, refrigerators.

## PYTHON™ Nut Style

These high-quality wire connectors provide an expanded wire range capability and are fully UL and CSA Approved. They are designed for optimum performance in a variety of applications including manufacturing, maintenance and new construction.



### Temperature 105°C (221°F)

| Insulation Color | Panduit Part Number       | Wire Range  |             | CMA Range |        | Pkg. Qty./ Type                  |
|------------------|---------------------------|-------------|-------------|-----------|--------|----------------------------------|
|                  |                           | Min.        | Max.        | Min.      | Max.   |                                  |
| Blue             | P72-C<br>P72-D<br>P72-10M | (2) #22 AWG | (3) #16 AWG | 1,280     | 7,740  | 100 Box<br>500 Bag<br>10,000 Keg |
| Orange           | P73-C<br>P73-D<br>P73-10M | (3) #20 AWG | (4) #16 AWG | 3,060     | 10,320 | 100 Box<br>500 Bag<br>10,000 Keg |
| Yellow           | P74-C<br>P74-D<br>P74-10M | (2) #18 AWG | (3) #12 AWG | 3,240     | 19,590 | 100 Box<br>500 Bag<br>10,000 Keg |
| Red              | P76-C<br>P76-TL<br>P76-5M | (4) #18 AWG | (4) #12 AWG | 6,480     | 26,120 | 100 Box<br>250 Bag<br>5,000 Keg  |

### High Temperature 150°C (302°F)

For High Temp. applications, such as high intensity discharge lighting (HID)

|       |                      |             |             |       |        |                       |
|-------|----------------------|-------------|-------------|-------|--------|-----------------------|
| Black | P72HT-D<br>P72HT-10M | (2) #22 AWG | (3) #16 AWG | 1,280 | 7,740  | 500 Bag<br>10,000 Keg |
|       | P73HT-D<br>P73HT-10M | (3) #20 AWG | (4) #16 AWG | 3,060 | 10,320 | 500 Bag<br>10,000 Keg |
|       | P74HT-D<br>P74HT-10M | (2) #18 AWG | (3) #12 AWG | 3,240 | 19,590 | 500 Bag<br>10,000 Keg |
|       | P76HT-TL<br>P76HT-5M | (4) #18 AWG | (4) #12 AWG | 6,480 | 26,120 | 250 Bag<br>5,000 Keg  |

## PYTHON™ Capacity Chart

| CMA*         | WIRE COMBINATIONS |       |       |       |       |       |       |       |       |  |
|--------------|-------------------|-------|-------|-------|-------|-------|-------|-------|-------|--|
|              | 2 #22             | 3 #22 | 2 #16 | 3 #16 | 4 #16 | 3 #14 | 4 #14 | 3 #12 | 5 #12 |  |
|              | 1280              | 1920  | 5160  | 7740  | 10320 | 12330 | 16440 | 19590 | 32650 |  |
| P72<br>P72HT | ■                 |       |       |       |       |       |       |       |       |  |
| P73<br>P73HT |                   | ■     |       |       |       |       |       |       |       |  |
| P74<br>P74HT |                   | ■     |       |       |       |       |       |       |       |  |
| P76<br>P76HT |                   |       |       | ■     |       |       |       |       |       |  |

\* CMA = Circular Mil Area (See Wire Combination Table, page 11)

# PANDUIT® P-CONN™ SCREW-ON WIRE CONNECTORS



## WIRE COMBINATION COMPARISONS

| FIN STYLE SCREW-ON CONNECTORS—WIRE COMBINATIONS                               |                                   |             |      |       |       |       |                |  |       |       |       |       |       |               |
|---|-----------------------------------|-------------|------|-------|-------|-------|----------------|--|-------|-------|-------|-------|-------|---------------|
| CMA   | 3 #22                             | 3 #20 2 #18 |      | 2 #14 | 2 #12 |       | 1 #10<br>1 #12 |  | 3 #12 | 3 #10 | 2 #8  | 4 #10 | 2 #6  | 2 #6<br>1 #10 |
|   | 1920                              | 3060        | 3240 | 8220  | 13060 | 16850 | 19590          |  |       | 30960 | 33020 | 41280 | 52540 | 62860         |
| PF1 (PANDUIT)<br>B1 (Buchanan)<br>SCOTCHLOK-Y (3M)<br>G1 (GB)<br>10-220 (T&B) | [Green bar across 3 #22 to 3 #12] |             |      |       |       |       |                |  |       |       |       |       |       |               |
| PF2 (PANDUIT)<br>B2 (Buchanan)<br>SCOTCHLOK-R (3M)<br>G2 (GB)<br>10-228 (T&B) | [Green bar across 3 #22 to 2 #8]  |             |      |       |       |       |                |  |       |       |       |       |       |               |
| PF4 (PANDUIT)<br>B4 (Buchanan)<br>SCOTCHLOK-B (3M)<br>10-166 (T&B)            | [Green bar across 2 #12 to 2 #6]  |             |      |       |       |       |                |  |       |       |       |       |       |               |
| PF2G (PANDUIT)<br>BGR (Buchanan)  | [Green bar across 2 #14 to 2 #8]  |             |      |       |       |       |                |  |       |       |       |       |       |               |

| HEX STYLE AND WING STYLE SCREW-ON CONNECTORS—WIRE COMBINATIONS  |                                   |             |      |       |       |       |                |  |       |       |       |       |       |               |
|---|-----------------------------------|-------------|------|-------|-------|-------|----------------|--|-------|-------|-------|-------|-------|---------------|
| CMA   | 3 #22                             | 3 #20 2 #18 |      | 2 #14 | 2 #12 |       | 1 #10<br>1 #12 |  | 3 #12 | 3 #10 | 2 #8  | 4 #10 | 2 #6  | 2 #6<br>1 #10 |
|   | 1920                              | 3060        | 3240 | 8220  | 13060 | 16850 | 19590          |  |       | 30960 | 33020 | 41280 | 52540 | 62860         |
| P1 (PANDUIT)<br>451* (Ideal)<br>W1 (Buchanan)<br>312 RANGER (3M)<br>O/B (3M)<br>84 (GB)<br>HI-Y (T&B) | [Green bar across 3 #22 to 3 #12] |             |      |       |       |       |                |  |       |       |       |       |       |               |
| PH1 (PANDUIT)<br>341* (Ideal)<br>H1 (GB)<br>212 HYFLEX (SM)   | [Green bar across 3 #22 to 2 #8]  |             |      |       |       |       |                |  |       |       |       |       |       |               |
| P2 (PANDUIT)<br>452* (Ideal)<br>W2 (Buchanan)<br>512 RANGER (3M)<br>R/Y (3M)<br>86 (GB)<br>HI-R (T&B) | [Green bar across 3 #22 to 2 #6]  |             |      |       |       |       |                |  |       |       |       |       |       |               |
| PH2 (PANDUIT)<br>342* (Ideal)<br>H2 (GB)  | [Green bar across 2 #12 to 2 #6]  |             |      |       |       |       |                |  |       |       |       |       |       |               |
| P4 (PANDUIT)<br>454* (Ideal)<br>W4 (Buchanan)<br>B/G (3M)<br>89 (GB)<br>HI-B (T&B)                    | [Green bar across 2 #12 to 2 #6]  |             |      |       |       |       |                |  |       |       |       |       |       |               |
| P2G (PANDUIT)<br>92* (Ideal)<br>WGR (Buchanan)<br>512G (3M)<br>95 (GB)                                | [Green bar across 2 #14 to 2 #8]  |             |      |       |       |       |                |  |       |       |       |       |       |               |

\* Registered Trademark of Ideal Industries Inc.

| NUT STYLE SCREW-ON CONNECTORS—WIRE COMBINATIONS  |       |      |       |  |       |  |       |      |       |  |       |       |       |  |       |  |       |       |       |  |
|--|-------|------|-------|--|-------|--|-------|------|-------|--|-------|-------|-------|--|-------|--|-------|-------|-------|--|
| CMA  | 2 #22 |      | 3 #22 |  | 2 #16 |  | 3 #16 |      | 4 #16 |  | 3 #14 |       | 4 #14 |  | 3 #12 |  | 5 #12 |       |       |  |
|  | 1280  | 1920 |       |  | 5160  |  |       | 7740 |       |  | 10320 | 12330 |       |  | 16440 |  |       | 19590 | 32650 |  |
| 71B* (Ideal)<br>N1 (Buchanan)<br>H-29 (3M)<br>GB-1 (GB)<br>Hi-0 (T&B)                              |       |      |       |  |       |  |       |      |       |  |       |       |       |  |       |  |       |       |       |  |
| P72 (PANDUIT)<br>72B* (Ideal)<br>N2 (Buchanan)<br>H-30 (3M)<br>GB-2 (GB)<br>Hi-2 (T&B)             |       |      |       |  |       |  |       |      |       |  |       |       |       |  |       |  |       |       |       |  |
| P73 (PANDUIT)<br>73B* (Ideal)<br>N3 (Buchanan)<br>H-31 (3M)<br>O/B (3M)<br>GB-3 (GB)<br>Hi-3 (T&B) |       |      |       |  |       |  |       |      |       |  |       |       |       |  |       |  |       |       |       |  |
| P74 (PANDUIT)<br>74B* (Ideal)<br>N4 (Buchanan)<br>H-33 (3M)<br>GB-4 (GB)<br>Hi-4 (T&B)             |       |      |       |  |       |  |       |      |       |  |       |       |       |  |       |  |       |       |       |  |
| P76 (PANDUIT)<br>76B* (Ideal)<br>N6 (Buchanan)<br>H-35 (3M)<br>GB-6 (GB)<br>Hi-6 (T&B)             |       |      |       |  |       |  |       |      |       |  |       |       |       |  |       |  |       |       |       |  |

\* Registered Trademark of Ideal Industries Inc.

## Wire Combination Table

For calculating total Circular Mil Area

**Directions:** Locate desired size of wire(s) in left column. Read across to find Circular Mil Area for the total number of wires per each wire size. Add these amounts together to calculate the total Circular Mil Area for desired wire combination.

Example: (1)#14 + (1)#12 = 10,640.  
(Use this table in conjunction with the wire range charts on pages 3, 5, 7 and 9 or the specific listed CMA range shown for each part.)

| Wire Size | Circular Mil Area per number of wires |         |         |         |         |
|-----------|---------------------------------------|---------|---------|---------|---------|
|           | 1 Wire                                | 2 Wires | 3 Wires | 4 Wires | 5 Wires |
| #22 AWG   | 640                                   | 1280    | 1920    | 2560    | 3200    |
| #20 AWG   | 1020                                  | 2040    | 3060    | 4080    | 5100    |
| #18 AWG   | 1620                                  | 3240    | 4860    | 6480    | 8100    |
| #16 AWG   | 2580                                  | 5160    | 7740    | 10320   | 12900   |
| #14 AWG   | 4110                                  | 8220    | 12330   | 16440   | 20550   |
| #12 AWG   | 6530                                  | 13060   | 19590   | 26120   | 32650   |
| #10 AWG   | 10380                                 | 20760   | 31140   | 41520   | 51900   |
| #8 AWG    | 16510                                 |         |         |         |         |

Consult product package or factory for UL Listed and CSA Certified combinations.



# PANDUIT® P-CONN™ SCREW-ON WIRE CONNECTORS


## "Pick-A-P-CONN™" Assortment Kits



A collection of the most popular wire connectors packaged in a sturdy, reusable plastic box.

| Part Number   | Description            |
|---------------|------------------------|
| KP-305        | Kit includes:          |
|               | 1 Reusable plastic box |
|               | 100 Yellow P1          |
|               | 100 Orange P73         |
|               | 75 Red P2              |
|               | 15 Blue P4             |
| 2 Quick-Spins |                        |
| KP-305S       | Kit includes:          |
|               | 100 Yellow PF1         |
|               | 100 Orange P73         |
|               | 75 Red PF2             |
|               | 15 Blue PF4            |
|               | 2 Quick-Spins          |

## "QUICK-SPIN" Installation Tools



Use these handy tools for quick and easy installation of screw-on and nut style connectors. Fits 1/4" drill (not included).

| Part Number | For use with Part Number |                   |
|-------------|--------------------------|-------------------|
| PQS1        | P1, P2                   | HAWK™ Wing Style  |
| PQS2        | P72, P73, P72HT, P73HT   | PYTHON™ Nut Style |
| PQS3        | P74, P76, P74HT, P76HT   | PYTHON™ Nut Style |
| PQS4        | PF1, PF2                 | SHARK™ Fin Style  |

## Crimp Joints



Solderless crimp - preferred for applications subject to vibration.

| Panduit Part Number    | Insul. Color | Wire Range  |             | CMA Range |        | Std. Pkg. | Bulk Pkg. |
|------------------------|--------------|-------------|-------------|-----------|--------|-----------|-----------|
|                        |              | Min.        | Max.        | Min.      | Max.   |           |           |
| <b>Nylon Insulated</b> |              |             |             |           |        |           |           |
| JN224-318-C            | Red          | (2) #24 AWG | (3) #18 AWG | 808       | 5,160  | 100       | 1000      |
| JN218-216-C            | Clear        | (2) #22 AWG | (2) #16 AWG | 1,284     | 5,160  | 100       | 1000      |
| JN418-212-C            | Clear        | (4) #18 AWG | (2) #12 AWG | 6,480     | 14,750 | 100       | 500       |
| JN314-412-C            | Clear        | (3) #14 AWG | (4) #12 AWG | 10,320    | 26,120 | 100       | 1000      |
| <b>Non-Insulated</b>   |              |             |             |           |        |           |           |
| J214-312-T             | -            | (2) #14 AWG | (3) #12 AWG | 5,760     | 19,590 | 200       | 2000      |
| J318-412-T             | -            | (3) #18 AWG | (4) #12 AWG | 4,860     | 27,330 | 200       | 2000      |
| J216-410-L             | -            | (2) #16 AWG | (4) #10 AWG | 5,160     | 41,600 | 50        | 500       |



\*Except JN314-412, J216-410

Our products are warranted to be free from defects in material and workmanship at the time of sale but our obligation under this warranty is limited to the replacement of any product proved to be defective within 6 months (for product) or 90 days (for tools) from the date of delivery. Tool warranty is void if Panduit tools are modified, altered or misused in any way. Use of Panduit tooling with any product other than the specified Panduit products for which the tool was designed, constitutes misuse. Before using, user shall determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection herewith.

This warranty is made in lieu of and excludes all other warranties expressed or implied. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR

PARTICULAR USE ARE SPECIFICALLY EXCLUDED. Neither seller nor manufacturer shall be liable for any other injury, loss or damage, whether direct or consequential, arising out of the use of, or the inability to use, the product.

The information contained in this literature is based on our experience to date and is believed to be reliable. It is intended as a guide for use by persons having technical skill at their own discretion and risk. We do not guarantee favorable results or assume any liability in connection with its use. Dimensions contained herein are for reference purposes only. For specific dimensional requirements consult the factory. This publication is not to be taken as a license to operate under, or a recommendation to infringe any existing patents. This supersedes and voids all previous literature, etc.



Panduit Corp.  
17301 Ridgeland Avenue  
Tinley Park, IL 60477-3091  
Phone: 888-506-5400, Ext. 2241  
708-532-1800  
FAX: 815-485-5839  
Email: info@panduit.com  
Website: www.panduit.com

Panduit Canada  
Div. of Panduit Corp.  
140 Amber Street  
Markham, Ontario L3R 3J8  
Phone: 800-387-9689  
FAX: 905-475-6998



**For Pricing and Further Information –  
Contact your local authorized  
PANDUIT Distributor or Sales Office**

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

SA101N146D-NL  
Printed in U.S.A.