

阅读申明


- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

SMD TYPE HIGH FREQUENCY CRYSTAL OSCILLATOR

SG-615 series



Actual size


Specifications (Characteristics)

Item	Symbol	SG-615P	SG-615PTJ	SG-615PH	Remarks
		Specifications			
Output frequency range	f_0	1.0250MHz to 26.0000MHz	26.0001MHz to 66.6667MHz		
Power source voltage	MAX. supply voltage	V_{DD-GND}			
	Operating voltage	V_{DD}			-0.3V to +7.0V 5.0V±0.5V
Temperature range	Storage temperature	T_{STG}			Stored as bare product after unpacking
	Operating temperature	T_{OPR}			
Soldering condition	T_{SOL}	Twice at under 260°C within 10sec. or under 230°C within 3min.			
Frequency stability	$\Delta f/f_0$	B : ±50ppm C : ±100ppm			B type is possible up to 55MHz
Current consumption	I_{OP}	23mA MAX.	35mA MAX.		No load condition
Duty	C-MOS level	40% to 60%	—	40% to 60%	C-MOS load : 1/2 V_{DD} TTL load : 1.4V
	TTL level	45% to 55%		—	
Output voltage	V_{OH}	$V_{DD} - 0.4V$ MIN.	2.4V MIN.	$V_{DD} - 0.4V$ MIN.	
	(I_{OH})	-400µA		-4mA	
	V_{OL}	0.4V MAX.			
	(I_{OL})	16mA	8mA	4mA	
Output load condition (fan out)	C-MOS	CL	50pF MAX.	50pF MAX.	
	TTL	N	10TTL MAX.	5TTL MAX.	
Output enable/disable input voltage	V_{IH}	2.0V MIN.	3.5V MIN.	2.0V MIN.	$I_{IH} = 1\mu A$ MAX. (OE= V_{DD}) $I_{IL} = -100\mu A$ MIN. (OE=GND) $I_{IL} = -500\mu A$ MIN. (OE=GND) PTJ
	V_{IL}	0.8V MAX.	1.5V MAX.	0.8V MAX.	
Output disable current	I_{OE}	12mA MAX.	28mA MAX.	20mA MAX.	OE=GND
Output rise time	C-MOS level	8nsec. MAX.	—	7nsec. MAX.	C-MOS load : 20% → 80% V_{DD} TTL load : 0.4V → 2.4V
	TTL level		5nsec. MAX.	—	
Output fall time	C-MOS level	5nsec. MAX.	—	7nsec. MAX.	C-MOS load : 80% → 20% V_{DD} TTL load : 2.4V → 0.4V
	TTL level		5nsec. MAX.	—	
Oscillation start up time	t_{OSC}	4msec. MAX.	10msec. MAX.		Time at 4.5V to be 0sec.
Aging	f_a	±5ppm/year MAX.			$T_a = 25^\circ C$, $V_{DD} = 5V$, first year
Shock resistance	S.R.	±20ppm MAX.			Drop test of 3 times on a hard board from 75cm height or excitation test with 3000G × 0.3ms × 1/2sine wave in 3 directions

Note: • Unless otherwise stated, characteristics (specifications) shown in the above table are based on the rated operating temperature and voltage condition.
• External by-pass capacitor is recommended.


External Dimensions

(Unit : mm)



Recommended soldering pattern

(Unit : mm)



■ Features

- High density mounting type SMD.
- Designed for universal purpose with heat-resisting cylindrical type AT cut quartz crystal and allowing almost the same soldering temperature as SMD IC.
- Cylindrical type AT quartz crystal built-in, thus assuring high reliability.
- Provided with output enable function.
- Low current consumption.

■ Specifications (Characteristics)

Item	Symbol	SG-615 PCV		Remarks
		Specifications		
Output frequency range	f ₀	40.0000MHz to 80.0000MHz		V _{DD} =2.7V to 5.5V
		40.0000MHz to 125.0000MHz		V _{DD} =4.5V to 5.5V
Power source voltage	MAX. supply voltage	V _{DD} -GND	-0.5V to +7.0V	
	Operating voltage	V _{DD}	2.7V to 5.5V	
Temperature range	Storage temperature	T _{STG}	-55°C to +125°C	Stored as bare product after unpacking
	Operating temperature	T _{OPR}	-10°C to +70°C	
Soldering condition	T _{SOL}	Twice at under 260°C within 10sec. or under 230°C within 3min.		
Frequency stability	Δf/f ₀	C : ±100ppm		-10°C to +70°C, V _{DD} :2.7V to 5.5V
Current consumption	I _{OP}	50mA MAX.		No load condition
Duty	T _W /T	35% to 60%		1/2 V _{DD}
Output voltage	V _{OH}	V _{DD} -0.5V		
	(I _{OH})	-16mA		
	V _{OL}	0.4V MAX.		
	(I _{OL})	16mA		
Output load condition (fan out)	CL	25pF MAX.		V _{DD} =4.5V to 5.5V
		15pF MAX.		V _{DD} =2.7V to 4.5V
Output enable/disable input voltage	V _{IH}	0.7V _{DD} MIN.		
	V _{IL}	0.2V _{DD} MAX.		
Output disable current	I _{OE}	27mA MAX.		OE=GND
Output rise time	T _{TLH}	4nsec.		20% → 80% V _{DD}
Output fall time	T _{THL}			80% → 20% V _{DD}
Oscillation start up time	t _{OSC}	10msec. MAX.		Time at 2.7V to be 0sec.
Aging	fa	±5ppm/year MAX.		T _a =25°C, first year
Shock resistance	S.R.	±20ppm MAX.		Drop test of 3 times on a hard board from 75cm height or excitation test with 3000G × 0.3ms × 1/2sine wave in 3 directions

Note: • Unless otherwise stated, characteristics (specifications) shown in the above table are based on the rated operating temperature and voltage condition.
 • External by-pass capacitor is recommended.

■ Frequency table

Model	Frequency	1MHz	26MHz	40MHz	67MHz	125MHz
SG-615P		—————				
SG-615PTJ			—————			
SG-615PH			—————			
SG-615PCV				—————		