

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



VOLTAGE-CONTROLLED CRYSTAL OSCILLATOR (VCXO)

VG-4231CB VG-4531CB

- Frequency range : 1 MHz to 80 MHz
- Supply voltage : 3.3 V
- Absolute pull range : $\pm 50 \times 10^{-6}$
- External dimensions: 5.0 × 3.2 × 1.2 t (mm) Typ.
- Function : Output enable(OE)



Product Number (please contact us)
 VG-4231CB : X1G002861xxxx00
 VG-4531CB : X1G002881xxxx00



Actual size



Specifications (characteristics)

Item	Symbol	Specifications		Remarks
		VG-4231CB	VG-4531CB	
Output frequency range	f _o	1.000 MHz to 60.000 MHz	60.001 MHz to 80.000 MHz	Please contact us for inquiries regarding available frequencies.
Supply voltage	V _{cc}	3.3 V ± 0.165 V		
Storage temperature range	T _{stg}	-55 °C to +125 °C		Store as bare product after unpacking
Operating temperature range	T _{use}	As per blow table.		
Frequency tolerance	f _{tol}	$\pm 50 \times 10^{-6}$ Max.		Includes frequency aging (20 years)
Current consumption	I _{cc}	10 mA Max.	15 mA Max.	No load condition.
Absolute pull range	APR	$\pm 50 \times 10^{-6}$ Min.		V _c = 1.65 V ± 1.5 V
Input resistance	R _{in}	10 M Ω Min.		DC level
Frequency change polarity	—	Positive slope		V _c = 0.15 to 3.15 V
Symmetry	SYM	45 % to 55 %		50 % V _{cc} level
High output voltage	V _{OH}	V _{cc} -0.4 V Min.		I _{OH} = -0.8 mA
Low output voltage	V _{OL}	0.4 V Max.		I _{OL} = 3.2 mA
Output load condition (CMOS)	L _{CMOS}	15 pF Max.		
Output enable / disable input voltage	V _{IH}	70 % V _{cc} Min.		V _{IH} or OPEN : Enable
	V _{IL}	30 % V _{cc} Max.		V _{IL} or GND : Disable
Rise time / Fall time	t _r / t _f	6 ns Max.		20 % V _{cc} to 80 % V _{cc} level
Start-up time	t _{str}	10 ms Max.		Time at minimum supply voltage to be 0 s
Frequency aging	f _{aging}	This is included frequency tolerance		+25 °C, V _{cc} =3.3 V, 20 years

* Please keep V_c pin open or ground while powering up V_{cc}.


Temperature range

VG-4231CB	Operating temperature range
GGCZ	-40 °C ~ +85 °C
JGCZ	-20 °C ~ +70 °C
KGCZ	0 °C ~ +70 °C

VG-4531CB	Operating temperature range
GGCT	-40 °C ~ +85 °C
JGCT	-20 °C ~ +70 °C
KGCT	0 °C ~ +70 °C

External dimensions

(Unit :mm)



Footprint (Recommended)

(Unit :mm)

